

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Avenue, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-039-29588 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.
--	---	--

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. ☐ WELL OVER BACK RESVR. ☐ OTHER ☐	7. Lease Name or Unit Agreement Name EL POSO																																							
2. Name of Operator BLUE DOLPHIN PRODUCTION, LLC.	8. Well No. #3																																							
3. Address of Operator 609 S. KELLY SUITE F-1 EDMOND, OK. 73003	9. Pool name or Wildcat WC 28N 1E EL POSO GREENHORN																																							
4. Well Location Unit Letter <u>N</u> : <u>480</u> Feet From The <u>SOUTH</u> Line and <u>2105</u> Feet From The <u>WEST</u> Line Section <u>11</u> Township <u>28N</u> Range <u>1E</u> NMPM RIO ARRIBA County																																								
10. Date Spudded 10-03-05	11. Date T.D. Reached 10-06-05	12. Date Compl. (Ready to Prod.) 11-20-05	13. Elevations (DF& RKB, RT, GR, etc.) 7250' GL	14. Elev. Casinghead 7250' GL																																				
15. Total Depth 1731'	16. Plug Back T.D. 1670'	17. If Multiple Compl. How Many Zones? N/A	18. Intervals Drilled By Rotary Tools SURF---TD. Cable Tools	19. Producing Interval(s), of this completion - Top, Bottom, Name GREENHORN 1534'-1554'																																				
21. Type Electric and Other Logs Run GR-CAL-FDC-CNL-IES-MICROLOG			20. Was Directional Survey Made NO																																					
22. Was Well Cored NO			23. CASING RECORD (Report all strings set in well) <table border="1" style="width:100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>CASING SIZE</th> <th>WEIGHT LB./FT.</th> <th>DEPTH SET</th> <th>HOLE SIZE</th> <th>CEMENTING RECORD</th> <th>AMOUNT PULLED</th> </tr> </thead> <tbody> <tr> <td>8-5/8"</td> <td>20.0#</td> <td>178'</td> <td>12-1/4"</td> <td>150 sx</td> <td></td> </tr> <tr> <td>4-1/2"</td> <td>10.5#</td> <td>1722'</td> <td>6-1/4'</td> <td>155 sx</td> <td></td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>		CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED	8-5/8"	20.0#	178'	12-1/4"	150 sx		4-1/2"	10.5#	1722'	6-1/4'	155 sx																			
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED																																			
8-5/8"	20.0#	178'	12-1/4"	150 sx																																				
4-1/2"	10.5#	1722'	6-1/4'	155 sx																																				
24. LINER RECORD <table border="1" style="width:100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>SIZE</th> <th>TOP</th> <th>BOTTOM</th> <th>SACKS CEMENT</th> <th>SCREEN</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>			SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN											25. TUBING RECORD <table border="1" style="width:100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>SIZE</th> <th>DEPTH SET</th> <th>PACKER SET</th> </tr> </thead> <tbody> <tr> <td>2-3/8"</td> <td>1532'</td> <td> </td> </tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>		SIZE	DEPTH SET	PACKER SET	2-3/8"	1532'																
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN																																				
SIZE	DEPTH SET	PACKER SET																																						
2-3/8"	1532'																																							
26. Perforation record (interval, size, and number) 1534'-1554' @ 4 SPF 0.38" EHD TOTAL 80 HOLES			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> </thead> <tbody> <tr> <td>1534"-1554"</td> <td>41M GAL LINEAR GEL-90M # 16/30 SAND</td> </tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> </tbody> </table>		DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	1534"-1554"	41M GAL LINEAR GEL-90M # 16/30 SAND																																
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED																																							
1534"-1554"	41M GAL LINEAR GEL-90M # 16/30 SAND																																							
28 PRODUCTION																																								
Date First Production 11-20-05		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING—1-1/4" INSERT		Well Status (Prod. or Shut-in) PROD.																																				
Date of Test 11-20-05	Hours Tested 24 HRS	Choke Size N/A	Prod'n For Test Period Oil - Bbl. 23 Gas - MCF TSTM	Water - Bbl. 9 Gas - Oil Ratio N/A																																				
Flow Tubing Press. 150 PSI	Casing Pressure 70 PSI	Calculated 24-Hour Rate Oil - Bbl. 23 Gas - MCF TSTM	Water - Bbl. 9 Oil Gravity - API - (Corr.) 32																																					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) USED FOR FUEL				Test Witnessed By B.W. SALZMAN																																				
30. List Attachments NONE																																								
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief Signature <i>Bradley W. Salzman</i> E-mail Address brads@titusconsulting.net Printed Name BRADLEY W. SALZMAN Title AGENT Date 11-27-05																																								

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos <u>surface</u>	T. McCracken
T. San Andres	T. Simpson	T. Gallup <u>719'</u>	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn <u>1556'</u>	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....785'.....to.....870'.....
No. 2, from.....910'.....to.....980'.....
No. 3, from.....1220'.....to.....1250'.....
No. 4, from.....1512'.....to.....1556'.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
Surf	1222'	1222'	Mancos-sandstone and shale
1222	1303'	81'	Sanostee/Juana Lopez-ss and sh
1303	1512'	209'	Carlisle-shale
1512	1556'	44'	Greenhorn-limey shale and limestone
1556	TD	175'	Graneros – shale and sandstone