

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires: January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.


SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator **Lance Oil & Gas Company, Inc.**

3a. Address
P. O. Box 70, Kirtland, NM 87417

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
**435' FSL & 2050' FEL
Section 23, T29N - R14W, NMPM**



5. Lease Serial No.
14 - 20 - 603 - 2198 - A

6. If Indian, Allottee or Tribe Name
NAVAJO

7. If Unit or CA/Agreement, Name and/or No.
FARMINGTON NM

8. Well Name and No.
NV Rachelle 23 #4

9. API Well No.
30 - 045 - 31184

10. Field and Pool, or Exploratory Area
West Kutz PC & Basin Fruitland Coal

11. County or Parish, State
San Juan County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Spud & Csg Sundry
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleting horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleting in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

The NV Rachelle 23 #4 was spud at 13:30 hrs, 11/10/05. Drill 12-1/4" hole down to casing point at 162' KB. Circulate and condition hole. TOOH. Run 4 joints 8-5/8", 24 ppg, J-55, ST&C casing, land casing at 157' KB. Cement 8-5/8" casing with 150 sxs Standard H cement containing 1/4 #/sx flocele and 2% CaCL2 (Weight - 15.6 ppg, Yield - 1.18 ft3/sx and Water - 5.2 gals/sx). Displace cement with 8.3 bbls fresh water. Bumped plug to 550 psig at 19:00 hrs, 11/10/05. Plug held. Circulate 8 bbls cement to surface. WOC - 10 hrs. NU WH and BOP's.

Pressure test BOP's, blind rams and pipe rams to 250 psig (low) and 2,000 psig (high). Pressure test casing shoe to 1,000psig. Pressure tests - Good. Tag cement at 128' KB. Drill cement to 162' KB. Drill new 7-7/8" hole to total depth on 11/14/05. Driller's TD - 1354' KB. Logger's TD - 1,348' KB. Circ and condition hole. TOOH. Run 31 joints 5-1/2", 15.5 ppg, J-55, LT&C and land casing at 1,310' KB. Cement 5-1/2" casing with 150 sxs as follows: Lead - 70 sxs Halliburton Type III containing 2% Econolite, 2% Calseal, 6% BWC Salt, 0.3% Versaset, 1/4 #/sx flocele, 5#/sx gilsonite and 0.1% Super CBL (Weight - 12.0 ppg, Yield - 2.55 ft3/sx and Water - 14.4 gals/sx). Tail - 80 sxs Halliburton Type III containing 2% Econolite, 2% calseal, 6% BWC salt, 0.3% versaset, 1/4 #/sx flocele, 5 #/sx gilsonite and 0.1% Super CBL (Weight - 13.0 ppg, Yield - 2.00 ft3/sx and Water - 10.31 gals/sx).

Displaced cement with 31.2 bbls fresh water. Full returns throughout. Bumped plug to 850 psig at 20:00 hrs, 11/15/05. Plug held. Circulated 10 bbls cement to surface. Rig released at 11:30 hrs, 11/16/05.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Thomas M. Erwin, P.E.

Title **Senior Production Engineer**

Signature

Thomas M. Erwin

Date

12/06/05

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

ACCEPTED FOR RECORD

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

Date

DEC 12 2005

Office

**FARMINGTON FIELD OFFICE
RY DB**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

NMOCD