

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

5. Lease Serial No.
NMSF079029

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
San Juan 32-8 Unit #249A

9. API Well No.
30-045-31626

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan NM

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
ConocoPhillips Co.

3a. Address
P.O. Box 2197, WL3-6085 Houston Tx 77252

3b. Phone No. (include area code)
(832)486-2463

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 3 T31N R8W NWSE 2000FSL 1495FEL

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

ConocoPhillips plugged and abandoned this well effective 12/21/2005, as per the attached Daily report.



14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Christina Gustartis

Title **Regulatory Specialist**

Signature

Chris Gustartis

Date **12/29/2005**

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

JAN 04 2006

NMOCD

FARMINGTON FIELD OFFICE
BY *S. [Signature]*

Regulatory Summary

SAN JUAN 32 8 UNIT #249A

Inactivate, 12/15/2005 10:30

API/Bottom UWI	County	State/Province	Surface Legal Location	N/S Dist (ft)	N/S Ref	E/W Dist (ft)	E/W Ref
300453162600	San Juan	NEW MEXICO	NMPM-31N-08W-03-J	2,000.00	S	1,495.00	E
Ground Elevation (ft)	Latitude (DMS)	Longitude (DMS)	Spud Date	Rig Release Date			
6,675.00	36° 55' 27" N	107° 39' 30" W	6/16/2003	6/20/2003			

12/15/2005 10:30 - <End Date?>

Last 24hr Summary

HELD SAFETY MEETING W/ ALL PERSONNEL ON LOCATION. ROAD RIG & EQUIP TO LOC & SPOT. HELD SAFETY MEETING W/ ALL PERSONNEL ON LOCATION. RU RIG. SECURE, SDFN.

12/16/2005 07:00 - 12/16/2005 16:00

Last 24hr Summary

HELD SAFETY MEETING W/ ALL PERSONNEL ON LOCATION. CK PRESS. BH & TBG 0#, CSG 400#. RU BLOW DOWN LINES, BLOW DOWN WELL. RD HORSES HEAD, RU ROD TOOLS. LATCH ON TO POLISH ROD. PRESS TEST TBG TO 800#. HELD. UNSEAT PUMP, LD POLISH ROD, 1- 6' SUB, 142- 3/4" RODS, & PUMP. RD ROD TOOLS. PRESS TEST BH. HELD. PUMP 30 BBLS DOWN TBG TO KILL WELL. ND WH, NU BOP & TEST. RU 2 7/8" TOOLS. PU ON TBG. LD TBG HANGER. TOH. SECURE, SDFN.

12/19/2005 07:00 - 12/19/2005 14:00

Last 24hr Summary

HELD SAFETY MEETING W/ ALL PERSONNEL ON LOCATION. CK PRESS, CSG 80#. RU LINES, BLOW DOWN WELL. RU PUMP TRK. PUMP 25 BBLS DOWN CSG TO KILL WELL. PU CSG SCRAPER, TIH TO 3207', TOH & LD SCRAPER. PU CMT RET. TIH & ATT TO SET @ 3207'. WOULD NOT SET. SET @ 3219'. APPV'D BY BLM REP. STING OUT, LOAD CSG & CIRC CLEAN. ATT TO PRESS TEST CSG. PRESS TO 500# BUT WOULD NOT HOLD. (POSSIBLY GOING AROUND CMT RET). APPV'D BY BLM REP TO SET 21 SX PLUG & WOC. PUMP PLUG #1 W/21 SX, 27.72 CU/FT, TYPE III CMT @ 14.8 PPG. 3219'-3101'. TOH W/ 15 STDS, LD 6 JTS. WOC. SECURE, SDFN.

12/20/2005 07:00 - 12/20/2005 00:00

Last 24hr Summary

HELD SAFETY MEETING W/ ALL PERSONNEL ON LOCATION. CK PRESS, 0#. RU LINES & PUMP TRK. OPEN WELL. TIH & TAG CMT RET @ 3219'. NO CMT THERE. LOAD CSG W/45 BBLS. PRESS TEST CSG TO 500#. HELD. APPV'D BY STEVE MASON W/BLM TO SET 21 SX PLUG ON TOP OF CMT RET & NO WOC REQUIRED SINCE CSG TESTED. PUMP PLUG #1A W/21 SX, 27.72 CU/FT, TYPE III CMT @ 14.8 PPG. 3219'-3012'. LD TBG TO 2470'. LOAD CSG. PUMP PLUG #2 W/23 SX, 30.36 CU/FT, TYPE III CMT @ 14.8 PPG. 2470'-2295'. EST TOC W/REQUIRED EXCESS 2243'. LD TBG TO 1030'. LOAD CSG. PUMP PLUG #3 W/16 SX, 21.12 CU/FT, TYPE III CMT @ 14.8 PPG. 1030'-930'. EST TOC W/REQUIRED EXCESS 872'. LD TBG TO 295'. STAND BACL 5 STDS. LD STINGER. TIH W5 STDS TO 295'. LOAD CSG. PUMP PLUG #4, SURF PLUG, W/16 SX, 71.28 CU/FT, TYPE III CMT @ 14.8 PPG. 295'-SURF. CIRC GOOD CMT OUT CSG. LD ALL TBG & WASH UP. RD FLOOR. RD PUMP TRK. ND BOP. DIG OUT WH & CUT OFF. TOP OFF & SET DRY HOLE MARKER W 20 SX TYPE III CMT @ 14.8 PPG. RD RIG. CUT OFF ANCHORS. SDFN. WELL P&A'D.

12/21/2005 00:00 - 12/21/2005 00:00

Last 24hr Summary

EARTH PIT 48' NW OF DRY HOLE MARKER CLOSED 12/21/05. FINAL REPORT.