Form 3160-5 (April 2004)

which would entitle the applicant to conduct operations thereon.

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

Expires March 31, 2007 5. Lease Serial No.

FORM APPROVED

OMB NO. 1004-0137

SUNDRY NOTICES AN	D REPORTS	ON	WELL	S:
-------------------	-----------	----	------	----

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

NMSF 80000 6. If Indian, Allottee or Tribe Name 29 FM 9 26

		P.E.O.Init'of CA/Agreement, Name and/or No ARMINGTON'NM			
1. Type of Well Oil Well X Gas Well Other 2. Name of Operator	15	£ 189177	2	8. Well Name and Federal 29-9	l No.
Energen Resources Corporation		JAN 2006		9. API Well No.	
3a. Address	P. A	Phone No. (melude are		30-045-2873	9
2198 Bloomfield Highway, Farmington,	1, (, , , ,)	(505) 325-6800)=-}	10. Field and Po-	ol, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey De	escription)	Louns. Day.		Basin Fruit	land Coal
Sec 23, T29N, R09W 790' FNL, 12	230' FEL 📡	DIST. 3	3		
NE/NE	(P)	, 3 9	y .	11. County or Pa	arish, State
		292021207125		San Juan	NM
12. CHECK APPROPRIATE	BOX(ES) TO INDICA	TE NATURE OF N	NOTICE, REPO	ORT, OR OTHE	R DATA
TYPE OF SUBMISSION			E OF ACTION		
Notice of Intent	Acidize	Deepen	Production	(Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamatio	n	Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomplete	<u> </u>	Other
<u></u>		=	= :	_	- Omer
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporaril	y Abandon	refrac
	Convert to Injection	Plug Back	Water Disp	oosal	
testing has been completed. Final Abandonment Netermined that the final site is ready for final inspect 11/01/05 MIRU. Kill well & TOH wiset 5.50" packer @ 2250'. Test cas 11/02/05 Re-perforate Lower Fruit Fruitland Coal from 2258-59', 2286 frac line across Upper Fruitland Cisolation tool. 11/03/05 Spearhead 2500 gals. 158 foam slickwater, 50000# 40/70 sand isolation tool. Flow back frac. 11/04/05 Flow back frac. Retrieve isolation tool. 11/08/05 Spearhead 2500 gals 158 foam slickwater, 5000# 40/70 sand wellhead isolation tool. Flow back 11/09-14/2005 Flow back and clear 11/15/05 Landed 2.375" tubing @ 2	tion.) ith tubing. TIH wising to 2000 psi— tland Coal from 23 6-88', 2290-98', 2 Coal perforations, HCL. Refrac Lower i & 27500# 20/40 si e frac liner & TOH HCL. Refrac Upper & 59300# 20/40 br k frac. n out frac to BP @	th 5.50" casing held CK. Releas 72-86' with 56 h 301-04' & 2308-1 to isolate performed from the following the foll	scrapper and se packer and se	ad bit to 241 ad TOH. B". Re-perfor holes - 0.43 at Stinger we estimate with 540 cm of 3.15 pt 2350'. RU Stinger with 81 centration of	o'. TOH. TIH & rate Upper "". Set 5.50" allhead "00 gals. 70Q "pg. RD wellhead "nger wellhead "500 gals 70Q 3.3 ppg. RD
14. I hereby certify that the foregoing is true and correct		Title			
Name (Printed/Typed) Vicki Donaghey			tory Analys	t	
Vicki tomaku		Date 12/27/05			
	SPACE FOR FEDER	AL OR STATE OF	FICE USE	#UCEPTEL	FOR RECORD
Approved by		Title		JANAA	& 200c
Conditions of approval, if any, are attached. Approval of	f this notice does not warra	nt or Office		FARMINGTON	8 4000

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.