District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

## Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No 
Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank Telephone: (505)326-9200 e-mail address: Operator: BP America Production Company Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: Day #4 API#: 30045 235/3 U/L or Qtr/Qtr F Sec 8 T 29N R 8W Longitude \_\_\_\_\_ NAD: 1927 🗌 1983 🗍 County: San Juan Surface Owner: Federal 🗌 State 🔲 Private 🔲 Indian 🗍 Below-grade tank Type: Drilling Production Disposal Volume: bbl Type of fluid: Workover ☐ Emergency ☐ Construction material: Double-walled, with leak detection? Yes \( \subseteq \text{ If not, explain why not.} \) Lined Unlined U Liner type: Synthetic Thickness \_\_\_\_mil Clay [ Pit Volume \_\_\_\_ bbl Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more ( 0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic Nο ( 0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more ( 0 points) Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite 🗌 offsite 🔲 If offsite, name of facility\_\_\_\_\_\_\_. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🗌 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit , or an (attached) alternative OCD-approved plan ... Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or

Approval: CAS INSPECTOR CAST. Printed Name/Title

regulations.

Signature

otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or

DEC 14

Date:

FIELD REPORT: CLOSURE VERIFICATION PAGE NO: 1 of 1  LOCATION: NAME: DAY WELL F: 4 PIT: TANK QUAD/UNIT: F SPC: 3 TWP.29N RNG: GW PM. NA CHT: SJ STAND QUAD/UNIT: F SPC: 3 TWP.29N RNG: GW PM. NA CHT: SJ STAND QUESTION APPROX. 12 FT x (2 FT. x 3 FT. DEEP. CUBIC YARDAGE: O  DISPOSAL FACILITY: SANSTE REMEDIATION METHOD CLOSE RS IS  ENDED NOTES & REMARKS: PIT LOCATED APPOXIVATELY 120 FT. NB2°W FRIM VELHEAD.  BESTH 10 GROUNDWATER 2019. NEAREST VATER SUBRCE: 2000 NEAREST SUBFRACE VATER 2000  NBCC RANKING SCORE: O  NBCC PHOLOSE SCOR	BLAGG ENGINEERING, INC.   LOCATION NO. 8.85.7     P.O. BOX 87, BLOOMFIELD, NM 87413   C.O.C. NO. 842.5
QUAD/UNIT F SEC: 3 TWP.29N RNG. 9W PM.MCCNTY: SJ STANT  GTR/FOOTAGE!  CONTRACTOR: FLINT  EXCHANATION APPROX. 12 FT. x /2 FT. x 3 FT. DEEP. CUBIC YARDAGE:  DISPOSAL FACILITY:  SH-STYLE  LEAD USE: BLAN FRANKS:  FIELD NOTES & REMARKS:  FIELD AND GROUNDATER AND NEAREST VATER SOURCE AND NEAREST SUBFACE VATER.  CHECK INE  C	FIELD REPORT: CLOSURE VERIFICATION PAGE NO: _1_ of _1_
EXCAMATION APPROX.	QUAD/UNIT: F SEC: 3 TWP: 29N RNG: 8W PM: NM CNTY: SJ ST:NM DATE FINISHED: 6.4.0/
LAND USE: BLAN FRAME LEASE: SF 07841M PORMATION: OK  FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 120 FT. NB2°W FROM WELLHEAD.  DEPTH TO GROUNDVATER: 2100 NEAREST WATER SOURCE: 2/000 NEAREST SURFACE WATER 2/000 NEAREST WATER 2/000 NEAREST WATER 2/000 NEAREST SURFACE NATER 2/000 NEAREST SURFACE NATER 2/000 NEAREST SURFACE NATER 2/000	EXCAVATION APPROX. 12 FT. x 2 FT. x 5 FT. DEEP. CUBIC YARDAGE: 0
DEPTH TO GROUNDVATER 2000  NEAREST VATER SOURCE 7000  NEAREST SURFACE VATER 1000  NEAREST SURFACE VATER 1000  NEAREST SURFACE VATER 1000  CHECK DNE 1000  STELL TANK INSTALLED 1100  FIBERGLASS TANK INSTALLED 1100  FIBERGLASS TANK INSTALLED 1100  FILD 418.1 CALCULATIONS  TIME SAMPLE I.D. LAB NO: WEIGHT (q) mL FREON DILUTION REACING CALC ppm  SCALE  O FT  O FT  O PIT PERIMETER  OVM  RESULTS  SAMPLE 1000  RESULTS  SAMPLE 1000  RESULTS  SAMPLE 1000  A P T TO THE 1000  A P T TO THE 1000  A P T TO THE 1000  COUNTY TO THE 1000  A P T TO THE 1000  COUNTY TO THE 1000  CHECK DNE 1000  STELL TANK INSTALLED 1100  STELL TANK INSTALLED 1100  STELL TANK INSTALLED 1100  STELL TANK INSTALLED 1100  FIBERGLASS TA	•
SCALE  O FT  PIT PERIMETER  OVM  RESULTS  SAMPLE PELD HADSPACE PID (Sport)  1 2 2 3 3 9 4 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000 NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM CALIB. READ. 130.4 PPM STEEL TANK INSTALLED TIME: 1500 OM PM STEEL TANK INSTALLED TIME: 1500 OM PM FIBERGLASS TANK INSTALLED O'-3' DRY, Yelfow Taw Sity Sound.  3-6' MOIST, ''', NO HC ODOR OR STAIN.
SCALE  O FT  PIT PERIMETER  OVM  RESULTS  SAMPLE FEEL HADSPACE 10 12  3 2 4 2 3 3 2 4 4 2 5 2 3 3 2 4 4 2 5 2 5	
OVM RESULTS  SAMPLE FELD HEADSPACE POLICIPAL  12 2 2 3 2 9 3 9 4 9 5 9 5 9 7  SAMPLES  SAMPLE	SCALE
RESULTS  SAMPLE FIELD HEADSPACE POD (Spirit)  1 @ C O G Z 3  2 @ 3 @ 4  4 @ 5 @ 7  12  SAMPLE SAMPLES  SAMPLE ANALYSIS TIME C O G TPH 1400  C O G TPH 1400	
LALLOUT W 1 $\sim$ CONSIDER W $\sim$ CONSIDER W	RESULTS  SAMPLE FIELD HEADSPACE POD (Spirit)  1 @ COG Z.3  2 @ 3 @ 4  4 @ 5 @ 7  12 / 5 @ 7  SAMPLES  SAMPLES

revised: 03/12/01



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Tank C @ 6'	Date Reported:	06-06-01
Laboratory Number:	19964	Date Sampled:	06-04-01
Chain of Custody No:	8425	Date Received:	06-05-01
Sample Matrix:	Soil	Date Extracted:	06-06-01
Preservative:	Cool	Date Analyzed:	06-06-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.7	0.2
Diesel Range (C10 - C28)	0.2	0.1
Total Petroleum Hydrocarbons	0.9	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Day #4.

Analyst C. Oyluna

Phristini my Walters