

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2005 JAN 10 AM 7 59

1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
835' FNL, 1525' FEL, Sec. 34, T28N, R5W, NMPM

5. Lease Number
SF-079522

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 28-5 Unit

8. Well Name & Number
San Juan 28-5 Unit 71

9. API Well No.
30-039-20037

10. Field and Pool
Basin Dakota

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other - Plug & Abandonment	

13. Describe Proposed or Completed Operations

12/20/05 MIRU. NU BOP & test. TOOH w/tbg & pkr. SDFN.
12/21/05 TIH w/tbg & set a 4 1/2" CR at 7786'. PT tbg to 1000 psi, ok. PT csg to 800 psi, leaking.
PLUG #1: w/16 sxs Type III cmt pumped down csg from 7786'-7686'. Spot a balanced plug above CIBP to isolate the Dakota perfs & top. TOOH w/tbg. SDFN.
12/22/05 Finished TOOH w/tbg. RU W/L, tag Plug #1 @ 7450'. PU perf 3 spf @ 6850'. RD W/L. PU 4 1/2" CR. TIH set CR @ 6800'. Sting into CR. OK'd by BLM to spot plug on top of CR.
PLUG #2: w/20 sxs Type III cmt pumped down csg from 6800'-6500'. SDF Holiday.
12/27/05 TIH tag Plug #2 @ 6553'. LD tbg to 5480'.
PLUG #3: w/20 sxs Type III cmt pumped down csg from 5480'-5380'. TOOH w/tbg. WOC. RU W/L. Tag Plug #3 @ 5137'. PT csg to 800 psi, leaking. Perf 3 spf @ 4306'. PU 4 1/2" CR. TIH, set @ 4256'.
PLUG #4: w/47 sxs Type III cmt pumped down csg from 4306'-4206'. TOOH w/tbg. SDFN.
12/28/05 TIH, tag Plug #4 @ 4120'. LD tbg to 3715'.
PLUG #5: w/22 sxs Type III cmt pumped down csg from 3715'-3615'. TOOH w/tbg. WOC. RU W/L. TIH, Tag plug #5 @ 3397'. PU CR. TIH, set @ 3340'.
PLUG #6 & #7: w/140 sxs Type III cmt pumped down csg from 3394'-2910'. Sting out of tbg. Spot Cmt to bottom of tbg. Sting into CR, pump plug under CR. Spot plug on top of CR to 2910'. TOOH w/stinger. LD tbg to next plug @ 1830'. WOC. SDFN.
12/29/05 RU W/L. TIH, tag #7 plug @ 2652'. PT csg to 800, ok. Perf 3 spf @ 1880'. PU CR. TIH, set @ 1840'.
PLUG #8: w/46 sxs Type III cmt pumped down csg from 1880'-1765'. RIH, perf 3 spf @ 372'. Break circ out BH. Circ clean.
PLUG #9: w/154 sxs Type III cmt pumped down csg from 372' to surface. ND BOP. Install P&A marker w/10 sxs cmt. RD. Rig released. Ray Espinoza w/BLM was on location. Jim Wright with BR was on location.
WELL PLUGGED & ABANDONED ON 12-29-05.

14. I hereby certify that the foregoing is true and correct.

Signed *Joni Clark* Title Regulatory Specialist Date 1/9/06 **JAN 10 2006**

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE

NMOC