

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SF-080430-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-6 Unit *MV PA# NMANM 78412A*

8. FARM OR LEASE NAME, WELL NO.

San Juan 28-6 Unit 159

9. API WELL NO.

30-039-20380 *CL*

10. FIELD AND POOL, OR WILDCAT

Blanco MV/Basin DK

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

SEC. 18 T28N, R06W, NMPM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface SEC. 18, T28N, R06W, NMPM
SESW 800' FSL, 1450' FWL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPUNDED

5/28/71

16. DATE T.D. REACHED

6/5/71

17. DATE COMPL. (Ready to prod.)

12/17/05

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)

6609'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

7870'

21. PLUG, BACK T.D., MD & TVD

7852'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

4358'-5708' Mesaverde

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR/CBL/CCL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" J-55	32.3#	208'	13 3/4"	190 sxs	
7" J-55	20#	3662'	8 3/4"	190 sxs	
4 1/2" J-55	11.6 & 10.5#	7870'	6 1/4"	330 sxs	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
				2 3/8

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
	7742'	

31. PERFORATION RECORD (Interval, size and number)

1 spf @ .34 dia. 4358'-4557' = 25 holes
1 spf @ .34 dia. 5037'-5217' = 25 holes
1 spf @ .34 dia. 5410'-5708' = 25 holes
75 holes total

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4358'-4557'	Acidize w/10 bbls 15% HCL
5037'-5217'	Frac w/539 bbls slickwater, 200,000# 20/40 Brady Sand, 1,202,400 scf N2
5410'-5708'	Acidize w/10 bbls 15% HCL
	Frac w/1195 bbls slickwater, 100,000# 20/40 Brady Sand, 1,050,800 scf N2
	Acidize w/10 bbls 15% HCL-Frac w/1193 bbls slickwater, w/100,000# 20/40 Brady Sand, 1,125,800 scf N2

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
12/19/05		Flowing					SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL		GAS-OIL RATIO
12/17/05	1 hour		→					
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL		OIL GRAVITY-API (CORR.)	
SI 451	435	→	0	1065	0			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

To be commingled DHC # 1846 AZ

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

None

ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *Joni Clark* TITLE Sr. Regulatory Specialist

DATE 12/21/05

JAN 09 2006

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE

NMOCD

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form, and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24 below regarding separate reports for separate completions. If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers' geologists, sample and core analysts, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form. See item 25.

Item 1: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference. (If there are not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion) so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s), and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS, AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOF	
					MEAS. DEPTH	TRUE VERT. DEPTH
				Mesa Verde	5025	
				Point Lookout	5564	
				Gallup	6620	
				Greenhorn	7526	
				Graneros	7587	
				Dakota	7750	