District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan" Yes 🔼 No 📋 Type of action: Registration of a pit or below-grade tank 🗍 Closure of a pit or below-grade tank 🔀		
Operator: BP America Production Company Telephon	e: <u>(505)326-9200</u> e-mail address:	
Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: #49 NES A #58 API #:3	045 25460 H/ or Otr/Otr T	188 (188 T 25m2
J	Longitude	
County: San Juan Latitude Surface Owner: Federal State Private Indian	Longitude	NAD. 1921 🗖 1903 🖺
	Delay goods tools	
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	
	Workover ☐ Emergency ☐ Construction material: ned ☐ Unlined ☐ Double-walled, with leak detection? Yes ☐ If not, explain why not.	
Lined Unlined Thickness mil Clay	Double-waited, with leak detection? Tes 11 110	t, explain why not.
Liner type: Synthetic Thicknessmil Clay Pit Volumebbl		
TH Volumeooi	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	(0 points)
	100 feet of more	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's		
your are burying in place) onsite offsite If offsite, name of facility_		
remediation start date and end date. (4) Groundwater encountered: No 🔲 Y		ft. and attach sample results.
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.	
Additional Comments:		
See Attached Documentation		
- Dec	1/00/1 3 (574
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \(\mathbb{X}\), a general permit \(\mathbb{I}\), or an (attached) alternative OCD-approved plan \(\mathbb{I}\).		
	4	
Printed Name/Title Jeffrey C. Blagg, Agent Signature C. Slegy		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval: TEPUTY OIL & GAS INSPECTOR, DIST. (2) Printed Name/Title Signature Signature Date:		
Printed Name/Title Signature Date:		

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	C.O.C. NO: <u>80866</u>
FIELD REPORT: CLOSURE VERIFICATION	PAGE No: 1 of 1
LOCATION: NAME: HUGHES A WELL #: 5E PIT: TANK	DATE STARTED: 6-25-01 DATE FINISHED: 6-25-01
QUAD/UNIT: J SEC: 33 TWP: ZGN RNG: BW PM: NMCNTY: SJST:NM QTR/FOOTAGE: 15405/15606 NWSE CONTRACTOR: FLINT	ENVIRONMENTAL JCS
EXCAVATION APPROX. 12 FT. x 12 FT. x 4 FT. DEEP. CUBIC	YARDAGE:
DISPOSAL FACILITY: REMEDIATION METHOD LAND USE: BLAM LEASE: SF 078049 FOR	_ i
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 140 FT.	
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE	CHECK DIVE
SOIL AND EXCAVATION OVM CALIB. READ. 132.4 ppm	1
DESCRIPTION: TIME: 1230 AMORD - EARTHEN PIT. USED BACKHUE TO DIE TEST PULC 1-	FIBERGLASS TANK INSTALLED
0'-5' Silty Soud, Mulst, HC OBOR & STAIN 2'-5' (G	
5-62 DEUSE, FIRM CLAYSTONE, HC ODOR X STAIN (GREEN/BLACE)
BEDROCK TOO HARD to Source, SAMPLED SILTY SOND	
BEDROCK (RISK ASSESSED) FIELD 418.1 CALCULATIONS	
TIME SAMPLE I.D. LAB No: WEIGHT (g) ML. FREON DII SCALE	LUTION READING CALC. ppm
O FT PIT PERIMETER PIT	PROFILE
OVM RESULTS	
SAMPLE FIELD HEADSPACE PIO (ppm) 1 @ 5 /37	
2 @ 3 @ 0	SAMPLE
A GIZ 5 e A SI	
12'	Contract of the second
LAB SAMPLES SAMPLE ANALYSIS TIME	BEDRIXK
Test CAS TPHYBT=x 13F5 THAT FAMED BYEX PASSED	
Hold Brex PASSED	
TRAVEL NOTES: CALLOUT: 6/25/6! 1015 ONSITE: 0/15/6! 13	2/5

revised: 03/12/01



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Tank C @ 5'	Date Reported:	06-28-01
Laboratory Number:	20154	Date Sampled:	06-25-01
Chain of Custody No:	9288	Date Received:	06-26-01
Sample Matrix:	Soil	Date Extracted:	06-27-01
Preservative:	Cool	Date Analyzed:	06-28-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	3,350	0.2
Diesel Range (C10 - C28)	4,060	0.1
Total Petroleum Hydrocarbons	7,410	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Hughes A #5E.

Analyst C. Oglene

Anister in Lactor



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Tank C @ 5'	Date Reported:	06-28-01
Laboratory Number:	20154	Date Sampled:	06-25-01
Chain of Custody:	9288	Date Received:	06-26-01
Sample Matrix:	Soil	Date Analyzed:	06-28-01
Preservative:	Cool	Date Extracted:	06-27-01
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Pangana	5 000	4.0
Benzene Toluene	5,990 1,150	1.8 1.7
Ethylbenzene	1,240	1.5
p,m-Xylene	3,260	2.2
o-Xylene	2,470	1.0
Total BTEX	14,100	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Hughes A #5E.

Analyst

Review Wallen