District I 1625 N. French Dr., Hobbs, NM 88240 District II

District III

District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

1220 South St. Francis Dr. office Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank					
Operator: BP America Production Company Telephon Address: 200 Energy Ct. Farmington, NM 87401					
Facility or well name: #49hes A#5E API#:3	•				
	Longitude	NAD: 1927 🗌 1983 🗍			
Surface Owner: Federal State Private Indian					
<u>Pit</u>	Below-grade tank				
Type: Drilling Production Disposal	Volume:bbl Type of fluid:				
Workover	Construction material: Double-walled, with leak detection? Yes If not, explain why not.				
Lined Unlined					
Liner type: Synthetic Thicknessmil Clay Divided the synthetic					
Pit Volumebbl	L	1 (20			
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)			
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)			
	100 feet or more	(0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)			
water source, or less than 1000 feet from all other water sources.)	No	(0 points)			
	Less than 200 feet	(20 points)			
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)			
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)			
	Ranking Score (Total Points)				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's					
your are burying in place) onsite 🔲 offsite 🔲 If offsite, name of facility_					
remediation start date and end date. (4) Groundwater encountered: No 🔲 Y		ft. and attach sample results.			
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.				
Additional Comments:					
See Attached Documentation					
	/	10+4			
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that t is X , a general permit , or an (attached) alterna	he above-described pit or below-grade tank tive OCD-approved plan .			
Data: 11/01/2005					
Printed Name/Title Jeffrey C. Blagg, Agent Signature					
Printed Name/Title					
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.					
Approval: OEDSTRA Out	15-				
Approval: OEPUTY OIL & GAS INSPECTOR, DIST. 61	Signature \Signature	Date: DEC 1 4 2005			
					

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 CLIENT: BP CLOCATION NO. \$0866 C.O.C. NO. 9298					
FIELD REPORT: CLOSURE VERIFICATION PAGE No: 1 of 1					
LOCATION: NAME: HUGHES A WELL #: 5E PIT: SEP DATE STARTED: 6-25-01 DATE FINISHED: 6-25-01					
QUAD/UNIT: J SEC: 33 TWP: 29N RNG: 9W PM: NM CNTY: SJ ST: NM QTR/FOOTAGE: 1840 S 1860 E NWSE CONTRACTOR: FLINT SPECIALIST: JCB					
EXCAVATION APPROX. 14 FT. x 14 FT. x 4 FT. DEEP. CUBIC YARDAGE: 0					
DISPOSAL FACILITY: 00-517E REMEDIATION METHOD: CLOSE 95 15 LAND USE: BLM LEASE: NMSF 078049 FORMATION: DK					
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 117 FT. 539 FROM WELLHEAD.					
DEPTH TO GROUNDWATER: > 1000 NEAREST WATER SOURCE: > 1000 NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM SELT ABANDONED PM					
SOIL AND EXCAVATION OVM CALIB. READ. 137. O PPM STEEL TANK INSTALLED					
DESCRIPTION: TIME: 1230 am/pm FIBERGLASS TANK INSTALLED					
ENOTHER PIT. USED BACKHUE TO DIG TEST HOLE IN PIT CENTER. 0'-5' Silty Soud, moist from 3'-5', No HC ODUR ON SHAIN.					
5'-7' V. Deuse Soudstone, Minor HC ODOR, TO HARD TO Souple.					
Soupled Sort @ 5'@ Bodovek interface					
BEDROCK CLOSED BOTTOM FIELD 418.1 CALCULATIONS					
TIME SAMPLE I.D. LAB No: WEIGHT (g) mL. FREON DILUTION READING CALC. ppm SCALE					
0 FT PERIMETER PIT PROFILE					
OVM RESULTS					
SAMPLE FIELD HEADSPACE PID (ppm) 1 @ S ZO SAMPLE SAMPLE SAMPLE SAMPLE SAMPLE SAMPLE SAMPLE					
1 2 @ 3 @					
4 @ A					
14'A 5'					
LAB SAMPLES SAMPLE ANALYSIS THE					
SAMPLE ANALYSIS TIME COST TIPH 1350 REDROCK					
SAMPLE TEST HOLE					
TRAVEL NOTES: CALLOUT: 6/25/01 1015 ONSITE: 6/25/01 1215					

revised: 03/12/01

bei1005.skd



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Separator C @ 5'	Date Reported:	06-28-01
Laboratory Number:	20155	Date Sampled:	06-25-01
Chain of Custody No:	9288	Date Received:	06-26-01
Sample Matrix:	Soil	Date Extracted:	06-27-01
Preservative:	Cool	Date Analyzed:	06-28-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.5	0.2
Diesel Range (C10 - C28)	15.0	0.1
Total Petroleum Hydrocarbons	15.5	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Hughes A #5E.

Analyst C. Cedence

Review M Wolfen