District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes No

Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank		
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:		
Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: Roelofs B#1 API#: 30045 0809/ U/L or Qtr/Qtr B Sec 32 T 39N R 8W		
	Longitude	NAD: 1927 🗌 1983 🗍
Surface Owner: Federal State Private Indian		
it Below-grade tank		
e: Drilling Production Disposal Volume:bbl Type of fluid:		
Workover		
	☐ Unlined ☐ Double-walled, with leak detection? Yes ☐ If not, explain why not.	
Liner type: Synthetic Thicknessmil Clay		
Pit Volumebbl	7 d 50 C	[(20
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)
	Danking Sease (Total Bainta)	
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit		
your are burying in place) onsite \(\square\) offsite \(\square\) If offsite, name of facility_	. (3) Attach a genera	al description of remedial action taken including
remediation start date and end date. (4) Groundwater encountered: No \square	Yes If yes, show depth below ground surface	ft. and attach sample results.
(5) Attach soil sample results and a diagram of sample locations and excava	tions.	(A) (1) (F)
Additional Comments:		13 14 15 16
See Attached Documentation		
		DEC 2005
S PRECEIVED 2		
C OIL CONS. DIV. 2		
		300
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described int or below-grade tank		
has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved than .		
Date:		
Printed Name/Title Jeffrey C. Blagg, Agent Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or		
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval:		
Printed Name/Title SPUTY OR & GAS INSPECTOR, DIST. 33 Signature Signature		

3004508091 CLIENT: AMOCO BLAGG ENGINEERING, INC. LOCATION NO BOSSY P.O. BOX 87, BLOOMFIELD, NM 87413 C.D.C. ND 8495 (505) 632-1199FIELD REPORT: CLOSURE VERIFICATION PAGE NO. 1 of 1 DATE STARTED: 31 JAN 01 LOCATION: NAME: ROELOFS B WELL #: 1 PIT: SEP DATE FINISHED: OI FEB OI QUAD/UNIT: B SEC: 22 TWP: 29N RNG: 8W PM:NM CNTY:SJ ST: NM ENVIRONMENTAL JCB OTR/FOOTAGE: 990 N/2310 E NUME CONTRACTOR: FLINT EXCAVATION APPROX. 10 FT. x 0 FT. x 0 FT. x 0 FT. x 0 FT. DEEP. CUBIC YARDAGE: ___O_ DISPOSAL FACILITY: ONSITE REMEDIATION METHOD: THE CLOSE AS 15 LAND USE: RANGE LEASE: SF-078415 FORMATION: MV FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY <u>[10</u> ft. <u>\$31°E</u> from wellhead DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM A PIT ABANDONED OVM CALIB. READ. 131.0 ppm _____ STEEL TANK INSTALLED SOIL AND EXCAVATION TIME: 1111 am pm ____ FIBERGLASS TANK INSTALLED DESCRIPTION: PIT EXCAVATES TO SANDSTONE BEDROCK. 0-4 YELLOW TAN COARGE GRANNED SAND, DAY, NOW GUSSIVE, NO AC STAIN. ABLE TO SAMPLE SIDEWALLS @ BASE @ BEDROCK INTERFACE V. FIRM SANISTONE BEDROCK, YELLOW TAN, NO HE OOCH OR STAIN, TOO DENSE & CEMENTED TO SAMPLE. MINOR ODOR ON SIDEWALL SAULICES BEDROOK CLOSED FIELD 418.1 CALCULATIONS SAMPLE I.D. LAB No: WEIGHT (g) ml. FREON DILUTION READING CALC. ppm Borron SCALE PIT PERIMETER PIT PROFILE OVM RESULTS TO WELLHEAD FIELD HEADSPACE PID (ppm) SAMPLE 1N@ 4 <u>--10'-</u> 350 10 A LAB SAMPLES SANDSTONE 8015/9021 1025 BEDROCK

TRAVEL NOTES:

CALLOUT: @31 JAN 01 1500 ONSITE: OIFEBOI 1000



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	04034-010
Sample ID:	Sep. S @ 4'	Date Reported:	02-05-01
Laboratory Number:	19167	Date Sampled:	02-01-01
Chain of Custody No:	8495	Date Received:	02-02-01
Sample Matrix:	Soil	Date Extracted:	02-05-01
Preservative:	Cool	Date Analyzed:	02-05-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	374	0.2
Diesel Range (C10 - C28)	775	0.1
Total Petroleum Hydrocarbons	1,150	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Roelops "B" #1.

Analyst

Prister m Wasters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	04034-010
Sample ID:	Sep. S @ 4'	Date Reported:	02-05-01
Laboratory Number:	19167	Date Sampled:	02-01-01
Chain of Custody:	8495	Date Received:	02-02-01
Sample Matrix:	Soil	Date Analyzed:	02-05-01
Preservative:	Cool	Date Extracted:	02-05-01
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	93.7	1.8
Toluene	1,150	1.7
Ethylbenzene	529	1.5
p,m-Xylene	1,070	2.2
o-Xylene	957	1.0
Total BTEX	3,800	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	100 %
	Bromofluorobenzene	100 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Roelops "B" #1.

Dere L. Open

A historie m Wallers
Beview