Form C-103 State of New Mexico Submit 3 Copies To Appropriate District Revised March 25, 1999 Energy, Minerals and Natural Resources Office **DISTRICT I** WELL API NO. OIL CONSERVATION DIVISION 1625 N. French Dr., Hobbs, NM 88240 ′30-045-31341 1220 South St. Francis Drive **DISTRICT II** Indicate Type of Lease Santa Fe, NM 87505 1301 W. Grand Ave., Artesia, MM 87210 FEE X STATE **DISTRICT III** 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. **DISTRICT IV** 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO 7. Lease Name or Unit Agreement Name A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH, MAY 2003 CLAYTON 1. Type of Well: OIL GAS WELL WELL OTHER Well No. 2. Name of Operator **1B CORDILLERA ENERGY, INC.** 9. Pool name or Wildcat 3. Address of Operator 5802 HIGHWAY 64, FARMINGTON, NEW MEXICO 87401 **BLANCO MESA VERDE/BASIN DAKOTA** 4. Well Location Line Feet From The SOUTH Line and WEST 660 Feet From The **Unit Letter** : 1980 SAN JUAN 12W NMPM Township 30N Range 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5828' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: **NOTICE OF INTENTION TO:** ALTERING CASING PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK COMMENCE DRILLING OPNS PLUG & ABANDONMENT CHANGE PLANS TEMPORARILY ABANDON CASING TEST & CEMENT JOB **MULTIPLE PULL OR ALTER CASING** COMPLETION Set 4-1/2" Casing OTHER: OTHER: 12. Describe Proposed or Completed Operatic (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. SEE RULE 1103. RIH w/162 its 4-1/2", 11.6#, N80 LT&C csg set @ 6798'. 5/14/2003 Cement: Pump 50 sx @ 4 bpm w/285 psi of San Juan Poz w/4% gel @ 11 ppg (1.80 cuft/sx). 340 sx @ 4 bpm w/310 psi of 50/50 Poz w/2% gel. 5# sx Gilsonite. 1/4# Cello, 0.6% Halad 9, 0.1% HR5, 6.44 gal/sx wtr @ 13.5 ppg (1.44 cuft/sx). Bumped plug w/1250 psi. OK. REPORT CEMENT TOPS I hereby certify that the Information above is true and complete to the best of my knowledge and belief. PRODUCTION TECHNICIAN 27-May-03 SIGNATURE KAY S. ECKSTEIN TELEPHONE NO. (505) 632-8056 TYPE OR PRINT NAME MAY 29 2003 (This space for State Use) DEPUTY OF A PAS SYSPECTAR, COLD AS

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: