

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
Abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 2000

5. Lease Serial No.

SF - 0078194

6. If Indian, Allottee or tribe Name

2006 FEB 21 PM 2 37

7. If Unit or CA/Agreement, Name and/or No.

RECEIVED
070 FARMINGTON NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well



Oil Well



Gas Well



Other

8. Well Name and No.

Ludwick LS 17M

2. Name of Operator

BP AMERICA PRODUCTION COMPANY

9. API Well No.

30-045-32923

3a. Address

PO BOX 3092 HOUSTON, TX 77253

3b. Phone No. (include area code)

281-366-4081

10. Field and Pool, or Exploratory Area

BASIN DAKOTA & BLANCO MESAVERDE

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1010' FSL & 1660' FSL; SEC 29 30N 10W SWSE Mer NMP

11. County or Parish, State

SAN JUAN, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OR NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION



Notice of Intent



Subsequent Report



Final Abandonment Notice

TYPE OF ACTION



Acidize



Deepen



Production (Start/Resume)



Water shut-Off



Alter Casing



Fracture Treat



Reclamation



Well Integrity



Casing Repair



New Construction



Recomplete



Other Spud & Set



Change Plans



Plug and Abandon



Water Disposal



Convert to Injection



Plug Back

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.

MIRU 9/28/05 & spud a 131/2" surface hole. Drill to 220'. RU & ran 9 5/8", 32.3# H-40 surface CSG to 212'. CMT w/22 bbls Redi-Mix (Est. 98 sxs) Circulate 4 bbls to surface.

1/20/06 Pressure test BOP 250 low & 1500 high. Test OK pres test 9 5/8" csg to 750 psi 30 min. OK.

Drilled out CMT & rat hole 182' - 220'. Drilled an 8 1/4" hole 220' to 4523'. RU & set 7"; FS, FC, 15 JTS (591') 23# N80 LTC, 3 JT (122') 20# J55, DV tool, 6 JTS 20# J55 CSG & tag bridge @925'. LD 7". Wash & Ream tight hole. RU CSG tools & run 7" CSG - shoe, 1 JT 23#, float collar, 14 jts 23# N80 LT&C, 3 jts 20# J55 DV tool, 6 jts 20# to 952' - end NPT. Cont run 7" to 4510'. TIH & CMT 7"; 1st STAGE: SCAVENGER w/167 sxs 50/50 CL G/POZ. 2nd STAGE SCAV 400 sxs 11.7 ppg CL G, Tailw/65 sxs @13.50 ppg, 50/50 CL G/POZ. Circ 6 bbls cmt to pit. Press test 7" to 1650#; 30 min. Test OK.

7" CSG IS 23# N-80 BELOW 4000'.

Drill out CMT @4466'. Drilled a 6 1/4" hole 4523' - 7250'. TD 01/31/2006. RU & set 4 1/2", 11.6#, P-110 LT & C, production CSG to 7250'. Lead: w/71 sxs of 9.5 ppg Density Litecreat. Yield 2.52 Tail w/195 sxs pozz 13.0 PPG, 1.44 yield cuft/sx.

Top of Cement @4200'. - Please report the 7" 1st stage TOC.

14. I hereby certify that the foregoing is true and correct
Name (Printed/typed)

Cherry Hlava

Title Regulatory Analyst (281) 366-4081

Signature

Cherry Hlava

Date 02/14/2006

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

