This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

ocation of We	ell: Unit L	etter A S	ec 29	Twp 026N	Rge	003W A	API# 30-039-20566
	Name of Reservoir or Pool			Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas		w	Tubing
Lower Completion	MV		Oil	Oil		ificial Lift	Tubing
			Pre-Flow S	Shut-In Pressu	re Data		
Upper Completion	Hour, Date, Shut-In 6/21/2015		96 h	Length of Time Shut-In 96 hours		Press. PSIG	
Lower Completion	Hour, Date, Shut-In 6/21/2015			Length of Time Shut-In 72 hours		Press. PSIG	Stabilized?(Yes or No) Yes
			Flo	ow Test No. 1			
Commenced	at:	6/24/2015		Zone Pro	oducing (Up	per or Lower):	LOWER
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SSURE Lower zone	Prod Zon Temperatu		Remarks
6/24/201	5	0	106	386			
6/24/2015 12:06:28 PM		12	106	38			
6/25/201	5	24	106	40			
roduction rate	e during te	est					
il: BPOD Based on: Bb			Bbls. In	ls. InHrs		Grav.	GOR
as	Bar.	MCFPD; Test th	nru (Orifice or N	Meter)	5		
			Mid-Test S	Shut-In Pressu	re Data		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In		Press. PSIG	Stabilized?(Yes or No)
Lower Hour, Date, Shut-In Completion		Length	Length of Time Shut-In		Press. PSIG	Stabilized?(Yes or No)	

JUL 07 2015

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)						
Time	Lapsed Time	PRESSURE		Prod Zone				
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks			
				1-3				
			Market Company		and the second			
-								
			1,129					
4.4	D Based on:	Bbls. In	Hrs.	Grav	GOR			
Sas	MCFPD; Test to	nru (Orifice or M	leter)					
	K - L							
emarks:								
		7						
	e information herein o		and complete	to the best of my k	nowleage.			
pproved: Jahn	Levertam 17-1	W 20 15	Opera	tor: COP	Land Hall Total			
New Mexico Oil Co		Ву:	By: Gilbert Lovato					
y:			Title	Title: Multi-Skilled Operator				
	QUAL PARTY							
itle:			Date:	Date: Monday, July 06, 2015				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure
 for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall
 remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

^{5.} Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above