

Submit 3 Copies to Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-09918
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Maxwell
8. Well Number #1
9. OGRID Number
10. Pool name or Wildcat Aztec PC/Flora Vista Fruitland Sands

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Other	
2. Name of Operator McKay Oil and Gas, LLC	OIL CONS. DIV DIST. 3
3. Address of Operator P.O. Box 14738, Albuquerque, NM 87191-4738	OCT 09 2015
4. Well Location Unit Letter _____ : 1850' feet from the FNL line and 1850 feet from the FWL line Section 1 Township 30N Range 12W NMPM San Juan County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 5818 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

McKay Oil and Gas, LLC plugged and abandoned this well on September 24, 2015 per the attached report by A- Plus Well Service.

Plug #1 with CR at 2175' spot 69 sxs (81.42 cf) Class B cement from 2175' to 1581' to cover the PC interval and Fruitland interval. Tag TOC at 1740'.

Plug #1a with 16 sxs (18.88 cf) Class B cement from 1740' to 1603' to top off plug #1 covering the Fruitland top. Tag TOC at 1630'.

Plug #2 with squeeze holes at 940' and CR at 897' spot 109 sxs (128.62 cf) Class B cement with 1% CaCl from 940' to 613' to cover the Kirtland and Ojo Alamo tops, 1) pump 76 sxs below CR at 897' (5 sxs inside and 71 sxs outside 5-1/2" casing), 2) sting out CR and leave 33 sxs above CR from 897' to 613'. Tag TOC at 867'.

Plug #2a with 28 sxs (33.04 cf) Class B cement from 867' to 626' to top off plug #2 and cover the Kirtland and Ojo Alamo tops. Tag TOC at 656'.

Plug #3 with 93 sxs (109.74 cf) Class B cement from 142' to surface to cover the 8-5/8" shoe and surface.

Plug #4 with 12 sxs (14.16 cf) Class B cement top off casings and install P&A markers with coordinates N 36° 50' 36" / W 108° 3' 10".

PNR only

Spud Date:

Rig Release Date:

Approved for plugging of wellbore only.
Liability under bond is retained pending
Receipt of C-103 (Subsequent Report of Well
Plugging) which may be found @ OCD web
page under forms
www.emnrd.state.us/ocd

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Frank Welker

TITLE

Engineer

DATE

10-6-2015

Type or print name

Frank Welker

E-mail address:

frank@mckayoilandgas.com

PHONE:

For State Use Only

APPROVED BY:

Frank Welker

TITLE

DEPUTY OIL & GAS INSPECTOR
DISTRICT #3

DATE

11/12/15

Conditions of Approval (if any):

RV

5

REPROGRAPHICS 090576J

Daily Report

A - PLUS WELL SERVICE

P.O. BOX 1979 • FARMINGTON, NM 87499
505-325-2627 • FAX (505) 325-1211

48120

Rig No 14Date 9-23-15 Day WEDNESDAYWell Name MAXWELL #1Company McKAY OIL & GAS

FROM	TO	DESCRIPTION OF OPERATION
6:00	7:00	LOAD SUPPLIES: TRAVEL TO LOC
7:00		SETY MTL ON JSA, SERV START EQUIP
		SICP-2", SIBHP-2", OPEN WELL TO PIT, FUNCTION TEST BOP
		PU PLUGGING SUB, TTH TBG TAG PLUG 1A TOG @ 1630', TOH LD TBG TO 897', SB
8:45		REMAINING TBG LD PLUGGING SUB, LOAD HOLE W/ 5 BBL
9:45	9:15	A-PLUS WLU- 3 1/8" HSC- 3 PERFS @ 940', EST RATE DOWN CSG 2 BPM @ 500'
9:15		PU 5 1/8" DHS CR, TTH TBG TO SET: RELEASE CR @ 897', PRESS TEST CSG-BLED 500'-
	9:45	6" IN 15 SECS, STING IN CR: PUMP 5 BBL @ RATE 2 BPM @ 1000'
9:45		PLUG 2- 109SX, 15.6", 1.18 YIELD = 128.62 CUFT CLASS B CMT FROM 940'- 613' TO
		TO COVER KIRTLAND: OA TOPS, 1) PUMP 76SX BELOW CR @ 897' (5SX INSIDE &
		71SX OUTSIDE 5 1/2" CSG), 2) STING OUT CR: LEAVE 33SX ABOVE CR FROM
	10:30	897'- 613' TOG, CMT PUMPED W/ 1% CACL, NO CIRC OUT AN THROUGHOUT PLUG
10:30		TOH LD TBG TO TOG, SB REMAINING TBG LD CR SETTING TOOL
	1:45	SL WELL: WDL UNTIL CMT SAMPLE HARD
1:45		TTH TBG TAG PLUG 2 TOG @ 867', RU PUMP TO TBG: LOAD HOLE W/ 2 BBL, CIRC
		HOLE W/ 25 BBL - RETURNS GAS CUT THEN CEMENT COLORED - 4.5 BBL CMT TO PIT
	2:15	PRESS TEST CSG TO 700' - HELD OK 10 MINS
2:15		PLUG 2A- 28SX, 15.6", 1.18 YIELD = 32.04 CUFT CLASS B CMT FROM 867'- 626' TOG
	2:45	TO TOP OFF PLUG 2: COVER KIRTLAND/OA
2:45		TOH LD ALL TBG + PLUGGING SUB, RU PUMP TO CSG: LOAD HOLE W/ 3.5 BBL -
		TBG DISP 1.5 BBL, ATTEMPT TO PRESS TEST CSG-BLED 500'- 0" IN 5 SECS THEN
		ON VACUUM
	3:30	SL WELL, CLEAN: SECURE LOC
3:30	4:00	TRAVEL TO YARD
		FRANK WELKER: BILL MAYHEM W/ ACKAY ON LOC
		JOHN DURHAM W/ NMOED ON LOC

Fuel & Motor Oil _____ Water Hauled _____

Rental Equipment _____ Cement Retainers 5 1/8" DHS CR @ 897'Cementing PLUG 2- 109SX W/ 1% CACL, PLUG 2A- 28SXWireline (WF) 3 1/8" HSC- 3 PERFS @ 940'

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	P FITZPATRICK	24	30	
Operator	W BENALLY	35	30	10
Derrick	R SLAUGH			10
Floors	P ROMERO			10
Floors	* J CHRISTENSEN			10
Floors				

REPROGRAPHICS 090576A

48121

P.O. BOX 1979 • FARMINGTON, NM 87499
505-325-2627 • FAX (505) 325-1211

Rig No. 14

Date 9-24-15 Day THURSDAY

Well Name MAXWELL #1

Company McKAY OIL & GAS

[illegible]

Fuel & Motor Oil _____ Water Hauled _____

Rental Equipment _____ Cement Retainers _____

Cementing PW#3-93sx, DHM-12sx

Wireline (NP) 3 1/8" HSL - 3 PERPS @ 142'

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	P FITZPATRICK	24	30	
Operator	W BENALLY	35	30	9.5
Derrick	R SLAUGH → FILLED BT #345			9.5
Floors	P ROMERO			9.5
Floors *	J CHRISTENSEN			9.5
Floors				

REPROGRAPHICS 0905764