
ENGINEERING ▼ ▼ ▼
FARMINGTON, NM

Hole Size 12-1/4"
Surf Csg @ 1408' KB
8-5/8", 24#, J-55
Cement w/ 395sx (814 cf) Type V 2% SMS
Tail 140sx (165cf) Type V 1% Caci2
Circ cmt to surf

30-045-34082

FEB 08 2016

Hole Size 7-7/8"
5-1/2", 15.5#, J55 at 4509' KB; Stage tool at 2224'
1st stg: Cemented w/ 345sx(652cf) of 65/35 POZ
100sx(146cf) of 50/50 POZ
Circ cmt to surf
2nd stg: Cemented w/ 260sx(491cf) of 65/35 POZ
50sx(59cf) of Type V neat
Circ cmt to surf

Tubing Detail			
	Length	Top	Bottom
KB Adjustment			0 13.5
102 lbs of 2-7/8", 6.5#, EUE, J55, IPC	3176.67	13.50	3190.17
AS1-X 6K Packer	9.20	3190.17	3199.37
		3199.37	3199.37
			0.00

[illegible]

	Pump Detail
--	-------------

Pumping Unit: _____ Gear Sheave: _____
 API Designation: _____ Stroke Length: _____
 Samson Post SN: _____ Gear Ratio: _____
 Gear Box SN: _____ SPM: _____
 Structural Unbalance: _____ Horse Power: _____
 Power: _____ Volts: _____
 Power SN: _____ Amps: _____
 Sheave Size: _____ Belts: _____

[illegible]