

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
CONOCOPHILLIPS CO.

3a. Address 3b. Phone No. (include area code)
P.O. BOX 2197 WL3 6108 HOUSTON TX 77252 (832)486-2326

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660 NORTH 2250 EAST
UL: B, Sec: 5, T: 29N, R: 6W

5. Lease Serial No.

8F 080377

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

SAN JUAN 29-6 UNIT 59B

9. API Well No.

30-039-29463

10. Field and Pool, or Exploratory Area
BLANCO MESAVERDE

11. County or Parish, State
RIO ARRIBA
NEW MEXICO


12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

ConocoPhillips requests approval to topset this well to prevent lost circulation problems. Attached are the new cement calculations.

Verbal given 3/17/06



2006 MAR 16 PM 2 43
RECEIVED
OTO FARMINGTON NM

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

DEBORAH MARBERRY

Title REGULATORY ANALYST

Signature

Deborah Marberry

Date 03/15/2006

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Andrea Brunley

Title PE

Date

3/17/06

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

FFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

NMOCDD

San Juan 29-6 # 59B
Schlumberger Cementing Program

SURFACE CASING :

Drill Bit Diameter	12.25"	
Casing Outside Diameter	9.625"	Casing Inside Diam. 9.001"
Casing Weight	32.3	ppf
Casing Grade	H-40	
Shoe Depth	235'	
Cement Yield	1.17	cuft/sk
Cement Density	15.8	lb/gal
Excess Cement	125	%
Cement Required	150	sx

SHOE 235 ', 9.625 ", 32.3 ppf, H-40 STC

INTERMEDIATE CASING :

Drill Bit Diameter	8.75"	
Casing Outside Diameter	7"	Casing Inside Diam. 6.456"
Casing Weight	20	ppf
Casing Grade	J-55	
Shoe Depth	3212'	
Lead Cement Yield	2.63	cuft/sk
Lead Cement Density	11.7	lb/gal
Lead Cement Excess	150	%
Lead Cement Required	349	sx
Tail Cement Length	642.4'	
Tail Cement Yield	1.28	cuft/sk
Tail Cement Density	13.5	lb/gal
Tail Cement Excess	150	%
Tail Cement Required	196	sx

SHOE 3212 ', 7 ", 20 ppf, J-55 STC

PRODUCTION CASING :

Drill Bit Diameter	6.25"	
Casing Outside Diameter	4.5"	Casing Inside Diam. 4.052"
Casing Weight	10.5	ppf
Casing Grade	J-55	
Top of Cement	3012'	200' inside intermediate casing
Shoe Depth	5927'	
Cement Yield	1.44	cuft/sk
Cement Density	13	lb/gal
Cement Excess	50	%
Cement Required	307	sx

SHOE 5927 ', 4.5 ", 10.5 ppf, J-55 LTC