OIL COMS. DIE

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

APR 26 2016

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Leas	e Name ROSS	S FEDERAL		Well No. 1M	
Location of We	ell: Unit L	etter P S	Sec 23	Twp 030N	Rge	011W API	# 30-045-29744	
Name of Reservoir or Pool			ol .	Type of Prod		Method of Prod	Prod Medium	
Upper Completion	Completion MV				Flow		Tubing	
Lower Completion	DK		Gas		Flow		Tubing	
			Pre-Flow S	Shut-In Pressu	ire Data			
Upper Completion	ompletion 4/12/2016			Length of Time Shut-In 229 hours		ss. PSIG 238	Stabilized?(Yes or No) Yes	
Lower Completion		te, Shut-In 2/2016		of Time Shut-In hours	SI Pre	ss. PSIG 416	Stabilized?(Yes or No) Yes	
			Flo	ow Test No. 1				
Commenced	at:	4/18/2016		Zone Pro	oducing (Uppe	r or Lower): LC	OWER	
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SSURE Lower zone	Prod Zone Temperature		Remarks	
4/18/2016 1:37:43 PM		13	238	416	55	flow rate 142		
4/19/2016 12:48:19 PM		36	238	49 53 Flow rate 134 / Csg psi 241		sg psi 241		
4/20/2016 1:01:01 PM		61	239	50	58	Flow rate 45 / Csg psi 245		
4/21/2016 1:19:22 PM 85			241	51	59	Flow rate 34 / Csg psi 246		
Production rate	e during to	est						
Oil: BPOD Based on:			Bbls. In	Bbls. In Hrs.		Grav.	GOR	
Gas		MCFPD; Test th	hru (Orifice or N	Meter)				
Upper Completion	Upper Hour, Date, Shut-In			Aid-Test Shut-In Pressure De Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)	
Lower Completion	Hour, Da	te, Shut-In	Length	of Time Shut-In	SI Pre	ss. PSIG	Stabilized?(Yes or No)	

(Continue on reverse side)

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

		Zone Producing (Upper or Lower)					
Time	Lapsed Time Since*	PRESSURE		Prod Zone			
(date/time)		Upper zone	Lower zone	Temperature	Remarks		
il: BPO	D Based on: MCFPD; Test t	hru (Orifice or M	Hrs.				
emarks:							
emarks:							
emarks:							
emarks:							
	e information herein	contained is true	and complete	to the best of my kr	nowledge.		
		contained is true		to the best of my kr	nowledge.		
nereby certify that the					owledge.		
nereby certify that the	4PM		Opera	tor: BR			
nereby certify that the pproved: 28 -/ New Mexico Oil Co	anservation Division Duvion		Opera By:	tor: BR Paul Sikora II	ator		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3