DISTRICT 1
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico **Energy Minerals and Natural Resources**

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

	k covered by a "general plan"? Yes No r below-grade tank Closure of a pit or below-gra		
Operator: BP AMERICA PROD. CO. Address: 200 ENERGY COURT, FARMINGTON, Facility or well name: CASE A #2 County: SAN JUAN Latitude 36.90323 Longitude 108	NM 87410 API#: 30-045- 23434 U/L or Qtr/Q	Qtr_D_Sec_17	T 31N R 11W
Below-grade tank Volume:bblType_offluid: / Workover _ Emergency			
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	0
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)	0
Distance to surface water: (horizontal distance to all wetlands, playas, gation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's your are burying in place) onsite ☑ offsite ☐ If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No ☑ You Attach soil sample results and a diagram of sample locations and excavation.	. (3) Attach a general of Yes If yes, show depth below ground surface	description of remedial ac	ction taken including
Additional Comments: PIT LOCATED APPROXIMATELY PIT EXCAVATION: WIDTH N/Aft., LENGTH PIT REMEDIATION: CLOSE AS IS: ⊠. LANDFARM: □. C Cubic yards: N/A	y 78 ft. N7W from we N/Aft., depth N/Aft	CLL HEAD	ER 2006 ECEIVED CONS. DIV.
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date:	SignatureSignature	the above-described pill approved plan \(\text{\tin}\text{\texi\text{\texi}\text{\texi{\text{\texi{\texi{\texi{\texi{\texi{\texi{\texi\texi{\texit{\texi{\texi{\texi{\texi{\texi{\texi{\texi{\texi{\t	or below-grade tank
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. Priorval: Signature Signature Signature Date:			

. I DLAV	GG ENGINEERING	INC	7)
0.	87, BLOOMFIELD	•	LOCATION NO: <u>\$1547</u>
	(505) 632-1199	, INIVI 0/413	COCR NO: 13885
FIELD REPORT: PIT CL	OSURE VERIF	ICATION	PAGE No:/_ of/_
LOCATION: NAME: CASE A	WELL#: 2 TYPE	: 5EP .	DATE STARTED: 6/15/05
	G: 1 PM: HYM CNTY: 5	ST: UM	DATE FINISHED:
QTR/FOOTAGE: 950/N71070'W NW			ENVIRONMENTAL SPECIALIST:
EXCAVATION APPROXNA FT. x			
D- 77 0 0	REMEDIA		
LAND USE: RANGE - BLM		595 FOI	
			FROM WELLHEAD.
<u> </u>	ATER SOURCE: 2/000		DE WATER:
NMOCD RANKING SCORE: NMOCD TPH	CLOSURE STD: 5,000 PI	°м	
SOIL AND EXCAVATION DESCRIP	•	OVM CALIB. READ	
COLL / HTD EXC/(V/(HON DECONN)		OVM CALIB. GAS	$= \frac{100}{100} \text{ ppm} \qquad \frac{\text{RF} = 0.52}{100}$
SOIL TYPE: (SAND) / SILTY SAND / SILT / SILTY	CLAY / CLAY / GRAVEL / OTH		
SOIL COLOR: PALE YELL DRAJGE 7	O MED. GRAY	BEDROCK - UT	, TO MED, GRAY
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL		COHESIVE	
CONSISTENCY (NON COHESIVE SOILS) TOOSE/FIRM PEASTICITY-(CLAYS): NON PLASTIC / SLIGHTLY PLAS		/ HIGHLY PLASTIC	
DENSITY (COHESIVE CLAYS & SILTS)> SOFT / FIRM / S			(CO2ED)
MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SA		/	
DISCOLORATION/STAINING OBSERVED YES / NO EX HC ODOR DETECTED: YES NO EXPLANATION - 013	PLANATION - BET. 3-3.5	BEWW GRADE	T BEDROCK JUNEACE,
SAMPLE TYPE: GRAB COMPOSITE - # OF PTS.		_	,
ADDITIONAL COMMENTS: COLLECTED SAMPLE	E FROM BEDROCK 51	REACE. BED	RUCK-VERY HARD,
BOTTOM COMPETENT.			
	FIELD 418.1 CALC	ULATIONS	
SCALE SAMP. TIME SAMP. ID	LAB NO. WEIGHT (g)	mL FREON DIL	JTION READING CALC. (ppm)
0 FT			
PIT PERIMETER ♠N		F	IT PROFILE
P.D.~2'	OVM READING		
0.1/	I KEADING		
P.D. 8. 6.	SAMPLE FIELD HEADSPACE		
6.0	SAMPLE FIELD HEADSPACE (ppm)		
BERN B.G.	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / 564 2 @		
BERN	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / 564 2 @ 3 @		
BERN 5	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / 564 2 @		
BERN	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / / 564 2 @ 3 @ 4 @	No	T APPLICABLE
BERN	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / / 564 2 @ 3 @ 4 @	No	T APPLICABLE
BERN 5 21 AD E	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5 / / 564 2 @ 3 @ 4 @	No	T APPLICABLE
BERN 5 21 AD E	SAMPLE FIELD HEADSPACE (ppm) 1 @ 3.5	No	T APPLICABLE
BERN 5 E P	SAMPLE ID FIELD HEADSPACE (ppm) 1 @ 3.5 / 564 2 @ 3 @ 4 @ 5 @ 5 @ LAB SAMPLES SAMPLE ANALYSIS TIME		T APPLICABLE
BERN 5 E P	SAMPLE ID FIELD HEADSPACE (ppm) 1 @ 3.5 / / 564 2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 MPLES SAMPLE ANALYSIS TIME D @ 3.5 / PH (\$0158) 1255		T APPLICABLE
BERN 5 E P	SAMPLE ID FIELD HEADSPACE (ppm) 1 @ 3.5 / 1,564 2 @ 3.6 / 4 @ 5 @ 5 @ LAB SAMPLES SAMPLE ANALYSIS TIME		T APPLICABLE
BERN SE P T.H. WI.S' B.O. WELD WEEDD	SAMPLE ID FIELD HEADSPACE (ppm) 1 @ 3.5 / 1,564 2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 MPLES LAB SAMPLES SAMPLE ANALYSIS TIME D @ 3.5 TPH (\$0.58) 12.5 " BIEX (\$0.21.8)"		T APPLICABLE
BERN 5 E P	SAMPLE ID FIELD HEADSPACE (ppm) 1 @ 3.5 / 1,564 2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 MPLES LAB SAMPLES SAMPLE ANALYSIS TIME D @ 3.5 TPH (\$0.58) 12.5 " BIEX (\$0.21.8)"		T APPLICABLE



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 3.5'	Date Reported:	06-17-05
Laboratory Number:	33357	Date Sampled:	06-15-05
Chain of Custody No:	13885	Date Received:	06-15-05
Sample Matrix:	Soil	Date Extracted:	06-16-05
Preservative:	Cool	Date Analyzed:	06-17-05
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	
Gasoline Range (C5 - C10)	29.8	0.2	
Diesel Range (C10 - C28)	7.2	0.1	
Total Petroleum Hydrocarbons	37.0	0.2	

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Case A #2 Separator Pit Grab Sample.

Analyst C. Comments

Review Walter

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Proiect #:	94034-010
Sample ID:	1 @ 3.5'	Date Reported:	06-17-05
Laboratory Number:	33357	Date Sampled:	06-15-05
Chain of Custody:	13885	Date Received:	06-15-05
Sample Matrix:	Soil	Date Analyzed:	06-17-05
Preservative:	Cool	Date Extracted:	06-16-05
Condition:	Cool & Intact	Analysis Requested:	BTEX

	Det.		
Parameter	Concentration (ug/Kg)	Limit (ug/Kg)	
Benzene	122	2.1	
Toluene	673	1.8	
Ethylbenzene	667	1.7	
p,m-Xylene	5,830	1.5	
o-Xylene	1,150	2.2	-
Total BTEX	8,440		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Case A #2 Separator Pit Grab Sample.

Analyst C. Cyanton

Mustine m Walten
Review