District 1 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

District IV 220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

	de Tank Registration or Closu		
ls pit or below-grade tan. Type of action: Registration of a pit o	k covered by a "general plan"? Yes No or below-grade tank \(\subseteq\) Closure of a pit or below-gra	i∐ ade tank ⊠	
Address: 200 ENERGY COURT, FARMINGTON.	API#: 30-045- 24184 U/L or Qtr/	/Qtr_ E _ Sec_ 19	
Pit Type: Drilling Production Disposal DEHYDRATOR II Workover Emergency Lined Unlined STEEL TANK Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl_Type-ef-fluid: Construction material: Double-walled, with leak detection? Yes If		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	10
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)	0
Distance to surface water: (horizontal distance to all wetlands, playas, jgation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	10
	Ranking Score (Total Points)		20
If this is a pit closure: (1) attach a diagram of the facility showing the pit's your are burying in place) onsite ☑ offsite ☐ If offsite, name of facility_emediation start date and end date. (4) Groundwater encountered: No ☑ You Attach soil sample results and a diagram of sample locations and excavation Additional Comments: PIT LOCATED APPROXIMATELY PIT EXCAVATION: WIDTH n/a ft., LENGTH PIT REMEDIATION: CLOSE AS IS: ☑, LANDFARM: ☐. Cubic yards: N/A	. (3) Attach a general Yes If yes, show depth below ground surface IS. Y 75 FT. S88W FROM WIND IN 1/2 ft. DEPTH IN 1/2 ft	description of remedialft. and attack	action taken including h sample results. (5) FER 2008
BEDROCK BOTTOM			TIBLE S
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date: 03/04/05 PrintedName/Title Jeff Blagg - P.E. # 11607 Your certification and NMOCD approval of this application/closure does rotherwise endanger public health or the environment. Nor does it relieve to regulations.	Signature	-approved plan ⊠.	aminate ground water or
proval: OSPUTY ON & GAS INSPECTOR, DIST. &	gnature Deny For	Date: FEB	2 1 2006

<u>50 - 045 - 2418</u> .	4 56.6.	7704 × 101.16167	VUL					
	BLAG	G ENGINEERING 87, BLOOMFIELD		LOCATION NO: BOOZ!				
CLIENT: <u>BP</u>		505) 632-1199	, 14101 07413	COCR NO: HALL				
FIELD REPO	ORT: PIT CLO	OSURE VERIF	CATION					
 -		WELL#: 8M TYPE		DATE STARTED: 2-28-05 DATE FINISHED: 2-28-05				
	1 1	BW PM: NM CNTY: S	`					
		WINW CONTRACTOR: SHER						
		<u> </u>						
				CLOSE AS 15				
		LEASE: NM 03549						
FIELD NOTES & RE				FROM WELLHEAD.				
	_	ATER SOURCE: >1000		ACE WATER:				
NMOCD RANKING SCORE:	NMOCD TPH	CLOSURE STD: 100 P	p					
SOIL AND EXCAV	ATION DESCRIPT	ION:	L .	D. = <u>53.の</u> ppm := (00 ppm <u>RF = 0.52</u>)				
			TIME: <u>1800</u>	am/pm DATE: 2-29-05				
SOIL TYPE: SAND/ SILT		CLAY / CLAY / GRAVEL OTH	ER) FIRM B	edrack @ 5'				
COHESION (ALL OTHERS):	NON COHESIVE) SLIGHTLY	COHESIVE / COHESIVE / HIGHLY						
f i		/ DENSE (VERY DENSE - & d IC / COHESIVE / MEDIUM PLASTIC						
DENSITY (COHESIVE CLAYS	& SILTS): SOFT / FIRM / STI	IFF / VERY STIFF / HARD		(CLOSED)				
MOISTURE: DRY / SLIGHTLY	Y MOIST MOIST WET / SAT	TURATED / SUPER SATURATED	Proch (Coox	51-52 (TAN@ 52)				
I HC ODOR DETECTED (YES)	YNO EXPLANATION -	MANOK		-				
SAMPLE TYPE: GRABY COM	MPOSITE - # OF PTS.	19'x 19'x 4'	DEAD PIT I	11/21 BBL Steel				
DEDICO	- lank, Use Duck	the to remove tour	Jayre "	Dense bedrock @				
BOTTOM 5'- SCRAPE TO 52 WITH BACKHUE TO SAMPLE FIELD 418.1 CALCULATIONS								
SCALE SAN	MP. TIME SAMP. ID		·	LUTION READING CALC. (ppm)				
O _T FT								
N PIT PERI	METER	¬ ~ ~ ~ ~		PIT PROFILE				
A'	PP	OVM READING						
19'	PD BU	SAMPLE FIELD HEADSPACE	<u> </u>					
		1@ 5 36						
	(5½ Bb)	2 @ 3 @						
./	1 (52)	4 @ 5 @	_A_	STAN TO 5 12 A				
19'			ゴル	STAIN				
			$-\Gamma \cup \mathcal{L}$	5 52				
	()							
1	1	LAD CAMPLEO]////	77/////				
ole	TANK FOOT PRINT (4'BG)	LAB SAMPLES SAMPLE ANALYSIS TIM						
Sample A	PRINT (4'156)	DOST TAT 172						
1			\exists F	TIRM BEDIZOCK				
P.D. = PIT DEPRESSION; B.G. = f.H. = TEST HOLE; ~ = APPROX				Sandstan?				
TRAVEL NOTES	· · · · · · · · · · · · · · · · · · ·	_	2-20					
I CA	LLOUT: <u>2-28-05</u>	ONSITE: _	2-28-05					

Hall Environmental Analysis Laboratory

Date: 09-Mar-05

CLIENT:

Blagg Engineering

Lab Order:

0503011

Project:

Florance C 8M

Lab ID:

0503011-03

Client Sample ID: Dehy #1 @ 5.5'

Collection Date: 2/28/2005 5:25:00 PM

Matrix: SOIL

Analyses	Result	PQL Qu	nal Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	SE ORGANICS		· ·		Analyst: SCC
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	3/4/2005 1:47:56 PM
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	3/4/2005 1:47:56 PM
Surr: DNOP	94.4	60-124	%REC	1	3/4/2005 1:47:56 PM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	3/3/2005 8:36:24 PM
Surr: BFB	104	78.3-120	%REC	1	3/3/2005 8:36:24 PM

B - Analyte detected in the associated Method Blank

^{* -} Value exceeds Maximum Contaminant Level

S - Spike Recovery outside accepted recovery limits

R - RPD outside accepted recovery limits

E - Value above quantitation range