

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 18 2016

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

5. Lease Serial No. **SF-080844**

SUNDRY NOTICES AND REPORTS ON WELLS *Burlington Field Office*
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		7. If Unit of CA/Agreement, Name and/or No.
2. Name of Operator Burlington Resources Oil & Gas Company LP		8. Well Name and No. T L Rhodes B 1
3a. Address PO Box 4289, Farmington, NM 87499	3b. Phone No. (include area code) (505) 326-9700	9. API Well No. 30-045-11777
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Surface Unit O (SWSE), 839' FSL & 2013' FEL, Sec. 20, T28N, R11W		10. Field and Pool or Exploratory Area Basin FC / Aztec PC
		11. Country or Parish, State San Juan, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

The subject well is part of the proposed Mangum SRC 1C P&A program agreed to with the NMOCD. The attached revised procedure replaces the procedure filed with the P&A NOI submitted on 3/30/2016.

Notify NMOCD 24 hrs
prior to beginning
operations

OIL CONS. DIV DIST. 3

JUN 01 2016

BLM'S APPROVAL OR ACCEPTANCE OF THIS ACTION DOES NOT RELIEVE THE LESSEE AND OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Dollie L. Busse Title **Regulatory Technician**

Signature *Dollie L. Busse* Date **5/16/16**

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by *[Signature]* Title **PE** Date **5/31/16**

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office **FFO**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

2016

ConocoPhillips
T L RHODES B 1
Expense - P&A

Lat 36° 38' 33.684" N

Long 108° 1' 27.948" W

PROCEDURE

This project requires the use of an A-Plus steel tank to handle waste fluids circulated from the well and cement wash up.

Prior to commencing abandonment operations, ensure that the bradenhead valve is dug out and properly plumbed to the surface. Record the casing, intermediate and bradenhead pressures with an appropriately ranged gauge. Contact the Engineer if bradenhead pressure is present (per Exhibit "A-3").

1. Hold pre-job safety meeting. Comply with all NMOCD, BLM, and COP safety and environmental regulations. Test rig anchors prior to moving in rig.

2. MIRU workover rig. Check casing, tubing, and bradenhead pressures and record them in WellView. **If there is pressure on the BH, contact the Wells Engineer.**

3. Remove existing piping on casing valve. RU blow lines from casing valves and begin blowing down casing pressure. Kill well as necessary. Ensure well is dead or on a vacuum.

4. ND wellhead and NU BOPE with 2-7/8" Rams. Pressure and function test BOP to 250 psi low and 1000 psi over SICP high to a maximum of 2000 psi held and charted for 10 minutes per COP Well Control Manual. PU and remove tubing hanger.

5. TOOH with tubing (per pertinent data sheet).

Tubing size: 1.66" 2.33# J-55

Set Depth: 1,693'

KB: 12'

Tubing size: 2-7/8" 6.4# UFJ J-55

Set Depth: 1,704'

6. PU 3-3/4" bit and watermelon mill and round trip as deep as possible above top perforation at 1,352'.

7. PU 4-1/2" CR on tubing, and set at 1,302'. Pressure test tubing to 1000 psi. Sting out of CR. Load hole, and pressure test casing to 800 psi. If casing does not test, spot or tag subsequent plugs as appropriate. POOH with tubing.

8. RU wireline and run CBL with 500 psi on casing from CR at 1,302' to surface to identify TOC. Adjust plugs as necessary for new TOC. *Email log copy to Wells Engineer, Troy Salyers (BLM) at tsalyers@blm.gov, and Brandon Powell (NMOCD) at brandon.powell@state.nm.us upon completion of logging operations.*

All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures. All cement will be ASTM Class B mixed at 15.6 ppg with a 1.18 cf/sk yield.

9. Plug 1 - Fruitland Formation Top and Perforations, 1040' - 1302', 24 Sacks Class B Cement

Mix 24 sx Class B cement and spot a balanced plug inside the casing to cover the Fruitland top and perforations. PUH.

10. Roll the hole with water and ensure that the wellbore is in a stabilized condition with no flow of gas and/or water before spotting the next plug. If flow occurs, the fluid weight must be increased until a stabilized condition is established (per Exhibit "A-3").

11. Cease operations for 30 minutes allowing the bradenhead to be observed for pressure build. Record pressures with crystal gauge for accuracy. If pressures are observed, notify Wells Engineer and Production Engineering for path-forward discussion with NMOCD (per Exhibit "A-3").

12. Plug 2 - Ojo Alamo and Kirtland Formation Tops, 367' - 582', 21 Sacks Class B Cement

Mix 21 sx Class B cement and spot a balanced plug inside the casing to cover the Ojo Alamo and Kirtland tops. POOH.

13. Plug 3 - Surface Shoe and Surface Plug, 0' - 350', 115 Sacks Class B Cement

RU WL and perforate 4 big hole charge (if available) squeeze holes at 350'. TOOH and RD wireline. Observe well for 30 minutes per BLM regulations. RU pump, close blind rams and establish circulation out bradenhead with water. Circulate BH clean. TIH with 4-1/2" CR and set at 300'. Mix 84 sx Class B cement and squeeze until good cement returns to surface out BH valve. Shut BH valve and squeeze to max 200 psi. Sting out of CR and reverse circulate cement out of tubing. TOOH and LD stinger. TIH with open ended tubing to 300'. Mix 31 sx Class B cement and pump inside plug. TOOH and LD Tubing. SI well and WOC.

14. Nipple down BOP and cut off casing below the casing flange. Install P&A marker with cement to comply with regulations. RDMO.

Exhibit "A-3"

To Final Agreement - Withdrawal of Notice of Violation (3-15-02)
dated May 4, 2016 from ConocoPhillips Company to NMOCD

Updated Abandonment Procedures

The following procedural changes will be required for the P&A Program:

- 1) Prior to commencing abandonment operations, ensure that the bradenhead valve is dug out and properly plumbed to the surface. Record the casing, intermediate and bradenhead pressures with an appropriately ranged gauge. Contact the Engineer if bradenhead pressure is present. After the last set of completion perforations are abandoned with cement, roll the hole with water and ensure that the wellbore is in a stabilized condition with no flow of gas and/or water before spotting the next plug. If flow occurs, the fluid weight must be increased until a stabilized condition is established.
- 2) Following the plug over the Fruitland Formation Top, and prior to the plug over the Kirtland and Ojo Alamo Tops:
 - a. Operations will cease for 30 minutes allowing the Bradenhead to be observed for pressure build.
 - b. Pressures will be recorded with a crystal gauge for accuracy.
 - c. If pressures are observed, notify Wells Engineer and Production Engineering for path-forward discussion with NMOCD.
- 3) Within 24 hours of the abandonment and after two weeks, BLM will check for the presence of gas at the base of the dry hole marker and at the weep hole. Note ambient weather conditions when recording the results. If gas is detected, contact the Engineer.
- 4) If a Cathodic Protection well is on the well pad, check for the presence of gas at the vent cap. If gas is present, record results in AFMSS and contact the Engineer.

Note: when checking any sample point for the presence of gas, please be prepared for the possibility of anomalous pressure and the H2S gas.

District NORTH	Field Name AZTEC FRUITLAND SAND (GAS)	API / UWI 3004511777	County SAN JUAN	State/Province NEW MEXICO
Original Spud Date 6/16/1966	Surface Legal Location 020-028N-011W-O	East/West Distance (ft) 2,013.00	East/West Reference FEL	North/South Distance (ft) 839.00
North/South Reference FSL				

Original Hole, 3/3/2016 2:34:11 PM

Vertical schematic (actual)	MD (ftKB)	Formation Tops
Cross Over; 2 7/8 in; 6.40 lb/ft; J-55; 12.0 ftKB; 13.0 ftKB	6.6	
Tubing; 1.66 in; 2.33 lb/ft; J-55; 6.5 ftKB; 39.0 ftKB	13.1	
Tubing Pup Joint; 1.66 in; 2.33 lb/ft; J-55; 39.0 ftKB; 41.0 ftKB	41.0	
1; Surface; 8 5/8 in; 8.097 in; 12.0 ftKB; 359.0 ftKB	359.9	
Tubing; 2 7/8 in; 6.40 lb/ft; J-55; 13.0 ftKB; 1,702.4 ftKB	532.2	OJO ALAMO KIRTLAND FRUITLAND
Tubing; 1.66 in; 2.33 lb/ft; J-55; 41.0 ftKB; 1,702.4 ftKB	1,352.0	
Fruitland; 1,352.0-1,572.0; 4/26/2003	1,579.1	PICTURED CLI...
Upper Pictured Cliffs; 1,598.0-1,604.0; 4/26/2003	1,604.0	
Lower Pictured Cliffs; 1,625.0-1,635.0; 4/26/2003	1,634.8	
Jet Pump Diffuser; 1.66 in; 2.33 lb/ft; J-55; 1,702.4 ftKB; 1,703.4 ftKB	1,703.4	
Jet Pump Serial # S-250-35; 2 7/8 in; 1,702.4 ftKB; 1,704.4 ftKB	1,718.5	
Sand Screen; 2 3/8 in; 1,704.4 ftKB; 1,718.4 ftKB	1,805.1	
PBD; 1,800.0	1,993.1	
Bridge Plug - Permanent; 1,800.0-1,805.0	2,990.2	CHACRA
Stage 3; 360.0-1,815.0; 7/21/1966; Records contain no cement information for stage 3 but TOC is estimated @ 360' - CBL 4-24-03.	3,151.9	CLIFF HOUSE
Cement Plug 3; 2,990.0-3,152.0; Plug 3 from 2990'- 3152'.	3,299.9	MENEFE
Cement Squeeze; 3,299.0-3,590.0; 1/7/1974; Squeezed hole @ 3590' with 100 sxs Class 'A' Neat, did not pressure up. Squeezed again with 75 sxs Class 'A' Cement. TOC @ 3299' - 75% Efficiency Calculation.	3,962.9	POINT LOOKO...
Stage 2; 1,993.0-4,403.0; 7/21/1966; Cemented Stage 2 with 550 sxs Class 'C' Cement, followed by 50 sxs Class 'C' Neat. TOC @ 1993' - 75% Efficiency Calculation.	4,402.9	MANCOS
Cement Plug 2; 5,090.0-5,247.0; Plug 2 From 5090'- 5247'.	5,179.1	GALLUP
Cement Plug 1; 5,843.0-6,000.0; Set cement plugs with 12 sxs ASTM Type III Cement. Plug 1 From 5843'- 6000'.	5,842.8	GREENHORN
Bridge Plug - Permanent; 6,000.0-6,005.0	6,000.0	
Fish; 6,020.0-6,111.0; 4" Model Packer with tail joint below it	6,011.2	GRANEROS
Upper Dakota; 6,061.0-6,072.0; 7/21/1966	6,042.0	TWO WELLS
Lower Dakota; 6,113.0-6,142.0; 7/21/1966	6,071.9	PAGUATE
Stage 1; 4,403.0-6,248.0; 7/21/1966; Cemented Stage 1 with 400 sxs Class 'C' Cement, followed by 100 sxs Class 'C' Neat TOC @ Stage Tool @ 4403' - 75% Efficiency Calculation.	6,110.9	
Auto cement plug; 6,211.0-6,248.0; 7/21/1966; Automatically created cement plug from the casing cement because it had a tagged depth.	6,142.1	CUBERO
2; Production 1; 4 1/2 in; 4.052 in; 12.0 ftKB; 6,248.0 ftKB	6,211.0	ENCINAL
	6,248.0	

Schematic - Proposed

API / UWI 3004511777	Surface Legal Location 020-028N-011W-0	Field Name AZTEC FRUITLAND SAND (SAB)	License No	State/Province NEW MEXICO	Well Configuration Type
Ground Elevation (ft) 5,674.00	Original KS-RT Elevation (ft) 5,686.00	KS-Ground Distance (ft) 12.00	KS-Casing Flange Distance (ft) 5,686.00	KS-Tubing Hanger Distance (ft) 5,686.00	

Original Hole, 1/1/2020 12:03:00 AM

Vertical schematic (actual)		MD (ftKB)	Formation Tops
	Plug #3- Squeeze ; 12.0-350.0; 1/1/2020; Mix 84 sx Class B Cement and squeeze to surface	12.1	
Bridge Plug - Permanent; 300.0-302.0	Plug #3 ; 12.0-350.0; 1/1/2020; Mix 31 sx Class B Cement, Spot a balanced plug to surface.	301.8	
Perf. 350.0; 1/1/2020 1; Surface; 8 5/8 in; 8.097 in; 12.0 ftKB; 359.0 ftKB	Surface Casing Cement; 12.0-359.0; 6/16/1966; Cemented with 200 sxs Class 'A' Cement, circulated to surface.	358.9	
	Plug #2 ; 367.0-582.0; 1/1/2020; Mix 21 sx Class B Cement, Spot a balanced Plug	367.1	OJO ALAMO KIRTLAND
	Plug #1 ; 1,040.0-1,302.0; 1/1/2020; Mix 24 sx Class B Cement, Spot a balanced Plug	532.2	
Bridge Plug - Permanent; 1,302.0-1,304.0		1,040.0	FRUITLAND
Fruitland; 1,352.0-1,572.0; 4/26/2003		1,301.8	
		1,352.0	PICTURED CL...
Upper Pictured Cliffs; 1,598.0-1,604.0; 4/26/2003		1,579.1	
Lower Pictured Cliffs; 1,625.0-1,635.0; 4/26/2003		1,604.0	
PBTD: 1,800.0		1,634.8	
Bridge Plug - Permanent; 1,800.0-1,805.0	Stage 3; 360.0-1,815.0; 7/21/1966; Records contain no cement information for stage 3 but TOC is estimated @ 360' - CBL 4-24-03.	1,805.1	CHACRA
	Cement Plug 3; 2,990.0-3,152.0; Plug 3 from 2990' - 3152'	1,993.1	
	Cement Squeeze; 3,299.0-3,590.0; 1/7/1974; Squeezed hole @ 3590' with 100 sxs Class 'A' Neat, did not pressure up. Squeezed again with 75 sxs Class 'A' Cement. TOC @ 3299' - 75% Efficiency Calculation.	2,990.2	CLIFF HOUSE
	Stage 2; 1,993.0-4,403.0; 7/21/1966; Cemented Stage 2 with 550 sxs Class 'C' Cement, followed by 50 sxs Class 'C' Neat. TOC @ 1993' - 75% Efficiency Calculation.	3,151.9	MENEFFEE
	Cement Plug 2; 5,090.0-5,247.0; Plug 2 From 5090' - 5247'	3,298.9	POINT LOOKO... MANCOS
	Cement Plug 1; 5,843.0-6,000.0; Set cement plugs with 12 sxs ASTM Type III Cement. Plug 1 From 5843' - 6000'	3,962.9	
Bridge Plug - Permanent; 6,000.0-6,005.0		4,402.9	GALLUP
		5,179.1	
		5,842.8	GREENHORN
Fish; 6,020.0-6,111.0; 4" Model Packer with tail joint below it		6,000.0	GRANEROS
Upper Dakota; 6,061.0-6,072.0; 7/21/1966		6,011.2	TWO WELLS
	Auto cement plug; 6,211.0-6,248.0; 7/21/1966; Automatically created cement plug from the casing cement because it had a tagged depth.	6,042.0	
	Stage 1; 4,403.0-6,248.0; 7/21/1966; Cemented Stage 1 with 400 sxs Class 'C' Cement, followed by 100 sxs Class 'C' Neat TOC @ Stage Tool @ 4403' - 75% Efficiency Calculation.	6,071.9	PAGUATE
Lower Dakota; 6,113.0-6,142.0; 7/21/1966		6,110.9	
		6,142.1	CUBERO
		6,211.0	ENCINAL
2; Production 1; 4 1/2 in; 4.052 in; 12.0 ftKB; 6,248.0 ftKB		6,248.0	

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE
6251 COLLEGE BLVD.
FARMINGTON, NEW MEXICO 87402

Attachment to notice of
Intention to Abandon:

Re: Permanent Abandonment
Well: TL Rhodes B1

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 564-7750.

Operator will run CBL from CR @ 1,302 ft. to surface to verify cement top. Submit the electronic copy of the log for verification to the following addresses: jwsavage@blm.gov
Brandon.Powell@state.nm.us

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.