Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				M02901
				6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on page 2				it or CA/Agreement, Name and/or No.
Type of Well Oil Well				Name and No. ISOM A 13
2. Name of Operator Contact: MICHAEL T HANSON COLEMAN OIL & GAS INCORPORATE Mail: mhanson@cog-fmn.com				Well No. 45-24561-00-S1
3a. Address FARMINGTON, NM 87499	3b. Phone No. (include area c Ph: 505-327-0356 Ext: ' Fx: 505-327-9425		Field and Pool or Exploratory Area BLANCO P.C. SOUTH	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. Cou	nty or Parish, State
Sec 3 T26N R8W SWNW 1610FNL 0800FWL 36.518463 N Lat, 107.675644 W Lon			SAN	JUAN COUNTY, NM
12. CHECK THE A	PPROPRIATE BOX(ES) T	O INDICATE NATURI	E OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION		
✓ □ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start	Resume)
5	☐ Alter Casing	☐ Hydraulic Fracturi	ng Reclamation	■ Well Integrity
Subsequent Report	☐ Casing Repair	■ New Construction	□ Recomplete	☐ Other
☐ Final Abandonment Notice	☐ Change Plans	☑ Plug and Abandon	□ Temporarily Aba	ndon
	☐ Convert to Injection	□ Plug Back	■ Water Disposal	
Attach the Bond under which the w following completion of the involve testing has been completed. Final Adetermined that the site is ready for See the attached P&A Report	nally or recomplete horizontally, gi ork will be performed or provide the ed operations. If the operation resul Abandonment Notices must be filed final inspection.	ve subsurface locations and me Bond No. on file with BLM/lts in a multiple completion or only after all requirements, in	easured and true vertical dept BIA. Required subsequent re recompletion in a new intervi- cluding reclamation, have been	hs of all pertinent markers and zones. ports must be filed within 30 days al, a Form 3160-4 must be filed once
been reclaimed.				OIL CONS. DIV DIST. 3 FEB 2 4 2017
	Electronic Submission #36 For COLEMAN OIL & G tted to AFMSS for processing	SAS INCORPORATED, se	nt to the Farmington	S0027SE)
Name (Printed/Typed) MICHAE	L T HANSON	Title ENG	INEER	9
Signature (Electronic	Submission)	Date 01/2	7/2017	4
	THIS SPACE FOR	R FEDERAL OR STAT	E OFFICE USE	
_Approved By_ACCEPTED			GADIR ELMANDANI DLEUM ENGINEER	Date 02/22/2017
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			ington	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2) ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **



A-PLUS WELL SERVICE, INC.

P.O. BOX 1979

Farmington, New Mexico 87499 505-325-2627 *fax: 505-325-1211

Coleman Oil & Gas Inc. Newsom A 13 December 16, 2016

Page 1 of 1

1610' FNL and 800' FWL, Section 3, T-26-N, R-8-W San Juan County, NM Lease Number: NMNM02901 API #30-045-24561

Plug and Abandonment Report Notified NMOCD and BLM on 12/14/16

Plug and Abandonment Summary:

Plug #1 with 160 sxs (18.88 cf) Class B cement from 2800' to surface with 78 sxs inside and 82 sxs outside.

Plug #2 with 32 sxs Class B cement top off with poly pipe and Install P&A marker with coordinates N 36° 31' 04.80" / W 107° 40' 35.40".

Plugging Work Details:

12/15/16 Rode cement equipment to location. Spot in. **Spot plug #1** with TOC at surface. RD cement equipment. Attempt to move off location, unable due to road conditions. SDFD.

12/16/16 Travel to location. Open up well; no pressures. Write Hot Work Permit. Cut off wellhead. Found cement at surface in 2-7/8" and down 22' on backside. **Spot plug #2** top off with poly pipe and Install P&A marker with coordinates N 36° 31' 04.80" / W 107° 40' 35.40". MOL.

Bobby Espinoza, Coleman O&G representative, was on location. Dustin Porch, BLM representative, was on location.