Current Schematic ConocoPhillips Well Name: PIERCE A #4 Well Configuration Type VERTICAL Surface Legal Locatio API / UWI 3004526597 **NEW MEXICO** 013-030N-010W-P BASIN DAKOTA (PRORATED GAS) KB-Casing Flange Distance (ft KB-Tubing Hanger Distance (ft) Ground Elevation (ft) 6,302.00 6,314.00 12.00 VERTICAL - Original Hole, 7/25/2017 8:13:13 AM MD Formation (ftKB) Vertical schematic (actual) Tops 1; Surface; 9 5/8 in; 9.001 in; 12.0 ftKB; 12. 224 1 Surface Casing Cement; 12.0-231.0; 12/8/1985; CEMENT W/ 230 SXS 225.1 CLASS 'B', 1/4#/SX GEL-FLAKE & 3% CACL (271 CUFT). CIRCULATED TO 231.0 SURFACE. 2 HOURS AFTER, CMT NACIMIENTO 250.0 FELL 30', PUMPED ADDITIONAL 50 SXS CLASS B. 1,250.0 OJO ALAMO 1.663.1 **KIRTLAND** 1,796.9 FRUITI AND 2.411.1 2; Intermediate1; 7 in; 6.456 in; 12.0 2,700.1 ftKB; 3,313.0 ftKB Intermediate Casing Cement; 1,250.0-PICTURED ... 2,967.8 3.313.0; 12/10/1985; TOC 1250' RAN 3,312.0 BY TEMP SURVEY ON 12/10/1985. CEMENT W/ 199 SXS CLASS 'B', 65/35 3,313.0 POZMIX, 6% GEL, 2% CACL & 1/2 CUFT PERLITE/SX (384 CUFT) 3.315.0 Tubing: 1.90 in; 2.90 lb/ft; J-55; 12.1 FOLLOWED BY 100 SXS CLASS 'B' & ftKB; 7,410.3 ftKB CHACRA 3,981.0 2% CACL (118 CUFT) **CLIFF HOUSE** 4.578.1 MENEFEE 4.791.0 POINT LOO ... 5,217.8 OR CONS. DIV. DIST. 3 MANCOS 5,565.9 6,456.7 GALLUP 6 491 1 **GREENHORN** 7,232.9 7,289.0 **GRANEROS** TWO WELLS 7.335.0 Hydraulic Fracture; 1/8/1986; FRAC W/ 45,000# 40/60 SAND & 67,650 GALS 7,337.9 SLICKWATER PERF - DAKOTA; 7,338.0-7,461.0; 7,410.4 Pump Seating Nipple; 1.90 in; 7,410.3 1/8/1986 ftKB; 7,411.3 ftKB 7,411.4 Tubing; 1.90 in; 2.90 lb/ft; J-55; 7,411.3 **PAGUATE** ftKB; 7,444.0 ftKB 7.437.0 7,443.9 7,461.0 Auto cement plug; 7,538.0-7,552.0; **CUBERO** 12/15/1985; Automatically created cement plug from the casing cement 7,520.0 **ENCINAL** because it had a tagged depth. 3; Production1; 4 1/2 in; 4.000 in; 12.0 PBTD; 7,538.0 7,538.1 ftKB; 7,552.0 ftKB 7,543.3 Production Casing Cement; 2,700.0-7,552.0; 12/15/1985; TOC 2700' RAN 7,544.3 BY TEMP SURVEY ON 12/15/1985. CEMENT W/ 246 SXS CLASS 'B', 8% 7,550.5 GEL, 1/4#/SX FINE GILSONITE, 0.4% 7,551.8 HR-7 (534 CUFT) FOLLOWED BY 100 SXS CLASS 'B', 1/4#/SX FINE TUF-MORRISON 7 627 0 PLUG, 0.4% HR-7 (118 CUFT) Page 1/1 Report Printed: 7/25/2017