District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: Below grade tank registration

Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778 OIL CONS. DIV DIST. 3
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Florance U 006
API Number: 3004509284 OCD Permit Number:
U/L or Qtr/Qtr M Section 23 Township 30N Range 9W County: San Juan
Center of Proposed Design: Latitude 36.79154 Longitude -107.75582 NAD: □1927 ⋈ 1983
Surface Owner: N Federal N State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
Subsection I of 19.15.17.11 NMAC TANK A
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other <u>Single wall/ Double bottom; sidewalls not visible</u>
Liner type: Thicknessmil
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

H

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution on the school.						
institution or church) ☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet						
Alternate. Please specify						
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other						
☐ Monthly inspections (If netting or screening is not physically feasible)						
7. Signs: Subsection C of 19.15.17.11 NMAC						
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers						
☐ Signed in compliance with 19.15.16.8 NMAC						
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.						
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source					
General siting						
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No					
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No					
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No					
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No					
Below Grade Tanks						
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)						
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No					

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No					
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 						
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No					
Within 100 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site						
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC 15.17.9 NMAC					
Previously Approved Design (attach copy of design) API Number: or Permit Number:						
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	documents are
 ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan □ Emergency Response Plan □ Oil Field Waste Stream Characterization □ Monitoring and Inspection Plan 	
Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	luid Management Pit
On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 							
	☐ Yes ☐ No						
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division							
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological							
Society; Topographic map	☐ Yes ☐ No						
Within a 100-year floodplain FEMA map	☐ Yes ☐ No						
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC						
Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.						
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)							
	210217						
OCD Representative Signature: Cross OCD Permit Number:	812017						
OCD Representative Signature: Approval Date: 8 10 Title: OCD Permit Number: 19.	812017						
OCD Representative Signature: Approval Date: 8 19 19 19 19 19 19 19	the closure report.						
OCD Representative Signature: Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.						
OCD Representative Signature: Title: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this						

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this c belief. I also certify that the closure complies with all applicable closure r	closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Mus Min	Date:July 20, 2017
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

FLORANCE U 006 API No. 3004509284 Unit Letter M, Section 23, T30N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.017
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.066
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u>78</u>
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
811 S. First St., Artesia, NM 88210
District III District IV 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction						
						OPERA'	ΓOR	☐ Init	ial Report 🛛 Final Report					
Name of Co						Contact: Steve Moskal								
		Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9497								
Facility Name: Florance U 006						Facility Typ	e: Natural gas v	well						
Surface Ow	ner: Feder	al		Mineral C)wner:	Federal		API N	o. 3004509284					
				LOCA	TIO	N OF RE	LEASE	·						
Unit Letter M	Section 23	Township 20N	Range 9W	Feet from the 990		/South Line	Feet from the 990	East/West Line West	County: San Juan					
			La	titude <u>36.79</u>		Longitu	de <u>-107.755</u> EASE	582°						
Type of Rele	ase: none						Release: unknow	vn Volume	Recovered: N/A					
Source of Re	lease: below	v grade tank –	95 bbl			Date and I	Hour of Occurrence	ce: Date and	Hour of Discovery: none					
Was Immedi	ate Notice (Yes 🗵	No Not Re	equired	If YES, To	Whom?							
By Whom?						Date and I								
Was a Water	course Read		Yes 🛚	No		If YES, Vo	olume Impacting t	the Watercourse.						
Describe Cau	ise of Proble		dial Action	n Taken.* Sampli			the BGT was do		l. Soil analysis resulted for					
									dial action is required.					
Describe 7 He	a i i i i cotto a i	and Cicunapi	retion run	en. Tro detion in	, cossur	j. Tinariaco	ratory analysis ac	termined no reme	and dotton is required.					
regulations a public health should their or or the environ	Il operators or the envir operations h nment. In a	are required to ronment. The lave failed to a	o report ar acceptance adequately OCD accep	nd/or file certain re te of a C-141 repo investigate and re	elease i ort by the emedia	notifications a ne NMOCD m te contaminati	nd perform correct arked as "Final R on that pose a three the operator of the	etive actions for re eport" does not re eat to ground wat responsibility for	rsuant to NMOCD rules and leases which may endanger lieve the operator of liability er, surface water, human health compliance with any other					
Signature:	May	Men					OIL CON	SERVATION	I DIVISION					
Printed Name	e: Steve Mo	skal				Approved by	Environmental S	pecialist:						
Title: Field E	nvironment	al Coordinato	r			Approval Da	te:	Expiration	Date:					
E-mail Addre	ess: steven.r	noskal@bp.co	om			Conditions of	f Approval:		Attached					
Date: July 20	0. 2017		Phone: 50	5-326-9497										

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

September 8, 2016

Bureau of Land Management Gary Smith 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: FLORANCE U 006

API#: 3004509284

Dear Mr. Smith,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 12, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:

Moskal, Steven

Sent:

Monday, September 12, 2016 7:25 AM

To:

'Smith, Cory, EMNRD'

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Fields, Vanessa, EMNRD; Gonzales, Jody J

Subject:

RE: BP Pit Close Notification - FLORANCE U 006

Yes, 10:00 this morning.

Thank you,

Steve Moskal

BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497 Cell: (505) 330-9179



This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

From: Smith, Cory, EMNRD [mailto:Cory.Smith@state.nm.us]

Sent: Monday, September 12, 2016 7:23 AM

To: Moskal, Steven

Cc: jeffcblagq@aol.com; blagq njv@yahoo.com; Fields, Vanessa, EMNRD

Subject: RE: BP Pit Close Notification - FLORANCE U 006

Steve,

Do you have a time for this BGT closure?

Cory Smith
Environmental Specialist
Oil Conservation Division
Energy, Minerals, & Natural Resources
1000 Rio Brazos, Aztec, NM 87410
(505)334-6178 ext 115
cory.smith@state.nm.us

From: Railsback, Farrah (CH2M HILL) [mailto:Farrah.Railsback@bp.com]

Sent: Thursday, September 08, 2016 1:46 PM **To:** Smith, Cory, EMNRD; Fields, Vanessa, EMNRD

Cc: jeffcblagg@aol.com; blagg njv@yahoo.com; Moskal, Steven

Subject: BP Pit Close Notification - FLORANCE U 006

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

September 8, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FLORANCE U 006 API 30-045-09284 (M) Section 23 – T30N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around September 12, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback
BGT Project Support
970-946-9199 -cell

CLIENT: BP	API #: 3004509	284			
	(50	5) 632-1199		(if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / O	THER:	PAGE #: 1 of	_1_
SITE INFORMATION	: SITE NAME: FLORAI	NCE U #6		DATE STARTED: 09/1	2/16
QUAD/UNIT: M SEC: 23 TWP:	30N RNG: 9W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 990'S / 990'\		CTDUCE		ENVIRONMENTAL	N/
	PROD. FORMATION: MV/DK CO	ONTRACTOR: BP - J. GO	NZALES	SPECIALIST(S):	JV
REFERENCE POINT	(1.11.11)	COORD.: 36.7919		GL ELEV.: 6,	
1) 95 BGT (SW/DB)	GPS COORD.: 36.	79154 X 107.75582	DISTANCE/BEA	RING FROM W.H.:162', S:	30VV
2)				RING FROM W.H.:	
3)				4-07.5- 3 ME-1, WOL 31.3-0-	
	GPS COORD.:			RING FROM W.H.:	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0			ED/9024D/200 0 (CI)	READING (ppm)
1) SAMPLE ID: 5PC - TB @ 5					NA
3) SAMPLE ID:					
4) SAMPLE ID:					
SOIL DESCRIPTION					
SOIL COLOR: DARK YELLOW		PLASTICITY (CLAYS): NON PLASTIC		OHESIVE / MEDILIM PLASTIC / HIGH	V PI ASTIC
COHESION (ALL OTHERS): NON COHESIVE (SLIGHTLY		DENSITY (COHESIVE CLAYS & S			LITEACTIC
CONSISTENCY (NON COHESIVE SOILS): LC		HC ODOR DETECTED: YES NO	EXPLANATION -		
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/W SAMPLE TYPE: GRAB/COMPOSITE +		ANY AREAS DISPLAYING WETNES	NE NE NO EVELAN	NATION	
DISCOLORATION/STAINING OBSERVED: YES IN		OM BGT IN SMALL ISOLATE	ED PATCHES BENE	ATH BGT BOTTOM.	
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT:	YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE	D AND/OR OCCURRED: YES NO EXPL	ANATION:			
EQUIPMENT SET OVER RECLAIMED AREA: OTHER: NMOCD & BLM REPS. PRESEN			ABOVE-GRADE TAI	NK TO BE SET ATOP BGT L	OCATION.
	NA - V NA	- V NA			NIA
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: >100' N	NA ft. X NA EAREST WATER SOURCE: >1,000'	ft. X NA ft. NEAREST SURFACE WATER:		FIMATION (Cubic Yards) : CD TPH CLOSURE STD: 1,00	NA nom
SITE SKETCH					DO ppm
OITE ONLTOIT	BGT Located: off on site	PLOT PLAN circ		CALIB. READ. = NA ppr	111 -0.02
	∱ то			CALIB. GAS = NA ppr :: NA am/pm DATE:	NA
	/ W.H.		N		
		BERM	l	MISCELL. NOT	ES.
COMP SEPARATOR	RESSOR			/O: EF #: P - 697	
SELARGION	\ \	1	-	EF#: P - 697 ID: VHIXONEVB2	
*		PROD. TANK		J#:	
) IAIIK		ermit date(s): 06/03	1/10
	BERM		-	CD Appr. date(s): 09/06	
	PBGTL		Tar	nk OVM = Organic Vapor Mete	er
	T.B. ~ 5' B.G.		A		1)
		X	- S.P.D.	BGT Sidewalls Visible: Y / N	N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION		LOW; T.H. = TEST HOLE; ~ = APPROX.; V	N.H. = WELL HEAD;	BGT Sidewalls Visible: Y / N	
	OW-GRADE TANK LOCATION;		WALL; NA - NOT N	Magnetic declination: 10	Ĕ
NOTES: GOOGLE EARTH IMAGE		ONSITE: 09/12/1	16		

Analytical Report

Lab Order 1609595

Date Reported: 9/14/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Florance U 6 Project:

Collection Date: 9/12/2016 10:10:00 AM

Lab ID: 1609595-001 Matrix: MEOH (SOIL) Received Date: 9/13/2016 8:15:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	: LGT
Chloride	ND	30	mg/Kg	20	9/13/2016 11:37:17 AM	27462
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	s			Analyst	: TOM
Diesel Range Organics (DRO)	ND	9.6	mg/Kg	1	9/13/2016 9:59:05 AM	27460
Motor Oil Range Organics (MRO)	78	48	mg/Kg	1	9/13/2016 9:59:05 AM	27460
Surr: DNOP	110	70-130	%Rec	1	9/13/2016 9:59:05 AM	27460
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	RAA
Gasoline Range Organics (GRO)	ND	3.3	mg/Kg	1	9/13/2016 11:16:43 AM	27448
Surr: BFB	90.5	68.3-144	%Rec	1	9/13/2016 11:16:43 AM	27448
EPA METHOD 8021B: VOLATILES					Analyst	RAA
Benzene	ND	0.017	mg/Kg	1	9/13/2016 11:16:43 AM	27448
Toluene	ND	0.033	mg/Kg	1	9/13/2016 11:16:43 AM	27448
Ethylbenzene	ND	0.033	mg/Kg	1	9/13/2016 11:16:43 AM	27448
Xylenes, Total	ND	0.066	mg/Kg	1	9/13/2016 11:16:43 AM	27448
Surr: 4-Bromofluorobenzene	111	80-120	%Rec	1	9/13/2016 11:16:43 AM	27448

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- Ε Value above quantitation range
- Analyte detected below quantitation limits Page 1 of 5 J
- Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

C	hain-c	of-Cus	tody Record	Turn-Around	I IIIe.	SAME	-			H	ALL	E	N	TE	50	NI	ME	NT	AI	
lient:	BLAG	G ENGR.	/ BP AMERICA	Standard Project Name	☑ Rush _	DAY				Al		LY	515	SL	A	ВО	RA		RY	7
failing A	ddress:	P.O. BO	X 87	F	LORANCE U	J #6		490)1 H	awkin								9		
		BLOOM	FIELD, NM 87413	Project #:						5-345						-410				
hone #:		(505) 63	2-1199										ysis		The same	-				
mail or		,		Project Mana	ger							T	_				7	T	T	
AQC P	-		Level 4 (Full Validation)		NELSON V	ELEZ	(80218)	TPH (Gas only)	/ MRO)		(5)		PO4,50	/ 8082 PCB's			water - 300,1)		E1	
ccredita	nion:			Sampler:	NELSON VI	ELEZ TY	9) Se	(Ga	DRO	= =	8270SIMS)		102	808			/ wa		dm	
NELA		□ Other		On Ice:	X Yes	□ No	#	TH	-	418	827	en.	03	1 50		(AC	300.00		ES 3	N J
EDD (Type)			Sample Temp	erature: 3.3		1	BE +	(GR	pou por	ò	etal	CLN	cide	X	ii-V	-1	1	oosil	17.0
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +- AME	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	1	orab sample 5 pt. composite sample	Air Bubbles (Y or N)
3/12/16	1010	SOIL	5PC-TB @ 5 '(95)	4 oz 1	Cool	-001	V		V								V		V	
													4							
								1												
									-			-		-			_	-	-	
									+	+	+	-					-	-		-
	-							s, .	+	+	+	-					-	+	+	_
	-								\dashv	+	+	-					-	+	+	-
								11	+	-	+		19	100	-		+	-	+	+
	1				-			7 7		+	+						+	+	+	+
										+	1								+	+
/12/16	Time: 1533	Relinquishe	ny /	Received by:	Walte	Date Time (4)12/14 1535	Ren	arks		BILL DIR		NG VI	D & RI	EFERE		WHE	APPI		E:	
1/12/16	Time: 184 6	Relinquishe	d by: U alla (milted to Hall Environmental may be su	Received by:	Concha la	Date Time	In the second	erenc		P	- 597		_		SHQF	_	_	ITCJW		ot.

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609595

14-Sep-16

Client:

Blagg Engineering

Project:

Florance U 6

Sample ID MB-27462

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 27462

RunNo: 37167

Prep Date: 9/13/2016

Analysis Date: 9/13/2016

Units: mg/Kg

Analyte

SeqNo: 1152914

RPDLimit

Qual

Chloride

Result ND PQL SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Sample ID LCS-27462

SampType: LCS Batch ID: 27462

PQL

TestCode: EPA Method 300.0: Anions RunNo: 37167

Client ID: Prep Date: 9/13/2016

SeqNo: 1152915

Units: mg/Kg

Page 2 of 5

Qual

Analyte

Analysis Date: 9/13/2016

SPK value SPK Ref Val %REC

HighLimit

RPDLimit

Chloride

Result

14

1.5

15.00

%RPD

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Η Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609595

14-Sep-16

Client:

Blagg Engineering

Project: Florance	e U 6								
Sample ID LCS-27460	SampType: LCS	TestCode: EPA Method	1 8015M/D: Diesel Rang	e Organics					
Client ID: LCSS	Batch ID: 27460	RunNo: 37139	_	_					
Prep Date: 9/13/2016	Analysis Date: 9/13/2016	SeqNo: 1151802	Units:`mg/Kg						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual					
Diesel Range Organics (DRO)	46 10 50.00	0 92.2 62.6	124						
Surr: DNOP	5.00 5.000	100 70	130						
Sample ID MB-27460 SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics									
Client ID: PBS	Batch ID: 27460	RunNo: 37139							
Prep Date: 9/13/2016	Analysis Date: 9/13/2016	SeqNo: 1151803	Units: mg/Kg						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual					
Diesel Range Organics (DRO)	ND 10								
Motor Oil Range Organics (MRO)	ND 50								
Surr: DNOP	11 10.00	107 70	130						
Sample ID LCS-27445	SampType: LCS	TestCode: EPA Method	l 8015M/D: Diesel Range	e Organics					
Client ID: LCSS	Batch ID: 27445	RunNo: 37139							
Prep Date: 9/12/2016	Analysis Date: 9/13/2016	SeqNo: 1152405	Units: %Rec						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual					
Surr: DNOP	5.1 5.000	102 70	130						
Sample ID MB-27445	SampType: MBLK	TestCode: EPA Method	l 8015M/D: Diesel Range	e Organics					
Client ID: PBS	Batch ID: 27445	RunNo: 37139							
Prep Date: 9/12/2016	Analysis Date: 9/13/2016	SeqNo: 1152406	Units: %Rec						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual					
Surr: DNOP	10 10.00	103 70	130						

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 3 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1609595

14-Sep-16

Client:

Blagg Engineering

Project:

Florance U 6

Sample ID LCS-27448

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: 27448

RunNo: 37145

Prep Date: 9/12/2016

Analysis Date: 9/13/2016

SeqNo: 1152768

%REC

105

99.8

Units: mg/Kg

HighLimit

Analyte Gasoline Range Organics (GRO) Result **PQL** 26

1000

SPK value SPK Ref Val 25.00 0

SPK value SPK Ref Val %REC

LowLimit 80 68.3 %RPD **RPDLimit**

Qual

Sample ID MB-27448

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: PBS

Result

ND

910

Batch ID: 27448

5.0

RunNo: 37145

120

144

Prep Date: 9/12/2016

Surr: BFB

Analysis Date: 9/13/2016

SeqNo: 1152769

Units: mg/Kg

%RPD **RPDLimit** Qual

Page 4 of 5

Analyte Gasoline Range Organics (GRO)

Surr: BFB

1000

1000

90.7

68.3

LowLimit

144

HighLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix В Analyte detected in the associated Method Blank

Е Value above quantitation range

Analyte detected below quantitation limits

P Sample pH Not In Range

RLReporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

ND

ND

ND

1.1

0.050

0.050

0.10

1.000

WO#:

1609595

14-Sep-16

Client:

Toluene Ethylbenzene

Xylenes, Total

Surr: 4-Bromofluorobenzene

Blagg Engineering

Project:

Florance U 6

Sample ID LCS-27448	Samp	SampType: LCS			TestCode: EPA Method 8021B: Volatiles					
Client ID: LCSS	Batch ID: 27448 Analysis Date: 9/13/2016			RunNo: 37145 SeqNo: 1152892						
Prep Date: 9/12/2016							Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	2.0	0.025	2.000	0	101	75.3	123			
Toluene	2.0	0.050	2.000	0	100	80	124			
Ethylbenzene	2.0	0.050	2.000	0	102	82.8	121			
Xylenes, Total	6.1	0.10	6.000	0	102	83.9	122			
Surr: 4-Bromofluorobenzene	1.2		1.000		116	80	120			
Sample ID MB-27448	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 27448			RunNo: 37145						
Prep Date: 9/12/2016	Analysis Date: 9/13/2016			SeqNo: 1152893 Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								

112

80

120

Qualifier	s:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank В

E Value above quantitation range


J Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 5 of 5



1901 Hawkins NE Albuquerque NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Website: www.hallenvironmental.com Client Name: Work Order Number: 1609595 RcptNo: 1 BLAGG Received by/date Logged By Ashley Gallegos 9/13/2016 B;15:00 AM Completed By: **Ashley Gallegos** 9/13/2016 8:57:49 AM Reviewed By: Chain of Custody Not Present No . 1. Custody seals intect on sample bottles? No | Not Present Yes V 2. Is Chain of Custody complete? 3. How was the sample delivered? Client Log In NA L Yes V No 4: Was an attempt made to cool the samples? NA 1 5. Were all samples received at a temperature of >0° C to 6.0°C No L Yes V No [Sample(s) in proper container(s)? 7 Sufficient sample volume for indicated test(s)? No . No . 8. Are samples (except VOA and ONG) properly preserved? No V NA | 9. Was preservative added to bottles? Yes No 🗌 No VOA Vials 10. VOA vials have zero headspace? No V 11. Were any sample containers received broken? # of preserved bottles checked for pH No 🗌 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No. 13. Are matrices correctly identified on Chain of Custody? 14. Is it clear what analyses were requested? Yes V No Checked by: 15. Were all holding times able to be met? Yes V No . (If no notify customer for authorization.) Special Handling (if applicable) 16. Was client notified of all discrepancies with this order? Yes __ No L NA V Person Notified: Date By Whom Via. eMail Phone Fax In Person Regarding Client Instructions: 17. Additional remarks: 18. Conler Information Cooler No Temp °C | Condition | Seal Intact | Seal No Seal Date Signed By 3.3 Good Yes

