

submitted in lieu of Form 3160-5  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
Sec., T--N, R--W, NMPM

Unit M (SWSW) 1185' FSL & 660' FWL, Sec. 1, T30N R10W NMPM

5. Lease Number  
NMSF-078208  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

8. Well Name & Number  
Sunray B #2B  
9. API Well No.  
30-045-33588  
10. Field and Pool

Blanco Mesaverde/ Basin Dakota

11. County and State  
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - 7" 4 1/2" Casing

13. Describe Proposed or Completed Operations

3/30/06 MIRU Aztec #301. NU BOP. PT csg 600psi for 30mins, ok. RIH w/8 3/4" bit & tagged cement @ 185'. 4/3/06 D/O cmt & ahead to 3437' Intermediate TD. Circulate hole. RIH w/78jts of 7"20# ST&C and 1jt 23# J55 LT&C csg & set @3427'. Circulate hole. 4/3/06 Pumped preflush w/10bbls H2O, 10bbls mud, 10bbls H2O. Pump 19sxs(57cu-10bbls)prem lite cmt w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4%FL-52, .4%SMS. Lead in w/449sxs(956cu-170bbls)Prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SMS. Tail w/90sxs(124cu-22bbls)Type 3 cmt w/1% CaCl2, .25pps Cell-o-Flake, .2% FL52. Drop plug and displaced w/37bbls H2O. Bumped plug to 1540#. Plug down @ 2242 hrs. Circulate 55bbls cmt. RD NU section "B" BOP. PT csg 1500psi for 30mis, ok.

4/4/06 RIH 6 1/4" bit and tagged cmt. 4/6/06 D/O ahead to TD 7722'. Circulated hole. 4/6/06 RIH w/4 1/2" 19jts of 11.6# J55 LT&C and 161jts 10.5# J55 ST&C csg set @ 7722'. Preflush w/10bbls chem wash and 2bbls FW. Pumped lead cement w/9sxs (28cu-5bbls)prem lite w/.25pps Cell-o-Flake, .3% CD32, 1% FL52. Tail 304sxs(602cu-107bbls)prem lite cmt w/.25 Cell-o-Flake, .3%CD32, 6.25pps LCM1, 1% FL52. Drop plug & displaced w/122bbls FW w/25# sugar in 1st 10bbls. Bump plug w/970psi. Plug down @ 2334hrs 4/6/06. RD ND BOP 4/6/06. Will show top of cement & casing PT on next report. PT will be conducted by completing rig.

14. I hereby certify that the foregoing is true and correct.

Signed Amanda Sandoval Amanda Sandoval Title Regulatory Compliance Assistant III Date 4/10/06

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

APR 14 2006

NMCG BURLINGTON FIELD OFFICE