

SMYERS COM LS 001A-MV

Current Wellbore



COMMENTS

EQUIPMENT DESCRIPTION

A

B

C

EOT @
5,358

TOL: 2922'

133000# 20/40 snd

PERFORATIONS:

MesaVerde
4237' - 5364'

PBTD: 5,398 MD TVD
TD: 5,415 MD TVD

Spud: 10/3/1978 Frac: 11/27/1978 Tbg: Workovers:

FIELD Farmington
WELL SMYERS COM LS 001A-MV
COUNTY
API No. 300452304500
RKB ELEVATION SEC: 2
GL ELEVATION 5,997 TOWN: 32N
RKB-GL RANGE: 11W
Lat: 36.92931 Long: -107.96369

DIRECTIONAL DATA

MAX ANGLE THRU
KOP TYPE

PRODUCTION DETAIL

	Tubing	CASING
SIZE	2 3/8	
WEIGHT		
GRADE		
DEPTH	5,358	
THREAD		
I.D.		
DRIFT		
BURST		
COLLAPSE		
CAPACITY		
# JOINTS		

PRODUCTION ASSEMBLY DETAIL

#	O. D. IN	I. D. IN	LENGTH FT	Description
1				
2				
3				
4				
5				
6				

CASING DETAIL

#	SIZE	WGHT	GRADE	THREAD	DEPTH
A	9 5/8	36			222
B	7	20			3,100
C	4 1/2				5,415
D					

PRESSURE DATA

BOTTOM HOLE PRESSURE
Calculated using HASP + (0.1 * Top Perf)
HIGHEST ANTICIPATED PRESSURE
SITP from offset MC 5-90 + 500 psi Safety Factor
MAXIMUM ALLOWABLE SURFACE PRESS
Rating of valves
BOTTOM HOLE TEMPERATURE
From PLT

Prepared by: Michael Morgan Date: 8-Aug-2017

Formation	Top
Cliff House	4230
Point Lookout	4956