

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2006 APR 18 PM 12 13

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
Sec., T--N, R--W, NMPM

Unit J (NWSE) 1790' FSL & 1425' FEL, Sec. 1, T31N R10W NMPM

RECEIVED  
070 FARMINGTON NM

5. Lease Number  
NMSF-078507  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

San Juan 32-9 Unit  
8. Well Name & Number

San Juan 32-9 Unit #268S  
9. API Well No.

30-045-33357  
10. Field and Pool

Basin Fruitland Coal  
11. County and State  
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - 7" Casing

13. Describe Proposed or Completed Operations

4/13/06 MIRU Aztec #580. NU BOPE. PT csg 600psi for 30 mins, ok. RIH w/8 3/4" bit & tagged cmt @ 240'. 4/16/06 D/O cmt & ahead to 3140'. Circulate hole. 4/17/06 RIH w/78jts of 7"20# J55 ST&C csg set @ 3140'. Cement 1<sup>st</sup> Stage: Pumped preflush of 10bbls H2O, 10bbls mud, 10bbls H2O. Cemented w/19sxs(57cu-10bbls)prem lite cmt w/3% CaCl2, .25pps Cell-o-flake, 5pps LCM1, .4% FL52, .4% SMS. Cemented tail w/463sxs(986cu-176bbls)prem lite w/3% CaCl2, .25pps Cell-o-flake, 5pps LCM1, .4% FL52, .4% SMS. Tail in w/90sxs(124cu-22bbls)Type 3 cmt w/1% CaCl2, .25pps Cell-o-Flake, .2% FL52. Drop plug and displace w/125bbls H2O. Bump plug to 1485#. Circulated 70bbls cmt to surface. Plug down @ 1915hrs. ND BOPE. RD Rig released 4/17/06 @ midnight. Will show csg PT on next report. PT will be done by completing rig.

14. I hereby certify that the foregoing is true and correct.

Signed Amanda Sandoval Amanda Sandoval Title Regulatory Analyst Date 4/18/06

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

NMOCD

APR 18 2006

FARMINGTON FIELD OFFICE