

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

JUL 24 2018

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Enduring Resources IV, LLC

3a. Address

332 Cr 3100 Aztec, NM 87410

3b. Phone No. (include area code)

505-636-9743

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SHL: 409' FSL & 1115' FEL Sec 17 T23N R9W Unit: P

SHL: 330' FNL & 1200' FEL Sec 18 T23N R9W Unit: A

5. Lease Serial No.

NMNM136267

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

NMNM 135255A

8. Well Name and No.

Kimbeto Wash Unit 770H

9. API Well No.

30-045-35755

10. Field and Pool or Exploratory Area

Basin Mancos

11. Country or Parish, State

San Juan, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <b>CHANGE IN PLANS</b>
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Enduring Resources IV, LLC requests a change in plans for the casing program and to drill, complete and equip a single lateral in the Mancos Silt formation per attached updated:

C102  
Wellbore  
Drill plan  
Ops plan

NMOC

AUG 14 2018

DISTRICT III

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Lacey Granillo

Title: Permit Specialist

Signature

Date: 7/24/18

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title PE

Date 8/13/18

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office FFO

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ADHERE TO PREVIOUS NMOC  
CONDITIONS OF APPROVAL

NMOC

District I  
1625 N. French Drive, Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720

District II  
811 S. First Street, Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720

District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV  
1220 S. St. Francis Drive, Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

Submit one copy to  
Appropriate District Office

**OIL CONSERVATION DIVISION**  
**1220 South St. Francis Drive**  
**Santa Fe, NM 87505**

☒ AMENDED REPORT

**WELL LOCATION AND ACREAGE DEDICATION PLAT**

*API Number 30-045-35755	*Pool Code 97232	*Pool Name BASIN MANCOS
*Property Code 321239	*Property Name KIMBETO WASH UNIT	*Well Number 770H
*GRID No. 372286	*Operator Name ENDURING RESOURCES, LLC	*Elevation 6561'


**10 Surface Location**

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	17	23N	9W		409	SOUTH	1115	EAST	SAN JUAN

**11 Bottom Hole Location If Different From Surface**

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	18	23N	9W		330	NORTH	1200	EAST	SAN JUAN
<b>12 Dedicated Acres</b> 1279.88 Entire Section 17 N/2 - Section 18 N/2 - Section 20					<b>13 Joint or Infill</b> 14 Consolidation Code 15 Order No. R-14084				

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



**17 OPERATOR CERTIFICATION**  
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom-hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature: *Lacey Granillo* Date: 7/24/18  
 Printed Name: Lacey Granillo  
 E-mail Address: lgranillo@enduringresources.com

**18 SURVEYOR CERTIFICATION**  
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Date Revised: JULY 24, 2018  
 Survey Date: DECEMBER 3, 2015

Signature and Seal of Professional Surveyor

**JASON C. EDWARDS**  
 NEW MEXICO  
 15269  
 REGISTERED PROFESSIONAL SURVEYOR

**JASON C. EDWARDS**  
 Certificate Number 15269



**ENDURING RESOURCES IV, LLC**  
**1050 SEVENTEENTH STREET, SUITE 2500**  
**DENVER, COLORADO 80265**

**DRILLING PLAN:** *Drill, complete, and equip single lateral in the Mancos Silt formation*

**WELL INFORMATION:**

**Name:** Kimbeto Wash Unit 770H

**API Number:** 30-045-

**State:** New Mexico

**County:** San Juan

**Surface Elevation:** 6,561 ft ASL (GL) 6,583 ft ASL (KB)

**Surface Location:** 17-23N-09W Sec-Twn-Rng 409 ft FSL 1,115 ft FEL

36.22058 ° N latitude 107.807071 ° W longitude (NAD 83)

**BH Location:** 18-23N-09W Sec-Twn-Rng 330 ft FNL 1,200 ft FEL

36.233261 ° N latitude 107.825193 ° W longitude (NAD 83)

**Driving Directions:** From the intersection of US HWY 550 and US HWY 64 in Bloomfield, NM: South on US HWY 550 for 35.9 miles to MM 115.7, right (southwest) at Nageezi Post Office on CR 7800 for 0.4 miles to 4-way intersection; straight (southwest) exiting CR7800 and continuing on 7820 for 0.6 miles to fork in road, right (southwest) on 7820 for 1.1 miles to 4-way intersection, straight (southwest) for 2.7 miles to existing access road for Kimbeto Wash 771H well.

**GEOLOGIC AND RESERVOIR INFORMATION:**

<i>Prognosis:</i>	Formation Tops	TVD (ft ASL)	TVD (ft KB)	MD (ft KB)	O / G / W	Pressure
	Ojo Alamo	6,438	145	145	W	normal
	Kirtland	6,341	242	242	W	normal
	Fruitland	6,081	502	502	G, W	sub
	Pictured Cliffs	5,731	852	853	G, W	sub
	Lewis	5,526	1,057	1,061	G, W	normal
	Chacra	5,341	1,242	1,251	G, W	normal
	Cliff House	4,336	2,247	2,316	G, W	sub
	Menefee	4,321	2,262	2,332	G, W	normal
	Point Lookout	3,331	3,252	3,385	G, W	normal
	Mancos	3,051	3,532	3,681	O,G	normal
	Gallup (MNCS. A)	2,826	3,757	3,913	O,G	normal
	<b>MNCS_SILT (Target Depth)</b>	<b>2,487</b>	<b>4,096</b>	<b>4,713</b>	<b>O,G</b>	<b>normal</b>
	<b>PROJECTED WELL TD</b>	<b>2,447</b>	<b>4,136</b>	<b>11,858</b>	<b>O,G</b>	<b>normal</b>

**Surface:** Nacimiento

**Oil & Gas Zones:** Several gas bearing zones will be encountered; target formation is the Gallup

**Pressure:** Normal pressure gradient (0.43 psi/ft) anticipated in all formations

Max. pressure gradient: 0.43 psi/ft Evacuated hole gradient: 0.22 psi/ft

**Maximum anticipated BH pressure, assuming maximum pressure gradient:** 1,770 psi

**Maximum anticipated surface pressure, assuming partially evacuated hole:** 870 psi

**Temperature:** Maximum anticipated BHT is 165° F or less

**H<sub>2</sub>S INFORMATION:**

**H<sub>2</sub>S Zones:** Encountering hydrogen-sulfide bearing zones is **NOT** anticipated.

**Safety:** Sensors and alarms will be placed in the substructure, on the rig floor, above the pits, and at the shakers.

## LOGGING, CORING, AND TESTING:

**Mud Logs:** None planned; remote geo-steering from drill out of 9-5/8" casing to TD; gas chromatograph from drillout of 13-3/8" casing to TD.

**MWD / LWD:** Gamma Ray from drillout of 13-3/8" casing to TD

**Open Hole Logs:** None planned

**Testing:** None planned

**Coring:** None planned

**Cased Hole Logs:** CBL on 5-1/2" casing from deepest free-fall depth to surface

## DRILLING RIG INFORMATION:

**Contractor:** Aztec

**Rig No.:** 1000

**Draw Works:** E80 AC 1,500 hp

**Mast:** Hyduke Triple (136 ft, 600,000 lbs, 10 lines)

**Top Drive:** NOV IDS-350PE (350 ton)

**Prime Movers:** 4 - GE Jenbacher Natural Gas Generator

**Pumps:** 2 - RS F-1600 (7,500 psi)

**BOPE 1:** Cameron double gate ram (11", 3,000 psi)

**BOPE 2:** Cameron annular (11", 3,000 psi)

**Choke** Cameron (4", 10,000 psi)

**KB-GL (ft):** 22

## BOPE REQUIREMENTS:

*See attached diagram for details regarding BOPE specifications and configuration.*

- 1) Rig will be equipped with upper and lower kelly cocks with handles available.
- 2) Inside BOP and TIW valves will be available to use on all sizes and threads of drill pipe used while drilling the well.
- 2) BOP accumulator will have enough capacity to open the HCR valve, close all rams and annular preventer, and retain minimum of 200 psi above precharge on the closing manifold without the use of closing pumps. The fluid reservoir capacity shall be at least double the usable fluid volume of the accumulator system capacity, and the fluid level shall be maintained at manufacturer's recommendation. There will be two additional sources of power for the closing pumps (electric and air). Sufficient nitrogen bottles will be available and will be recharged when pressure falls below manufacturer's recommended minimum.
- 3) BOP testing shall be conducted (a) when initially installed, (b) whenever any seal is broken or repaired, (c) if the time since the previous test exceeds 30 days. Tests will be conducted using a test plug. BOP ram preventers will be tested to 5,000 psi for 10 minutes, and the annular preventer will be tested to 2,500 psi for 10 minutes. Ram and annular preventers will be tested to 250 psi for 5 minutes. Additionally, BOP and casing strings will be tested to .22 psi/ft or 1,500 psi, whichever is greater but not exceeding 70% of yield strength of the casing, for 30 minutes, prior to drilling out 13-3/8" and 9-5/8" casing. Rams and hydraulically operated remote choke line valve will be function tested daily at a minimum.
- 4) Remote valve for BOP rams, HCR, and choke shall be placed in a location that is readily available to the driller. The remote BOP valve shall be capable of closing and opening the rams.
- 5) Manual locking devices (hand wheels) shall be installed on rams. A valve will be installed on the annular preventer's closing line as close as possible to the preventer to act as a locking device. The valve will be maintained in the open position and shall only be closed when there is no power to the accumulator.

## FLUIDS AND SOLIDS CONTROL PROGRAM:

**Fluid Measurement:** Pumps shall be equipped with stroke counters with displays in the dog-house. Slow pump speed shall be recorded daily and after mudding up, at a minimum, on the drilling report. A Pit Volume Totalizer will be installed and the readout will be displayed in the dog-house. Gas-detecting equipment will be installed at the shakers, and readouts will be available in the dog-house and the in the geologist's work-station (if geologist or mud-logger is on-site).

**Closed-Loop System:** A fully, closed-loop system will be utilized. The system will consist of above-ground piping and above-ground storage tanks and bins. The system will not entail any earthen pits, below-grade storage, or drying pads. All equipment will be disassembled and removed from the site when drilling operations cease. The system will be capable of storing all fluids and generated cuttings and of preventing uncontrolled releases of the same. The system will be operated in an efficient manner to allow the recycling and reuse of as much fluid as possible and to minimize the amount of fluids and solids that require disposal.

**Fluid Disposal:** Fluids that cannot be reused, recycled, or returned to the supplier will be hauled to and disposed of at an approved disposal site (Industrial Ecosystem, Inc. or Envirotech, Inc.).

**Solids Disposal:** Drilling solids will be stored (until haul-off) on-site in separate containers with no other waste, debris, or garbage products. Waste solids will be hauled to and disposed of at an approved disposal site (Industrial Ecosystem, Inc. or Envirotech, Inc.).

**Fluid Program:** See "Detailed Drilling Plan" section for specifics.

## DETAILED DRILLING PLAN:

**SURFACE:** Drill vertically to casing setting depth (plus necessary rathole), run casing, cement casing to surface.

0 ft (MD)	to	240 ft (MD)	Hole Section Length:	240 ft
0 ft (TVD)	to	240 ft (TVD)	Casing Required:	220 ft

Note: Surface hole may be drilled, cased, and cemented with a smaller rig in advance of the drilling rig.

Fluid:	Type	MW (ppg)	FL (mL/30 min)	PV (cp)	YP (lb/100 sqft)	pH	Comments
	Fresh Water	8.4	N/C	2 - 8	2 - 12	9.0	Spud mud

**Hole Size:** 17-1/2"

**Bit / Motor:** Mill Tooth or PDC, no motor

**MWD / Survey:** No MWD, run gyro survey after drilling

**Logging:** None

**Casing Specs:**

	Wt (lb/ft)	Grade	Conn.	Collapse (psi)	Burst (psi)	Tens. Body (lbs)	Tens. Conn (lbs)
Specs	13.375	54.5	J-55	BTC	1,130	2,730	853,000
Loading					105	510	111,406
Min. S.F.					10.78	5.36	7.66

Assumptions: Collapse: fully evacuated casing with 8.4 ppg equivalent external pressure gradient

Burst: maximum anticipated surface pressure with 9.5 ppg fluid inside casing while drilling intermediate hole and 8.4 ppg equivalent external pressure gradient

Tension: buoyed weight in 8.4 ppg fluid with 100,000 lbs over-pull

**MU Torque (ft lbs):** Minimum: N/A Optimum: N/A Maximum: N/A

\* Make-up as per API Buttress Connection running procedure.

**Casing Details:** Float shoe, 1 jt casing, float collar, casing to surface

**Centralizers:** 2 centralizers per jt stop-banded 10' from each collar on bottom 3 jts, 1 centralizer per 2 jts to surface

Cement:	Type	Weight (ppg)	Yield (cuft/sk)	Water (gal/sk)	Hole Cap. (cuft/ft)	% Excess	Planned TOC (ft MD)	Total Cmt (sx)
	Class G	15.8	1.174	5.15	0.6946	100%	0	284

Calculated cement volumes assume gauge hole and the excess noted in table

Halliburton HALCEM surface cementing blend

Notify NMOCD & BLM if cement is not circulated to surface. Cement must achieve 500 psi compressive strength before drilling out.

**INTERMEDIATE:** Drill as per directional plan to casing setting depth, run casing, cement casing to surface, install wellhead.

220 ft (MD)	to	2,465 ft (MD)	Hole Section Length:	2,245 ft
220 ft (TVD)	to	2,362 ft (TVD)	Casing Required:	2,465 ft

Fluid:	Type	MW (ppg)	FL (mL/30 min)	PV (cp)	YP (lb/100 sqft)	pH	Comments
	WBM	8.8 - 9.5	20	8 - 14	8 - 14	9.0 - 9.5	OBM as contingency

Hole Size: 12-1/4"

Bit / Motor: PDC w/mud motor

MWD / Survey: MWD with GR, inclination, and azimuth survey (every 100' at a minimum)

Logging: None

Pressure Test: NU BOPE and test (as noted above); pressure test 13-3/8" casing to 1,500 psi for 30 minutes.

Note: The intermediate hole section may be drilled with annular preventer and blind rams only (no pipe rams).

Maximum anticipated surface pressure while drilling intermediate hole section is 500 psi

Casing Specs:	Wt (lb/ft)	Grade	Conn.	Collapse (psi)	Burst (psi)	Tens. Body (lbs)	Tens. Conn (lbs)
Specs	9.625	36.0	J-55	LTC	2,020	3,520	564,000
Loading					1,032	1,005	177,386
Min. S.F.					1.96	3.50	3.18

Assumptions: Collapse: fully evacuated casing with 8.4 ppg equivalent external pressure gradient

Burst: maximum anticipated surface pressure with 9.5 ppg fluid inside casing while drilling production hole and 8.4 ppg equivalent external pressure gradient

Tension: buoyed weight in 8.4 ppg fluid with 100,000 lbs over-pull

MU Torque (ft lbs): Minimum: 3,400 Optimum: 4,530 Maximum: 5,660

Casing Details: Float shoe, 1 jt casing, float collar, landing collar, casing to surface

Centralizers: 2 centralizers per jt stop-banded 10' from each collar on bottom 3 jts, 1 centralizer per 2 jts to surface

Cement:	Type	Weight (ppg)	Yield (cuft/sk)	Water (gal/sk)	Hole Cap. (cuft/ft)	% Excess	Planned TOC (ft MD)	Total Cmt (sx)
Lead	G:POZ Blend	12.3	1.987	10.16	0.3132	40%	0	434
Tail	Class G	15.8	1.148	4.98	0.3132	10%	1,965	150

Calculated cement volumes assume gauge hole and the excess noted in table

Halliburton ECONOCHEM & HALCEM cementing blend

Notify NMOCD & BLM if cement is not circulated to surface. Cement must achieve 500 psi compressive strength before drilling out.

**PRODUCTION:** Drill to TD following directional plan, run casing, cement casing to surface.

2,465 ft (MD)	to	11,858 ft (MD)	Hole Section Length:	9,393 ft
2,362 ft (TVD)	to	4,136 ft (TVD)	Casing Required:	11,858 ft

Estimated KOP:	3,603 ft (MD)	3,400 ft (TVD)
Estimated Landing Point (P.O.E.):	4,713 ft (MD)	4,096 ft (TVD)
Estimated Lateral Length:	7,145 ft (MD)	

Fluid:	Type	MW (ppg)	FL (mL/30')	PV (cp)	YP (lb/100 sqft)	pH	Comments
	WBM	8.8 - 9.5	20	8 - 14	8 - 14	9.0 - 9.5	OBM as contingency

Hole Size: 8-1/2"

Bit / Motor: PDC w/mud motor

MWD / Survey: MWD with GR, inclination, and azimuth (survey every joint from KOP to Landing Point and survey every 100' minimum before KOP and after Landing Point)

Logging: GR MWD for entire section, no mud-log or cuttings sampling, no OH WL logs

**Pressure Test:** NU BOPE and test (as noted above); pressure test 9-5/8" casing to **1,500** psi for 30 minutes.

<b>Casing Specs:</b>	Size (in)	Wt (lb/ft)	Grade	Conn.	Collapse (psi)	Burst (psi)	Tens. Body (lbs)	Tens. Conn (lbs)
<i>Specs</i>	5.500	17.0	P-110	LTC	7,460	10,640	546,000	445,000
<i>Loading</i>					2,043	8,887	273,950	273,950
<i>Min. S.F.</i>					<b>3.65</b>	<b>1.20</b>	<b>1.99</b>	<b>1.62</b>

**Assumptions:** Collapse: fully evacuated casing with 9.5 ppg fluid in the annulus (floating casing during running)  
 Burst: 8,500 psi maximum surface treating pressure with 10.2 ppg equivalent mud weight sand laden fluid with 8.4 ppg equivalent external pressure gradient  
 Tension: buoyed weight in 9.0 ppg fluid with 100,000 lbs over-pull

**MU Torque (ft lbs):** Minimum: 3,470 Optimum: 4,620 Maximum: 5,780

**Casing Details:** Float shoe, 2 jts casing, float collar, landing collar, toe-initiation sleeve with handling pups, 1 jt casing, toe-initiation sleeve, with handling pups, casing to KOP with 20' marker joints spaced evenly in lateral every 2,000'. Place Floatation Sub at KOP (+/-). Continue running casing to surface. **The toe-initiation sleeves must be positioned INSIDE the 330' unit setback.**

**Centralizers:** Lateral: Minimum of 1 centralizer per 2 joints

Curve: 1 centralizer every joint from landing point to KOP

Vertical: 1 centralizer every 2 joints from KOP to 9-5/8" shoe, 1 every 3 joints from 9-5/8" shoe to surface

<b>Cement:</b>	Type	Weight (ppg)	Yield (cuft/sk)	Water (gal/sk)	Hole Cap. (cuft/ft)	% Excess	Planned TOC (ft MD)	Total Cmt (sx)
<i>Lead</i>	G:POZ blend	12.3	1.987	10.16	0.2691	40%	0	618
<i>Tail</i>	G:POZ blend	13.3	1.354	5.94	0.2291	10%	3,400	1,574

Calculated cement volumes assume gauge hole and the excess noted in table

Halliburton ECONOCEM & EXTENDACEM cementing blend

**Notify NMOCD & BLM if cement is not circulated to surface.**

**Note:** The lateral may be drilled past applicable setback to maximize the length of the completed interval and to maximize resource recovery. If the well is drilled past the setback, the toe Initiation sleeve and all perforations will be placed inside the setback. An unorthodox location application is not required because the completed interval will be entirely within the setback as defined and allowed by NMAC 19.15.16.7B(1), NMAC 19.15.16.14B(2), NMAC 19.15.16.15B(2) . Order number for Kimbeto Wash Unit is R-14084.

**FINISH WELL:** ND BOP, NU WH with BPV and cap, RDMO.

## COMPLETION AND PRODUCTION PLAN:

**Frac:** Lateral will be fracture-stimulated in approximately 33 plug-and-perf stages with approximately 180,000 bbls slickwater fluid and 13,000,000 lbs of proppant.

**Flowback:** Depending on well pressures, flow back may be either up 5-1/2" casing or 2-7/8" production tubing. Well will be flowed back until proppant volumes are low enough that the well can safely be produced through permanent production facilities.

**Production:** Well will produce up production tubing via gas-lift into permanent production and storage facilities.

## ESTIMATED START DATES:

**Drilling:** 9/1/2018

**Completion:** 11/1/2018

**Production:** 12/15/2018

**Prepared by:** Alec Bridge 7/11/2018



# **Enduring Resources LLC**

**San Juan Basin - Kimbeto Wash Unit**

**771H pad**

**770H**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report**

**23 July, 2018**

<b>Project</b>	San J	1 - Kimbeto 1	Unit
<b>Map System:</b>	US State Plane 1983		<b>System Datum:</b> Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Western Zone		

<b>Site</b>	771H pad, San Juan Co., New Mexico		
<b>Site Position:</b>		<b>Northing:</b>	1,899,575.11 usft
<b>From:</b>	Lat/Long	<b>Easting:</b>	2,730,824.78 usft
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16 "
		<b>Latitude:</b>	36.220539°N
		<b>Longitude:</b>	107.807116°W
		<b>Grid Convergence:</b>	0.02 °

<b>Well</b>	770H		
<b>Well Position</b>	+N/-S	14.9 usft	<b>Northing:</b> 1,899,590.04 usft
	+E/-W	13.3 usft	<b>Easting:</b> 2,730,838.04 usft
<b>Position Uncertainty</b>	0.0 usft	<b>Wellhead Elevation:</b>	<b>Latitude:</b> 36.220580°N
			<b>Longitude:</b> 107.807071°W
			<b>Ground Level:</b> 6,561.0 usft

<b>Wellbore</b>	Wellbore #1		
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>
	IGRF200510	12/31/2009	10.01
			<b>Dip Angle (°)</b> 63.05
			<b>Field Strength (nT)</b> 50,602.98459015

<b>Design</b>	Design #1		
<b>Audit Notes:</b>			
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b> 0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>
	0.0	0.0	0.0
			<b>Direction (°)</b> 310.81

<b>Plan Survey Tool Program</b>	<b>Date</b> 7/23/2018		
<b>Depth From (usft)</b>	<b>Depth To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>
1	0.0	11,857.8	Design #1 (Wellbore #1)
			MWD
			OWSG MWD - Standard

<b>Plan Sections</b>										
<b>Measured Depth (usft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
240.0	0.00	0.00	240.0	0.0	0.0	0.00	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,495.1	19.90	163.61	1,475.2	-164.1	48.3	2.00	2.00	0.00	163.61	
3,595.3	19.90	163.61	3,450.0	-850.0	250.0	0.00	0.00	0.00	0.00	770H KOP
4,325.6	71.05	311.61	4,031.4	-711.4	-30.9	12.07	7.00	20.27	149.91	
4,713.1	89.68	315.15	4,096.0	-450.0	-307.0	4.89	4.81	0.91	10.95	770H POE
11,857.8	89.68	315.15	4,136.0	4,615.2	-5,345.7	0.00	0.00	0.00	0.00	770H BHL

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
240.0	0.00	0.00	240.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	2.00	163.61	600.0	-1.7	0.5	-1.5	2.00	2.00	0.00
700.0	4.00	163.61	699.8	-6.7	2.0	-5.9	2.00	2.00	0.00
800.0	6.00	163.61	799.5	-15.1	4.4	-13.2	2.00	2.00	0.00
900.0	8.00	163.61	898.7	-26.7	7.9	-23.4	2.00	2.00	0.00
1,000.0	10.00	163.61	997.5	-41.8	12.3	-36.6	2.00	2.00	0.00
1,100.0	12.00	163.61	1,095.6	-60.1	17.7	-52.6	2.00	2.00	0.00
1,200.0	14.00	163.61	1,193.1	-81.6	24.0	-71.5	2.00	2.00	0.00
1,300.0	16.00	163.61	1,289.6	-106.5	31.3	-93.3	2.00	2.00	0.00
1,400.0	18.00	163.61	1,385.3	-134.5	39.6	-117.9	2.00	2.00	0.00
1,495.1	19.90	163.61	1,475.2	-164.1	48.3	-143.8	2.00	2.00	0.00
1,500.0	19.90	163.61	1,479.8	-165.7	48.7	-145.2	0.00	0.00	0.00
1,600.0	19.90	163.61	1,573.8	-198.4	58.4	-173.8	0.00	0.00	0.00
1,700.0	19.90	163.61	1,667.9	-231.1	68.0	-202.4	0.00	0.00	0.00
1,800.0	19.90	163.61	1,761.9	-263.7	77.6	-231.0	0.00	0.00	0.00
1,900.0	19.90	163.61	1,855.9	-296.4	87.2	-259.7	0.00	0.00	0.00
2,000.0	19.90	163.61	1,950.0	-329.0	96.8	-288.3	0.00	0.00	0.00
2,100.0	19.90	163.61	2,044.0	-361.7	106.4	-316.9	0.00	0.00	0.00
2,200.0	19.90	163.61	2,138.0	-394.3	116.0	-345.5	0.00	0.00	0.00
2,300.0	19.90	163.61	2,232.0	-427.0	125.6	-374.1	0.00	0.00	0.00
2,400.0	19.90	163.61	2,326.1	-459.7	135.2	-402.7	0.00	0.00	0.00
2,500.0	19.90	163.61	2,420.1	-492.3	144.8	-431.3	0.00	0.00	0.00
2,600.0	19.90	163.61	2,514.1	-525.0	154.4	-459.9	0.00	0.00	0.00
2,700.0	19.90	163.61	2,608.2	-557.6	164.0	-488.5	0.00	0.00	0.00
2,800.0	19.90	163.61	2,702.2	-590.3	173.6	-517.2	0.00	0.00	0.00
2,900.0	19.90	163.61	2,796.2	-622.9	183.2	-545.8	0.00	0.00	0.00
3,000.0	19.90	163.61	2,890.2	-655.6	192.8	-574.4	0.00	0.00	0.00
3,100.0	19.90	163.61	2,984.3	-688.2	202.4	-603.0	0.00	0.00	0.00
3,200.0	19.90	163.61	3,078.3	-720.9	212.0	-631.6	0.00	0.00	0.00
3,300.0	19.90	163.61	3,172.3	-753.6	221.6	-660.2	0.00	0.00	0.00
3,400.0	19.90	163.61	3,266.4	-786.2	231.2	-688.8	0.00	0.00	0.00
3,500.0	19.90	163.61	3,360.4	-818.9	240.8	-717.4	0.00	0.00	0.00
3,595.3	19.90	163.61	3,450.0	-850.0	250.0	-744.7	0.00	0.00	0.00
3,600.0	19.41	164.46	3,454.4	-851.5	250.4	-746.0	12.07	-10.40	18.21
3,700.0	10.91	199.04	3,551.0	-876.6	251.8	-763.4	12.07	-8.51	34.57
3,800.0	12.23	261.96	3,649.4	-887.0	238.2	-760.0	12.07	1.32	62.93
3,900.0	21.65	289.14	3,745.0	-882.4	210.2	-735.8	12.07	9.42	27.18
4,000.0	32.80	299.43	3,833.9	-863.0	169.0	-691.9	12.07	11.16	10.29
4,100.0	44.40	304.83	3,911.9	-829.6	116.5	-630.3	12.07	11.60	5.40
4,200.0	56.17	308.35	3,975.7	-783.7	55.0	-553.7	12.07	11.77	3.52
4,300.0	68.01	311.01	4,022.4	-727.3	-12.8	-465.6	12.07	11.84	2.66
4,325.6	71.05	311.61	4,031.4	-711.4	-30.9	-441.5	12.07	11.87	2.35
4,400.0	74.62	312.33	4,053.4	-663.9	-83.7	-370.5	4.89	4.80	0.96
4,500.0	79.43	313.26	4,075.8	-597.7	-155.2	-273.2	4.89	4.81	0.93
4,600.0	84.24	314.15	4,090.0	-529.3	-226.7	-174.3	4.89	4.81	0.90
4,700.0	89.05	315.04	4,095.9	-459.3	-297.8	-74.8	4.89	4.81	0.88
4,713.1	89.68	315.15	4,096.0	-450.0	-307.0	-61.7	4.89	4.81	0.88
4,800.0	89.68	315.15	4,096.5	-388.4	-368.3	25.0	0.00	0.00	0.00
4,900.0	89.68	315.15	4,097.0	-317.5	-438.8	124.7	0.00	0.00	0.00
5,000.0	89.68	315.15	4,097.6	-246.6	-509.3	224.4	0.00	0.00	0.00
5,100.0	89.68	315.15	4,098.2	-175.7	-579.9	324.1	0.00	0.00	0.00
5,200.0	89.68	315.15	4,098.7	-104.8	-650.4	423.8	0.00	0.00	0.00
5,300.0	89.68	315.15	4,099.3	-33.9	-720.9	523.5	0.00	0.00	0.00
5,400.0	89.68	315.15	4,099.8	37.0	-791.4	623.2	0.00	0.00	0.00
5,500.0	89.68	315.15	4,100.4	107.9	-862.0	722.9	0.00	0.00	0.00
5,600.0	89.68	315.15	4,101.0	178.8	-932.5	822.6	0.00	0.00	0.00
5,700.0	89.68	315.15	4,101.5	249.7	-1,003.0	922.4	0.00	0.00	0.00
5,800.0	89.68	315.15	4,102.1	320.6	-1,073.5	1,022.1	0.00	0.00	0.00
5,900.0	89.68	315.15	4,102.6	391.5	-1,144.0	1,121.8	0.00	0.00	0.00
6,000.0	89.68	315.15	4,103.2	462.3	-1,214.6	1,221.5	0.00	0.00	0.00

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
6,100.0	89.68	315.15	4,103.8	533.2	-1,285.1	1,321.2	0.00	0.00	0.00
6,200.0	89.68	315.15	4,104.3	604.1	-1,355.6	1,420.9	0.00	0.00	0.00
6,300.0	89.68	315.15	4,104.9	675.0	-1,426.1	1,520.6	0.00	0.00	0.00
6,400.0	89.68	315.15	4,105.4	745.9	-1,496.7	1,620.3	0.00	0.00	0.00
6,500.0	89.68	315.15	4,106.0	816.8	-1,567.2	1,720.0	0.00	0.00	0.00
6,600.0	89.68	315.15	4,106.6	887.7	-1,637.7	1,819.8	0.00	0.00	0.00
6,700.0	89.68	315.15	4,107.1	958.6	-1,708.2	1,919.5	0.00	0.00	0.00
6,800.0	89.68	315.15	4,107.7	1,029.5	-1,778.8	2,019.2	0.00	0.00	0.00
6,900.0	89.68	315.15	4,108.2	1,100.4	-1,849.3	2,118.9	0.00	0.00	0.00
7,000.0	89.68	315.15	4,108.8	1,171.3	-1,919.8	2,218.6	0.00	0.00	0.00
7,100.0	89.68	315.15	4,109.4	1,242.2	-1,990.3	2,318.3	0.00	0.00	0.00
7,200.0	89.68	315.15	4,109.9	1,313.1	-2,060.9	2,418.0	0.00	0.00	0.00
7,300.0	89.68	315.15	4,110.5	1,384.0	-2,131.4	2,517.7	0.00	0.00	0.00
7,400.0	89.68	315.15	4,111.0	1,454.9	-2,201.9	2,617.4	0.00	0.00	0.00
7,500.0	89.68	315.15	4,111.6	1,525.8	-2,272.4	2,717.2	0.00	0.00	0.00
7,600.0	89.68	315.15	4,112.2	1,596.7	-2,342.9	2,816.9	0.00	0.00	0.00
7,700.0	89.68	315.15	4,112.7	1,667.6	-2,413.5	2,916.6	0.00	0.00	0.00
7,800.0	89.68	315.15	4,113.3	1,738.5	-2,484.0	3,016.3	0.00	0.00	0.00
7,900.0	89.68	315.15	4,113.8	1,809.4	-2,554.5	3,116.0	0.00	0.00	0.00
8,000.0	89.68	315.15	4,114.4	1,880.2	-2,625.0	3,215.7	0.00	0.00	0.00
8,100.0	89.68	315.15	4,115.0	1,951.1	-2,695.6	3,315.4	0.00	0.00	0.00
8,200.0	89.68	315.15	4,115.5	2,022.0	-2,766.1	3,415.1	0.00	0.00	0.00
8,300.0	89.68	315.15	4,116.1	2,092.9	-2,836.6	3,514.8	0.00	0.00	0.00
8,400.0	89.68	315.15	4,116.6	2,163.8	-2,907.1	3,614.6	0.00	0.00	0.00
8,500.0	89.68	315.15	4,117.2	2,234.7	-2,977.7	3,714.3	0.00	0.00	0.00
8,600.0	89.68	315.15	4,117.8	2,305.6	-3,048.2	3,814.0	0.00	0.00	0.00
8,700.0	89.68	315.15	4,118.3	2,376.5	-3,118.7	3,913.7	0.00	0.00	0.00
8,800.0	89.68	315.15	4,118.9	2,447.4	-3,189.2	4,013.4	0.00	0.00	0.00
8,900.0	89.68	315.15	4,119.4	2,518.3	-3,259.8	4,113.1	0.00	0.00	0.00
9,000.0	89.68	315.15	4,120.0	2,589.2	-3,330.3	4,212.8	0.00	0.00	0.00
9,100.0	89.68	315.15	4,120.6	2,660.1	-3,400.8	4,312.5	0.00	0.00	0.00
9,200.0	89.68	315.15	4,121.1	2,731.0	-3,471.3	4,412.2	0.00	0.00	0.00
9,300.0	89.68	315.15	4,121.7	2,801.9	-3,541.9	4,512.0	0.00	0.00	0.00
9,400.0	89.68	315.15	4,122.2	2,872.8	-3,612.4	4,611.7	0.00	0.00	0.00
9,500.0	89.68	315.15	4,122.8	2,943.7	-3,682.9	4,711.4	0.00	0.00	0.00
9,600.0	89.68	315.15	4,123.4	3,014.6	-3,753.4	4,811.1	0.00	0.00	0.00
9,700.0	89.68	315.15	4,123.9	3,085.5	-3,823.9	4,910.8	0.00	0.00	0.00
9,800.0	89.68	315.15	4,124.5	3,156.4	-3,894.5	5,010.5	0.00	0.00	0.00
9,900.0	89.68	315.15	4,125.0	3,227.3	-3,965.0	5,110.2	0.00	0.00	0.00
10,000.0	89.68	315.15	4,125.6	3,298.1	-4,035.5	5,209.9	0.00	0.00	0.00
10,100.0	89.68	315.15	4,126.2	3,369.0	-4,106.0	5,309.6	0.00	0.00	0.00
10,200.0	89.68	315.15	4,126.7	3,439.9	-4,176.6	5,409.4	0.00	0.00	0.00
10,300.0	89.68	315.15	4,127.3	3,510.8	-4,247.1	5,509.1	0.00	0.00	0.00
10,400.0	89.68	315.15	4,127.8	3,581.7	-4,317.6	5,608.8	0.00	0.00	0.00
10,500.0	89.68	315.15	4,128.4	3,652.6	-4,388.1	5,708.5	0.00	0.00	0.00
10,600.0	89.68	315.15	4,129.0	3,723.5	-4,458.7	5,808.2	0.00	0.00	0.00
10,700.0	89.68	315.15	4,129.5	3,794.4	-4,529.2	5,907.9	0.00	0.00	0.00
10,800.0	89.68	315.15	4,130.1	3,865.3	-4,599.7	6,007.6	0.00	0.00	0.00
10,900.0	89.68	315.15	4,130.6	3,936.2	-4,670.2	6,107.3	0.00	0.00	0.00
11,000.0	89.68	315.15	4,131.2	4,007.1	-4,740.8	6,207.0	0.00	0.00	0.00
11,100.0	89.68	315.15	4,131.8	4,078.0	-4,811.3	6,306.8	0.00	0.00	0.00
11,200.0	89.68	315.15	4,132.3	4,148.9	-4,881.8	6,406.5	0.00	0.00	0.00
11,300.0	89.68	315.15	4,132.9	4,219.8	-4,952.3	6,506.2	0.00	0.00	0.00
11,400.0	89.68	315.15	4,133.4	4,290.7	-5,022.8	6,605.9	0.00	0.00	0.00
11,500.0	89.68	315.15	4,134.0	4,361.6	-5,093.4	6,705.6	0.00	0.00	0.00
11,600.0	89.68	315.15	4,134.6	4,432.5	-5,163.9	6,805.3	0.00	0.00	0.00
11,700.0	89.68	315.15	4,135.1	4,503.4	-5,234.4	6,905.0	0.00	0.00	0.00
11,800.0	89.68	315.15	4,135.7	4,574.3	-5,304.9	7,004.7	0.00	0.00	0.00
11,857.8	89.68	315.15	4,136.0	4,615.2	-5,345.7	7,062.3	0.00	0.00	0.00

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
770H KOP - plan hits target center - Point	0.00	0.00	3,450.0	-850.0	250.0	1,898,740.04	2,731,088.04	36.218245°N	107.806225°W
770H POE - plan hits target center - Point	0.00	0.01	4,096.0	-450.0	-307.0	1,899,140.04	2,730,531.04	36.219344°N	107.808112°W
770H BHL - plan hits target center - Point	0.00	0.01	4,136.0	4,615.2	-5,345.7	1,904,205.25	2,725,492.36	36.233261°N	107.825193°W

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name		Casing Diameter (")	Hole Diameter (")
240.0	240.0	13 3/8"		13-3/8	17-1/2
2,438.2	2,362.0	9 5/8"		9-5/8	12-1/4

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
145.0	145.0	Ojo Alamo		0.00		
242.0	242.0	Kirtland		0.00		
502.0	502.0	Fruitland		0.00		
852.9	852.0	Pictured Cliffs		0.00		
1,060.6	1,057.0	Lewis		0.00		
1,250.6	1,242.0	Chacra		0.00		
2,315.9	2,247.0	Cliff House		0.00		
2,331.9	2,262.0	Menefee		0.00		
3,384.7	3,252.0	Point Lookout		0.00		
3,680.6	3,532.0	Mancos		0.00		
3,912.9	3,757.0	Gallup (MNCS. A)		0.00		
4,713.1	4,096.0	SILT (Target)		0.00		



Enduring Resources LLC

Directional Drilling Plan  
Plan View & Section View

Kimbeto Wash Unit 770H

San Juan Co., New Mexico


T23N-R09W-Sec.17-Lot P

Surface Latitude: 36.220580°N

Surface Longitude: 107.807071°W

Ground Level: 6561.0

Reference Elevation: KB @ 6583.0usft (Original Well Elev)




Design Target Details

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
770H KOP	3450.0	-850.0	250.0	1898740.04	2731088.04	36.218245°N	107.806224°W
770H POE	4096.0	-450.0	-307.0	1899140.04	2730531.04	36.219344°N	107.808112°W
770H BHL	4136.0	4615.2	-5345.7	1904205.24	2725492.36	36.233261°N	107.825193°W

Directional Drilling Plan Details

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	VSect
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.0
240.0	0.00	0.00	240.0	0.0	0.0	0.00	0.0
500.0	0.00	0.00	500.0	0.0	0.0	0.00	0.0
1495.1	19.90	163.61	1475.2	-164.1	48.3	2.00	-143.8
3595.3	19.90	163.61	3450.0	-850.0	250.0	0.00	-744.7
4325.6	71.05	311.61	4031.4	-711.4	-30.9	12.07	-441.5
4713.1	89.68	315.15	4096.0	-450.0	-307.0	4.89	-61.7
11857.8	89.68	315.15	4136.0	4615.2	-5345.7	0.00	7062.3



**WELL NAME: Kimbeto Wash Unit 770H****OBJECTIVE: Drill, complete, and equip single lateral in the Mancos Silt formation****API Number:** 30-045-**State:** New Mexico**County:** San Juan**Surface Elev.:** 6,561 ft ASL (GL) 6,583 ft ASL (KB)**Surface Location:** 17-23N-09W Sec-Twn- Rng 409 ft FSL 1,115 ft FEL**BH Location:** 18-23N-09W Sec-Twn- Rng 330 ft FNL 1200 ft FEL

**Driving Directions:** From the intersection of US HWY 550 and US HWY 64 in Bloomfield, NM: South on US HWY 550 for 35.9 miles to MM 115.7, right (southwest) at Nageezi Post Office on CR 7800 for 0.4 miles to 4-way intersection; straight (southwest) exiting CR7800 and continuing on 7820 for 0.6 miles to fork in road, right (southwest) on 7820 for 1.1 miles to 4-way intersection, straight (southwest) for 2.7 miles to existing access road for Kimbeto Wash 771H well.

**QUICK REFERENCE**

Sur TD (MD)	240	ft
Int TD (MD)	2,465	ft
KOP (MD)	3,603	ft
KOP (TVD)	3,400	ft
Target (TVD)	4,096	ft
Curve BUR	12 °/100 ft	
POE (MD)	4,713	ft
TD (MD)	11,858	ft
Lat Len (ft)	7,145	ft

**WELL CONSTRUCTION SUMMARY:**

	Hole (in)	TD MD (ft)	Csg (in)	Csg (lb/ft)	Csg (grade)	Csg (conn)	Csg Top (ft)	Csg Bot (ft)
Surface	17.500	240	13.375	54.5	J-55	BTC	0	220
Intermediate	12.250	2,465	9.625	36.0	J-55	LTC	0	2,465
Production	8.500	11,858	5.500	17.0	P-110	LTC	0	11,858

**CEMENT PROPERTIES SUMMARY:**

	Type	Wt (ppg)	Yd (cuft/sk)	Wtr (gal/sk)	Hole Cap. (cuft/ft)	% Excess	TOC (ft MD)	Total (sx)
Surface	Class G	15.8	1.174	5.15	0.6946	100%	0	284
Inter. (Lead)	G:POZ Blend	12.3	1.987	10.16	0.3132	40%	0	434
Inter. (Tail)	Class G	15.8	1.148	4.98	0.3132	10%	1,965	150
Prod. (Lead)	G:POZ blend	12.3	1.987	10.16	0.2691	40%	0	618
Prod. (Tail)	G:POZ blend	13.3	1.354	5.94	0.2291	10%	3,400	1,574

**COMPLETION / PRODUCTION SUMMARY:**

**Frac:** 36-stage (+/-) plug-and-perf frac with slick water and 13,000,000 lbs (+/-) proppant

**Flowback:** Flow up 5-1/2" casing or 2-7/8" tubing until returns are free of sand

**Production:** 2-7/8" tubing with packer set in 5-1/2" casing and gas-lift mandrels as needed

