

CHACO 2308-24I 155H API # 30-045-35551



Location

SHL: 1524' FSL 255' FEL Sec: 24 Twnshp: 23N Rge: 8W
 BHL: 2400' FSL 246' FWL Sec: 24 Twnshp: 23N Rge: 8W

Lat: 36.209393
 Long: -107.625161

Spud Date: 11/3/2014
 Completion: 5/19/2015
 Pool Name: Mancos
 Convert from GLV to Rod: 9/18/18

Wellbore updated 9/26/18 lg

Tops	MD	TVD
Ojo Alamo	876	875
Kirtland	1094	1091
Picture Cliffs	1537	1528
Lewis	1678	1667
Chacra	1920	1905
Cliff House	3021	2990
Menefee	3067	3036
Point Lookout	3930	3885
Mancos	4131	4084
Gallup	4466	4418

Land tubing @ 5699' w 2-7/8", L-80, 6.5#
 Tubing/Rod detail:

{ PROD. STRING. RAN, TOP/DOWN, 1/JNT. YELLOWBAND 3 1/2" 9.3# N80
 TOTAL/32.75', 3 1/2" X 2 7/8" EUE 8RD XOVER TOTAL/.80', 104/JNTS.
 SCANNED YELLOWBAND 2 7/8" J55 6.4# EUE TOTAL/3198.79', 43/JNTS.
 YELLOWBAND 2 7/8" 6.5# EUE N80 TOTAL/1370.17', 26/JNTS. NEW 2 7/8" EUE
 6.5# L-80 TOTAL/808.78', 2 7/8" X 7" TAC W/45K SHEAR TOTAL/2.33', 7/JNTS.
 NEW 2 7/8" EUE 6.5# L-80 TOTAL/216.47', NEW SN W/2.28 ID TOTAL/1.10',
 1/JNT. 2 7/8" EUE 6.5# J55 TOTAL/30.73', 2 7/8" X 2 3/8" EUE 8RD XOVER
 TOTAL/.80, 2 3/8" J55 SUB TOTAL/3.10', 2 7/8" SLOTTED SAND SCREEN
 TOTAL/10.14', 2 3/8" GAS BUSTER TOTAL/9.90', 2 3/8" MULESHOE W/CROSS
 PIN. W/14" KB ADDED TOP OF TAC@/5424' SN@/5643' EOT@/5699' LAND
 TBG. W/TBG/HANGER AND 2' SUB, SET TAC W/13 TO 15KK TENSION

12 1/4"
Hole

8 3/4"
Hole

6 1/8"
Hole

Surface: 9-5/8" 15 jnts 36# J-55 ST&C
 csg, set @ 402', float collar @ 373'
 Cmt'd 245sx of Type G. Circ., 26 bbls
 of cmt to surface.

TD @ 407'.

Intermediate: 7" csg set @ 5743', 154jts of
 J55, 23#, FC @ 5705'. Cmt'd w/ Lead @
 (737sx/192 bbls) of Halcem, followed by
 Tail @ (100sx/24 bbls) of Varicem. w/ 75

TD @ 5750'.

Prod Liner: 4 1/2" csg set @ 10387', 107 jts
 of P-110, 11.6#. LC @ 10296', RSI @ 10291',
 TOL @ 5582'.

Cmt'd 440sx/107 bbls of Extendacem. Circ.,
 24 Bbl Good Cement to Surface

TOL @ 5582'.

TD @ 10398'

PBTD @ 10296'.

