Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018 5. Lease Serial No. NMNM008005

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				If Indian, Allottee or Tribe Name EASTERN NAVAJO	
SUBMIT IN TRIPLICATE - Other instructions on page 2				7. If Unit or CA/Agreement, Name and/or No. NMNM132981A	
1. Type of Well ☑ Oil Well ☐ Gas Well ☐ Other				8. Well Name and No. NAGEEZI UNIT 501H	
Name of Operator Contact: JEVIN CROTEAU ENCANA OIL & GAS (USA) INCORPŒ-Mail: jevin.croteau@encana.com				9. API Well No. 30-045-35860-00-X1	
3a. Address 370 17TH STREET, SUITE 1700 Ph: 720- DENVER, CO 80202		. (include area code) 6-5339		10. Field and Pool or Exploratory Area BASIN MANCOS	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State	
Sec 3 T23N R9W SWNE 2544FNL 1510FEL 36.256241 N Lat, 107.772491 W Lon				SAN JUAN COUNTY, NM	
12. CHECK THE AI	PPROPRIATE BOX(ES) TO INDICA	TE NATURE OF	NOTICE,	REPORT, OR OTHE	ER DATA
TYPE OF SUBMISSION					
☐ Notice of Intent	☐ Acidize ☐ Deepen		☐ Production (Start/Resume)		☐ Water Shut-Off
	☐ Alter Casing ☐ Hydraulic Fracturing ☐		□ Reclamation		☐ Well Integrity
	☐ Casing Repair ☐ Ne	g Repair		lete	⊘ Other
☐ Final Abandonment Notice	☐ Change Plans ☐ Plu	inge Plans ☐ Plug and Abandon ☐ Te		orarily Abandon Drilling Operations	
BC	☐ Convert to Injection ☐ Plug Back ☐ Water		☐ Water D	isposal	
testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. The following Surface Casing data has been amended and added to this SN as requested by OCD: Drilled 12.25 in Surface hole to 334 ft (KB), run 9 5/8 in, 32.3 ppf K-55 casing to 329 ft (KB). Cement Surface Casing with 10bbls fresh water spacer, 38.98 bbls of 15.8 ppg type G cement (185sx), drop plug and displace with 24.1 bbls fresh water. Bump plug at 138 psi, float holding. Returned 18 bbls cement to surface. 8/20/18 Test BOP. Test Surface Casing to 1500 psi for 30 minutes, no pressure drop. Drilled 8.75 in Intermediate hole to 5265 ft (KB). Set Intermediate 7 in, 26 ppf J-55 Casing from surface to 5244 ft (KB).					
14. I hereby certify that the foregoing is true and correct. Electronic Submission #437274 verified by the BLM Well Information System For ENCANA OIL & GAS (USA) INCORPO, sent to the Farmington Committed to AFMSS for processing by JACK SAVAGE on 09/26/2018 (18JWS0160SE)					
Name (Printed/Typed) JEVIN CROTEAU Title AUTHORIZED REF				RESENTATIVE	
Signature (Electronic Submission) Date 09/26/2018					
	THIS SPACE FOR FEDER	AL OR STATE (OFFICE US	SE	
Approved By ACCEPT	JACK SAV	VAGE EUM ENGINEER		Date 09/26/2018	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the conduction of th	Office Farmington				
	U.S.C. Section 1212, make it a crime for any p statements or representations as to any matter v		willfully to ma	ke to any department or ag	gency of the United

Additional data for EC transaction #437274 that would not fit on the form

32. Additional remarks, continued

Cement Intermediate Casing, Stage 1 lead cement pumped 610 sxs of 12.3 ppg Class G cement, yield 1.95 ft3/sk. Stage 2 Tail cement pumped 240 sxs of 13.5 ppg Class G cement, yield 1.30 ft3/sk. Returned 90 bbls cement to surface. TOC at surface and BOC at 5265 ft (KB).

Tested 7 in Intermediate Casing on 8/24/18 to 1500 psi for 30 minutes, no pressure drop.

Started drilling out good Intermediate cement on 8/24/18.