Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137

Expires: July 31, 2010

5. Lease Serial No. NMSF079049B

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					Also ent
SUBMIT IN TRIPLICATE - Other instructions on page 2.				7. If Unit of CA/Agreement, Name and/or No.	
1. Type of Well Oil Well X Gas Well Other				8. Well Name and No. San Juan 28-6 Unit 151	
2. Name of Operator Hilcorp Energy Company			9. API Well No. 30-039-20317		
		. Phone No. (include are	ea code)	10. Field and Pool or Exploratory Area	
382 Road 3100, Aztec, NM 87410		505-599-34	100	Blanco Mesaverde/Basin Dakota	
4. Location of Well (Footage, Sec., T.,R Surface Unit G (S)	a.,M., or Survey Description) WNE) 1650'FNL & 1650' FEL	., Sec. 34, T28N,	R06W	11. Country or Parish, State Rio Arriba	, New Mexico
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA					
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Acidize	Deepen	P	roduction (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	R	eclamation	Well Integrity
X Subsequent Report	Casing Repair	New Construction	XR	ecomplete	Other
BP	Change Plans	Plug and Abandon	T	emporarily Abandon	
Final Abandonment Notice	Convert to Injection peration: Clearly state all pertinent details.	Plug Back		ater Disposal	
Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) 10/25/18 MIRU. ND WH. NU BOP. PT BOP, test good. Pull tbg hanger & tag fill @ 7844'. TOOH w/2-3/8" tbg. TIH w/4.5" csg scraper to 6200'. SDON. 10/26/18 TOOH w/csg scraper. TIH w/4.5" CIBP set @ 6075'. Roll well clean & test csg to 560#, good. TOOH. RU W/L. Run CBL from 6075' to surface. PT 4.5" csg & CIBP to 2000#/30 mins, test good. TOOH. Verbal CBL approval from Charile Perrin, NMOCD & Jack Savage, BLM to perf MV. 10/27/18 ND BOP. NU 5K WH, test seals, good. Install 7" 5K frac stack. PT csg & frac stack to 4000#, test good. RD. Rig released. 11/8/18 RU frac crew. Perf PT Lookout & Lower Menefee @ 5698', 5686', 5685', 5684', 5665', 5664', 5663', 5662', 5648', 5647', 5619', 5618', 5617', 5616', 5600', 5599', 5569', 5568', 5567', 5543', 5542', 5541', 5540', 5639', 5538', 5518', 5517', 5506', 5505' (1 SPF) for a total of 29, 0.34" dia holes. CONTINUED on Page 2					
14. I hereby certify that the foregoing is	true and correct. Name (Printed/Typed)				
Tammy Jones	Title Op	Title Operations/Regulatory Technician - Sr.			
Signature Tamy Imo			11/26	12018	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by		Title	MMOO	Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office	DEC 2 0	2018

11/9/18 Broke down well with water & 500 gal 15% HCL. Foam FRAC'D PT Lookout & Lower Menefee w/ 150,200# 40/70 sand & 50,408 gal slickwater & 1.80 million SCF N2 70 quality. avg rate = 57 BPM, avg PSI = 2432. Dropped 12 bio-balls with 1/2 of sand pumped. TIH & set frac plug @ 5450'. PT plug to 3000#, ok. Perf Cliffhouse & Upper Menefee @ 5418', 5417', 5416', 5415', 5414', 5349', 5348', 5338', 5320', 5319', 5318', 5305', 5304', 5303', 5302', 5301', 5295', 5294', 5293', 5272', 5271', 5270', 5269', 5268', 5185', 5184', 5163', 5148', 5124', 5123', 5122', 5121', 5119', 5118', 5117', 5091', 5090', 5081', 5071', 5049', 5048', 5022', 5021', 5020', 5019', 5018', 5017' (1 SPF) for a total of 47, 0.34" dia holes. Broke down well with water & 500 gal 15% HCL. Foam FRAC'D Cliffhouse & Upper Menefee w/ 150,160# 40/70 sand & 49,301 gal slickwater & 1.92 million SCF N2 70 quality. avg rate = 58 BPM, avg PSI = 2615. Dropped 9 bio-balls with 1/2 of sand pumped. RD frac crew.

11/15/18 MIRU. RU W/L. TIH & set isolation plug @ 4690'. RD W/L.

11/16/18 ND frac stack. NU BOP & PT, test good. TIH w/3-3/4" bit, D/O frac plugs. Clean out to CIBP @ 6075'. D/O CIBP & TIH to DK perf top. SDON.

11/17/18 Circ & clean out to PBTD @ 7848'. TOOH w/3-3/4" bit. TIH w/BHA to 7840', pump 8 bbls pad & PT tbg to 600#, good. Pump off check @ 1300# & unload well. PUH & Land 248 jts 2-3/8" 4.7# J-55 EUE T&C upset tubing @ 7750', SN @ 7748'. ND BOP. NU WH. RD. Rig released.

Well is now producing as Blanco Mesaverde/Basin Dakota commingle under DHC4023AZ.