

CHACO 2206 05A 436H API # 30-043-21226



Location

SHL: 939' FNL 357' FEL Sec: 5 Twnshp: 5N Rge: 6W
BHL: 990' FNL 2334' FEL Sec: 6 Twnshp: 22N Rge: 6W

Spud Date: 7/23/2014

Lat: 36.1726001 Completion: 10/4/2014

Long: -107.4833223 Pool Name: Lybrook Gallup

GLV install: 1/12/2015

Rod Pump: 3/28/2019

wellbore update: 4/5/19

Tops	MD	TVD
Ojo Alamo	1334'	999
Kirtland	1595'	1163
Pictured Cliffs	1903'	1459
Lewis	2010'	1576
Chacra	2323'	1872
Cliff House	3413'	2947
Menefee	3439'	3022
Point Lookout	4211'	3881
Mancos	4342'	4041
Gallup	4752'	4367

HOLE SIZE	CASING	CEMENT	VOLUME	CMT TOP
12-1/4"	9-5/8"	101 sx	163 cu. ft.	Surface
8-3/4"	7"	740 sx	1034 cu. ft.	Surface
6-1/8"	4-1/2"	500 sx	714 cu. ft.	TOL 5511'

12 1/4"
Hole

8 3/4"
Hole

6 1/8"
Hole

RAN 16 JTS, 9-5/8", LT&C, 36#, J-55, CSG
SET @ 345', FC @ 315'
Surface Casing -Hole Size: 12-1/4"

Run 139 jts 7", 23#, J-55, LT&C csg. Landed
@ 5875', FC @ 5830'
Intermediate Casing - Hole Size: 8-3/4"

Land tubing @ 5549' w/ 167 jnts 2-7/8", J-55, 6.5#

RIH WITH RODS, { ROD SRING RAN, 1 1/2" X 26'
CENTER SPRAY POLISH ROD, 4'6'8" X 7/8" PONY
RODS, 61 X 7/8" GUIDED 6/PER NEW RODS, 140 X
3/4" GUIDED 6/PER NEW RODS, 12 X 7/8" GUIDED
6/PER NEW RODS, 2 STABILIZER SUBS 1" X 4'
GUIDED, NEW 26K SHEAR SUB, 2 1/2" X 1 1/2" X 16'
X 18' RHBC PUMP WITH 1 1/2" X 15' DIP TUBE. 136"
STROKE. } TAG/SPACE OUT AS DIRECTED BY BLACK
ARROW THEN LOAD/TEST 20/BBLs. WATER WITH
RIG PUMP AND STROKING PUMP WITH RIG TO
450/PSI. GOOD/TEST, LEAVE 6" OFF BOTTOM AS
DIRECTED, CLAMP OFF RODS. SHUT IN WELL.

Land well at 5593' w/ 15' KB as follows 1/2 MS, 1 Jt
of 2.375" J55 4.7lb 8md EUE tbg, 1.50" FN at 5564',
183 Jts of 2.375" J55 4.7lb 8md EUE tbg 184 jts
total

TD @ 12348'

TOL @ 5511'

PBTD @ 12257'