

Submit to Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-10:
Revised June 10, 2007

WELL API NO.
30-045-33148

5. Indicate Type of Lease
STATE ☒ FEE ☐

State Oil & Gas Lease No.
B-11505-60-NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____
b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

7. Lease Name or Unit Agreement Name

Day State

2. Name of Operator
Burlington Resources LP

8. Well No.
#2M

3. Address of Operator
PO Box 4289 Farmington, NM 87499

9. Pool name or Wildcat
Blanco Mesaverde/Basin Dakota

4. Well Location
Unit Letter B : 295 Feet From The North Line and 2180 Feet From The East Line

Section 32 Township 32N Range 11W NMPM County San Juan

10. Date Spudded 2/1/06 11. Date T.D. Reached 2/8/06 12. Date Compl. (Ready to Prod.) 4/21/06 13. Elevations (DF& RKB, RT, GR, etc.) KB- 6458' GL- 6444' 14. Elev. Casinghead

15. Total Depth 7744' 16. Plug Back T.D. 7741' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools Cable Tools No

19. Producing Interval(s), of this completion - Top, Bottom, Name Basin Dakota 7574'-7702' 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run CBL-GR-CCL 22. Was Well Cored NO

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#, J55, ST&C	274'	12 1/4"	165 sx	15 bbls
7"	20#, J55, ST&C	3384'	8 3/4"	471 sx	35 bbls
4 1/2"	10.5#, J55, ST&C	7743'	6 1/4"	307 sx	TOC- 3250'

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SIZE	DEPTH SET	PACKER SET
				2-3/8" 4.7#, J55	7655'	None

26. Perforation record (interval, size, and number)

1 SPF @ 7574' to 7640' 17 HOLES
2 SPF @ 7650' to 7702' 40 HOLES
Total Holes= 57

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
7574'-7702' 10bbls 15% HCL acid, 102018 gal slickwater, 40000# 20/40 TLC sand

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)			Well Status (Prod. or Shut-in)		
SI		Pump			SI		
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas/Oil Ratio
4/19/06	1 hour	2			12 MCF		
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCFD	Water - Bbl.	Oil Gravity - API - (Corr.)	
SI-638#	SI-459#			291 MCF/D		MAY 2006	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
To Be Sold

Test Witnessed By

30. List Attachments

This is a MV/DK well being DHC per order #2141az.

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature Amanda Sandoval Printed Name Amanda Sandoval Title Regulatory Analyst Date 4/27/06
E-mail Address asandoval@br-inc.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo 1266'	T. Todilto
T. Salt	T. Strawn	T. Kirtland- 1321'	T. Entrada
		T. Fruitland- 2818'	
B. Salt	T. Atoka	T. Pictured Cliffs 3116'	T. Wingate
T. Yates	T. Miss	T. Lewis 3301'	T. Chinle
T. 7 Rivers	T. Devonian	T. Huer. Bent. 3796'	T. Permian
T. Queen	T. Silurian	T. Chacra 4236'	T. Penn "A"
T. Grayburg	T. Montoya	T. Upper Cliff House 4628'	
T. San Andres	T. Simpson	T. Mass. Cliff House 4856'	T. Penn. "B"
T. Glorieta	T. McKee	T. Menefee 5011'	T. Penn. "C"
T. Paddock	T. Ellenburger	T. Point Lookout 5378'	T. Penn. "D"
T. Blinberry	T. Gr. Wash	T. Mancos 5735'	T. Leadville
T. Tubb	T. Delaware Sand	T. Gallup 6764'	T. Madison
T. Drinkard	T. Bone Springs	T. Greenhorn 7451'	T. Elbert
T. Abo	T.	T. Graneros 7509'	T. McCracken
T. Wolfcamp	T.	T. Dakota 7571'	T. Ignacio Otzite
T. Penn	T.		T. Granite
T. Cisco (Bough C)	T.	T. Morrison	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
1266	1321		White, cr-gr ss.	6764	7451		Lt gry to brn calc carb micac Glaucl silts & very fine gr gry ss w/irreg.interbed sh
1321	2818		Gry sh interbedded w/tight, gry, fine-gr ss.	7451	7509		Highly calc gry sh w/thin lmst.
2818	3116		Dk gry-gry carb sh, coal, gm silts, light- med gry, tight, fine gr ss.	7509	7571		Dk gry shale, fossil & carb w/pyrite incl.
3116	3301		Bn-Gry, fine gm, tight ss.	7571			Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks
3301	3796		Shale w/siltstone stringers				
3796	4236		White, waxy chalky bentonite				
4236	4628		Gry fn gm silty, glauconitic sd stone w/drk gry shale				
4628	4856		Light gry, med-fine gr ss, carb sh				
4856	5011		Light gry, med-fine gr ss, carb sh				
5011	5378		Med-dark gry, fine gr ss, carb sh & coal				
5378	5735		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation				
5735	6764		Dark gry carb sh.				