

GL 6500'
KB 25'

NEBU 604 Com 3H
API # 30-045-35829

Surface Casing

26" hole @ 131'
20", 94#, J55 BTC @ 128' MD
TOC @ surface

Intermediate I Casing

17 1/2" hole @ 1035'
13 3/8", 54.5#, J55 BTC @ 1030' MD
TOC @ surface

DV 2397 - 2400'
ACP 2400 - 2425'

TOC @ 2810'

Intermediate II Casing

12 1/4" hole; TD 6520' MD
9 5/8", 40#, P110HC BTC @ 6503' MD; DV tool @ 2397'; ECP @ 2400'

Production Csg

8 3/4" hole @ 17,389' MD / 7080' TVD
5 1/2" 20# P110HC GBCD @ 17,352' MD

Frac plug @ 16,430'

PBTD 17,213'

Lower TS @ 17,166'

Upper TS @ 17,141'

Last perf @ heel 7581'

Perforating guns stuck in hole while POH (after perf 16,542 - 16,392 - stg 4)
Pumped down back to bottom
RIH w/ coil @ 16,420' to verify;
Roundtrip WL gauge ring, CCL (16,435') and 40 ft gun spacer; end of tool @ 16,476'
RIH & Set plug @ 16,430' - **this plug has not been drilled**

NMOC

JUL 11 2019

DISTRICT III