Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an Lease Serial No. NMSF078860

abandoned well. Use form 3160-3 (APL	6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on page 2		7. If Unit or CA/Agreement, Name and/or No. NMNM132981A		
Type of Well Oil Well		8. Well Name and No. NAGEEZI UNIT 627H		
2. Name of Operator Contact: SHAW-MARIE FORD DJR OPERATING LLC E-Mail: sford@djrllc.com		9. API Well No. 30-045-35649-00-X1		
3a. Address 1 ROAD 3263 AZTEC, NM 87410	3b. Phone No. (include area code) Ph: 505-632-3476	Field and Pool or Exploratory Area BASIN MANCOS		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State		
Sec 30 T24N R8W SWSW 1133FSL 0447FWL		SAN JUAN COUNTY, NM		
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				

TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off	
☑ Subsequent Report	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation	■ Well Integrity	
	☐ Casing Repair	■ New Construction	□ Recomplete	⊠ Other	
☐ Final Abandonment Notice	☐ Change Plans	□ Plug and Abandon	□ Temporarily Abandon	Drilling Operations	
bl	☐ Convert to Injection	☐ Plug Back	■ Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Intermediate Casing & Cement.
11/26/19: MIRU ad 920. NU 11 inch 3K BOP on pre-set 9.625 36# J55 surface casing with install 11 inch 5K Cameron wellhead. PT annular and TIW 250 low 5 min. 1500 high 10 min. PT blind rams, HCR, pipe rams, kill valves, check valve, lower Kelly, choke manifold and valves, full opening safety valve and inside BOP valve 250 low 5 min, 3000 high for 10 min. PT pre-set 9.625 inch surface casing to 1500 high 30 min. Drill 8.75 inch hole to 443 ft. 11/27/19: Drill 8.75 inch hole to 3591 ft. 11/28/19: Drill 8.75 inch hole to 4666 ft. 11/29/19: Drill 8.75 inch hole to 5864 ft. 11/30/19: Run 139 jts of 26 lb J55 LTC casing set at 5854 ft. Float collar at 5809 ft. RU BJ cement crew. PT 5000 on lines. Test good. Cement with 50% excess on both lead and tail. 10 bbls 7% KCL water spacer at 8.3 lb. Followed by 50 bbls (74 sx) 11 ppg. 3.82 yield. 25.75 gps. Integra Gaurd EZ

water spacer at 8.3 lb. Followed by 50 bbls (74 sx) 11 ppg, 3.82 yield, 25.75 gps IntegraGaurd EZ

MMOCD

OEC 03 2019

DISTRICT III

14. I hereby certify that the foregoing is true and correct. Electronic Submission #494120 verified by the BLM Well Information System For DJR OPERATING LLC, sent to the Farmington Committed to AFMSS for processing by JQHN HOFFMAN on 12/03/2019 (20JH0080SE)						
Name (Printed/Typed)	SHAW-MARIE FORD	Title	REGULATORY SPECIALIST			
Signature	(Electronic Submission)	Date	12/02/2019			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved By ACC	CEPTED		OHN HOFFMAN ETROLEUM ENGINEER	Date 12/03/2019		
certify that the applicant hol	ny, are attached. Approval of this notice does not warrant or ds legal or equitable title to those rights in the subject lease licant to conduct operations thereon.	Office	Farmington			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

⁽Instructions on page 2) ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **



Additional data for EC transaction #494120 that would not fit on the form

32. Additional remarks, continued

II spacer. LEAD: 168 bbls (404 sx) 12.3 ppg, 2.34 yield, 13.4 gps. TAIL: 62 bbls (233 sx) 13.5 ppg, 1.5 yield, 7.24 gps. Displace with 222 bbls FW. Bump plug. Check floats. Floats held. 10 bbls good cement back to surface.