

Submit 1 Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised July 18, 2013

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO.  
 30-045-30271  
 5. Indicate Type of Lease  
 STATE  FEE   
 6. State Oil & Gas Lease No.  
 E9707

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)  
 1. Type of Well: Oil Well  Gas Well  Other  
 2. Name of Operator  
 Mustang Resources LLC  
 3. Address of Operator  
 1220 S Main Ave, Aztec, NM 87410 / 1660 Lincoln ST, STE 1450, Denver, CO 80264  
 4. Well Location  
 Unit Letter F : 1910 feet from the North line and 1765 feet from the West line  
 Section 2 Township 26N Range 13W NMPM County San Juan  
 11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
 6047' GR

7. Lease Name or Unit Agreement Name  
 Flush  
 8. Well Number 1  
 9. OGRID Number  
 375495  
 10. Pool name or Wildcat  
 SWD; Mesa Verde

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Mustang Resources (Mustang) intends to plug and abandon the Flush 1 SWD, following the attached procedure.

Mustang has also attached wellbore schematics pre-plug, and post-plug.

*COAs*  
 Add Chacra plug: 1690-1590' Chacra top @ 1640'  
 Change Fruitland plug: 1070-970' Fruitland top @ 1020'  
 Add Kirtland/Ojo Alamo plug: 553'-380'  
 Kirtland top @ 503'  
 Ojo Alamo top @ 430'

**NMOCD**  
**MAR 06 2020**  
**DISTRICT III**

# Notify the OCO 24hrs prior to beginning operations.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Darlene Tadlock TITLE Production Technician DATE March 5, 2020

Type or print name Darlene Tadlock E-mail address: dtadlock@mustangresourcesllc.com PHONE: 505-334-9111

**For State Use Only**

APPROVED BY: Brandon Powell TITLE Line Manager DATE 3-25-20  
 Conditions of Approval (if any): FOR Brandon Powell

Company Name: Mustang Resources LLC  
 Well Name: Flush 1 (SWD)  
 API Number: 30-045-30271  
 Location: Sec 2, T26N, R13W (F) 1910' FNL & 1765' FWL  
 County: San Juan County, New Mexico



9 5/8" 36# Casing Shoe 282'  
 7" 23# Production Casing 4106'  
 Mesa Verde Perfs 2065'-3866'  
 7" Packer 1914'  
 DV Tool 1946'

Note: Follow all NMOCD/NEPA Rules and Regulations.

Note: Class G, 15.8 ppg Density and 1.15 ft<sup>3</sup>/sx yield for all cement activities.

<u>Step</u>	<u>Description</u>
1	***Must complete Bradenhead test prior to P&A
2	Prior to work, check lease roads, test rig anchors, arrange for fresh water on location
3	<b>Notify NMOCD and Tribal Agency 48 hours before commencing rig operations</b>
4	MIRU workover rig with 2M Class II BOPE.
5	***Complete MIT test on casing prior to releasing packer
6	ND WH and NU BOP
7	Release 7" Lock-Set production packer @ 1914'
8	TOH with 2 7/8" plastic coated tubing and packer
9	RU Wireline and set 7" CIBP @ 2040'
10	TIH with 2 3/8" 6.5 coated tubing to top of CIBP and circulate hole full of fresh water
11	<b>Plug 1:</b> Spot balanced plug of 29.6 sxs cement (34 ft <sup>3</sup> ), includes 50% excess, on top of CIBP. (2040' to 1890') Mesa Verde top is 2065'
12	TOH to 1850, reverse circulate to clean up any cement - WOC min 4 hours
13	TIH and tag top of cement
14	TOH to 1283'
15	<b>Plug 2:</b> Pictured Cliff top 1233'-Spot balanced plug of 29.6 sxs cement (34 ft <sup>3</sup> ), includes 50% excess (1283' to 1133')
16	TOH to 1100', reverse circulate to clean up any cement - WOC min 4 hours
17	TIH and tag top of cement
18	TOH to 850'
19	<b>Plug 3:</b> Fruitland top 800'-Spot balanced plug of 29.6 sxs cement (34 ft <sup>3</sup> ), includes 50% excess (850' to 700')
20	TOH to 650', reverse circulate to clean up any cement - WOC min 4 hours
21	TIH and tag top of cement
22	TOH 2 3/8" tubing
23	RU Wireline and perforate squeeze holes at 332' (TOC was recorded at 490')
24	RIH and set Cement Retainer @ 320'
25	TIH 2 7/8" tubing, establish circulation just above retainer to fill hole
26	Sting into retainer and establish circulation to surface up bradenhead (circulate clean)
27	<b>Plug 4:</b> Cement behind 7" csg from 332' to Surface'- Cement with 100 sxs cement (115 ft <sup>3</sup> ), includes 100% excess (332' to surface). Once cement to surface, Sting out of Cement Retainer (CR) and then place balanced plug 26.1 sxs cement (30 ft <sup>3</sup> ) from top of CR (320') up to 232' (50' above 9 5/8" shoe) includes 50% excess
28	TOH to 150', reverse circulate to clean up any cement - WOC min 4 hours
29	TIH and tag top of cement
30	TOH to 125'
31	<b>Plug 5:</b> Surface to 125' balanced plug of 36.5 sxs cement (42 ft <sup>3</sup> ), includes 50% excess (125' to surface), or pump cement until good cement to surface
32	TOH 2 7/8" tubing
33	Top off casing with cement
34	Cut off Casing and install P&A Permanent Marker to regulatory specifications
35	RD Rig and release



# Flush No. 1 SWD


## Current Wellbore Configuration

Location: 1910' FNL, 1765' FWL, (F)  
 Sec 2, T26N, R13W, San Juan  
 County, New Mexico

Field: Mesa Verde

API #: 30-045-30271

Spud Date: December 2000  
 Completion Date: April 20, 2001



Kirtland - 76'

Fruitland - 800'

Pictured Cliffs - 1233'

Mesaverde - 2060'



# Flush No. 1 SWD

## As Plugged Wellbore Configuration

Elevation: 6047' GL, 6052'KB

Location: 1910' FNL, 1765' FWL, (F)

Top of Cement @ Surface 9 5/8"

Sec 2, T26N, R13W, San Juan County, New Mexico

Bit Size - 12 1/4"

**Plug 5: Surface Top off, (125'-0'), mix 24.3 sx (28 cf) cement 125' balanced plug plus 50% excess, or until good cement to surface, top off casing when tubing out of hole**

Kirtland - 76'

9 5/8" 36# at 282' w/ 200sx; 236(cf) Class H

Field: Mesa Verde  
API #: 30-045-30271

Squeeze Holes 332'

Retainer

**Plug 4: TOC 490', Perforate squeeze holes @ 332', Cement Retainer (CR) 320', Sting in CR establish circulation, Mix 50.4 sx (58 cf) cement plus 100% excess, circulate until good cement to surface, sting out of CR, place 88' balanced plug with 17.4 sx (20 cf) cement plus 50% excess.**

CBL - TOC @ 490'

Spud Date: December 2000  
Completion Date: April 20, 2001

Fruitland - 800'

**Plug 3: Fruitland Top 800', (850'-750') Mix 20 sx (23 cf) cement 100' balanced plug plus 50% excess**

Bit size 8 3/4"

Pictured Cliffs - 1233'

**Plug 2: Pictured Cliff Top 1233, (1283'-1183') Mix 20 sx (23 cf) cement 100' balanced plug plus 50% excess**

DV Tool @ 1946' KB. Cement w/ 200sx (412 cf) Class H w/ 2% SMS, 1% CaCl2 and 1/4#/sx Celloflake. Tail w/ 50sx (59 cf) Class H

Mesaverde - 2060'

CIBP

**Plug 1: Mesa Verde Top 2060, set CIBP @ 2040', (2040'-1940') Mix 20 sx (23 cf) cement 100' balanced plug plus 50% excess**

Mesa Verde Perfs:

2065' - 2432' Total 332 holes. Frac w/ filtered produced water & 154,800# 20/40 sand

2753' - 3270' Total 170 holes. Frac w/ filtered produced water & 101,000# 20/40 sand

3433' - 3866' Total 186 holes (all zones, holes 0.32"). Frac w/ produced water & 101,000# Brady Sand (April 11, 2001)

7" 23.0# Csg @ 4103' w/ 400 sx (473cf) Class H w/1%CaCl2 and 1/4#/sx Celloflake (Note: 42 jts 23# N-80 LT&C on bottom, 19 jts 23# J-55 ST&C next, DV Tool, then 23 jts 23# J-55 ST&C, then 35 jts 26# J-55 on top)

PBTD @ 4069' KB  
TD: 4106' KB