Form 3160-5 (April 2004)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OM B No. 1004-0137 Expires: March 31, 2007
---

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an	6 101 C AU TO 3 31
	6. If Indian, Allottee or Tribe Name
abandoned well. Use Form 3160 - 3 (APD) for such proposals.	Ute Mountain Ute
SUBMIT IN TRIPLICATE- Other instructions on reverse side.	7. If Unit or CA/Agreement, Name and/or No.
Type of Well     Oil Well	8. Well Name and No.
2. Name of Operator Elk San Juan, Inc.	Ute Mountain Tribal 22D  9. API Well No.
3a Address 3b. Phone No. (include area code)	3004533423
1401 17th. Street, Suite 700, Denver Colorado, 80202 303 296 4505	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Dakota  11. County or Parish, State
J: 1990' FSL, 1545 FEL, CSE Section 22-T31N-R14W	11. County of Parisit, State
	San Juan County, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	4/1/10000
Acidize Deepen Production (Sta	art/Resume) Water Shut-Off
□ Notice of Intent □ Alter Casing □ Fracture Treat □ Reclamation	Well Integrity
Subsequent Report Casing Repair New Construction Recomplete	Other Spud Notice
Change Plans   Plug and Abandon   Temporarily Ab	pandon Revised
Final Abandonment Notice Convert to Injection Plug Back Water Disposal	
The subject well was spudded on 12/5/05 with the Patterson Rig #753. A 12 1/4" hole was drilled to casing @ 377. Cmt surface csg w/ 10 bbls wtr spacer, 245 sx standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 10 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 10 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface. Tstd BOPs, tsted csg to 15 mm from the standard cmt 1 w/ 3% calcium chloric yield, 5.20 gal/sk wtr. Pmp cmt @ 15.6 ppg; circulated 15 bbls to surface.	de, 1/4# flocele sk 15.60 lb/gal, 1.18 cuft/sk 850#
To Radove Ture 5/18/06	HAR 2 0 2006
San Aven Frescures Area	Bureau of Land Menagament
title and the second sections	Durango, Golorado
Freed and Alota Airport of	Comme
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	
Karin Kulin Title Engineering Technicia	n
Signature XIVIX XUM Date 04	4/18/2006
THIS SPACE FOR FEDERAL OR STATE OFFICE	USE
Approved by Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  Office	-
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to	

(Instructions on page 2)

