

Submit to Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-10:
Revised June 10, 2001

WELL API NO.
30-039-29463

5. Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER ☐

2. Name of Operator
ConocoPhillips

3. Address of Operator
PO Box 4289 Farmington, NM 87499

7. Lease Name or Unit Agreement Name

San Juan 29-6 Unit

8. Well No.
#59B

9. Pool name or Wildcat
Blanco Mesaverde

4. Well Location

Unit Letter B : 660 Feet From The North Line and 1150 Feet From The East Line

Section 5 Township 29N Range 6W NMPM County Rio Arriba

10. Date Spudded 3/19/06 11. Date T.D. Reached 3/24/06 12. Date Compl. (Ready to Prod.) 5/16/06 13. Elevations (DF& RKB, RT, GR, etc.) KB- 6303' GL- 6290' 14. Elev. Casinghead

15. Total Depth 5930' 16. Plug Back T.D. 5898' 17. If Multiple Compl. How Many Zones? Single 18. Intervals Drilled By Rotary Tools Cable Tools No

19. Producing Interval(s), of this completion - Top, Bottom, Name
Blanco Mesaverde 4440'-5710'

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run

22. Was Well Cored
NO

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#, H40, ST&C	234'	12 1/4"	Surface; 150 sx	15 bbls
7"	20#, J55, ST&C	3230'	8 3/4"	Surface; 560 sx	50 bbls
4 1/2"	10.5#, J55, ST&C	5934'	6 1/4"	TOC 2382'; 315 sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-3/8" 4.7#, J-55	5605'	None

26. Perforation record (interval, size, and number)

5218'-5222'; 5241'-5245'; 5264'-5268'; 5285'-5295'; 5600'-5612';
5624'-5630'; 5660'-5692'; 5706'-5710'; (46 holes)

4440'-4465'; 4576'-4579'; 4588'-4595'; 4611'-4614'; (42 holes)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5218'-5710'	1000 gals 15% HCL acid 60 quality slickfoam, 202020 20/40 Brady sand, 1000 gals of F103, F104, B105, 2750180 SCF N2
4440'-4614'	1000 gals 15% HCL acid 70 quality 20# linear gel, 125860 16/30 Brady sand, 1000 gals of B105, F103, GBW-30, 1797516 SCF N2

28. PRODUCTION

Date First Production SI		Production Method (Flowing, gas lift, pumping - Size and type pump) Pump			Well Status (Prod. or Shut-in) SI		
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
5/16/06	4 hours	½"		0	320 MCF	0	
Flow Tubing Press. 290#	Casing Pressure	Calculated 24- Hour Rate	Oil - Bbl.	Gas - MCFD	Water - Bbl.	Oil Gravity - API - (Corr.)	
	520#			1914 MCFD			

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Test Witnessed By

To Be Sold

30. List Attachments

This is a single producing Mesaverde well.

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature Amanda Sandoval Printed Name Amanda Sandoval Title Regulatory Analyst Date 5/23/06
E-mail Address asandoval@br-inc.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo 2494'	T. Todilto
T. Salt	T. Strawn	T. Kirtland- 2645'	T. Entrada
		T. Fruitland- 3085'	
B. Salt	T. Atoka	T. Pictured Cliffs 3405'	T. Wingate
T. Yates	T. Miss	T. Lewis	T. Chinle
T. 7 Rivers	T. Devonian	T. Huer. Bent.	T. Permian
T. Queen	T. Silurian	T. Chacra 4421'	T. Penn "A"
T. Grayburg	T. Montoya	T. Upper Cliff House 5106'	
T. San Andres	T. Simpson	T. Mass. Cliff House	T. Penn. "B"
T. Glorieta	T. McKee	T. Menefee 5301'	T. Penn. "C"
T. Paddock	T. Ellenburger	T. Point Lookout 5592'	T. Penn. "D"
T. Blinberry	T. Gr. Wash	T. Mancos	T. Leadville
T. Tubb	T. Delaware Sand	T. Gallup	T. Madison
T. Drinkard	T. Bone Springs	T. Greenhorn	T. Elbert
T. Abo	T.	T. Graneros	T. McCracken
T. Wolfcamp	T.	T. Dakota	T. Ignacio Otzte
T. Penn	T.		T. Granite
T. Cisco (Bough C)	T.	T. Morrison	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
2494	2645		White, cr-gr ss.				Lt gry to brn calc carb micac Glauc silts & very fine gr gry ss w/irreg.interbed sh
2645	3085		Gry sh interbedded w/tight, gry, fine-gr ss.				Highly calc gry sh w/thin lmst.
3085	3405		Dk gry-gr carb sh, coal, gm silts, light- med gry, tight, fine gr ss.				Dk gry shale, fossil & carb w/pyrite incl.
3405	4421		Bn-Gry, fine gm, tight ss. Shale w/siltstone stringers White, waxy chalky bentonite				Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks
4421	5106		Gry fn gm silty, glauconitic sd stone w/drak gry shale				
5106	5301		Light gry, med-fine gr ss, carb sh Light gry, med-fine gr ss, carb sh				
5301	5592		Med-dark gry, fine gr ss, carb sh & coal				
5592			Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation Dark gry carb sh.				