<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

1220 South St. Francis Dr. office Santa Fe, NM 87505

Is pit or below-grade tan	ade Tank Registration or Clos ak covered by a "general plan"? Yes 🛣 1	No 🗌	
Type of action: Registration of a pit of	or below-grade tank Closure of a pit or below-	grade tank 🔀	
Operator: BP America Production Company Telephor	ne: <u>(505)326-9200</u> e-mail address:	· · · · · · · · · · · · · · · · · · ·	
Address: 200 Energy Ct. Farmington, NM 87401			
Facility or well name: Blanco Com#2-1 API#: 3	30045 09 8 67 U/L or Qtr/Qtr_t	Sec <u>23</u> t <u>30N r 11W</u>	
County: San Juan Latitude	Longitude	NAD: 1927 🗌 1983 🗍	
Surface Owner: Federal State Private Indian			
Pit	Below-grade tank		
Type: Drilling Production Disposal	Volume:bbl Type of fluid:		
Workover	Construction material:		
Lined 🔲 Unlined 🔲	Double-walled, with leak detection? Yes If not, explain why not.		
Liner type: Synthetic Thicknessmil Clay			
Pit Volumebbl			
	Less than 50 feet	(20 points)	
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)	
high water elevation of ground water.)	100 feet or more	(0 points)	
	V	(20	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	No	(0 points)	
Distance to surface untary (horizontal distance to all yestlands misses	Less than 200 feet	(20 points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)	
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks (2) Inc.	dicate disposal location: (check the onsite box if	
your are burying in place) onsite offsite foffsite, name of facility	• • • • • • • • • • • • • • • • • • • •	-	
remediation start date and end date. (4) Groundwater encountered: No 🗆 Y		n. and attach sample results.	
(5) Attach soil sample results and a diagram of sample locations and excaval	tions.		
Additional Comments:			
See Attached Documentation			
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline			
Date: 11/01/2005	1		
Printed Name/Title Jeffrey C. Blagg, Agent Signate	ure Juffy C. She	>	
Your certification and NMOCD approval of this application/closure does n	not relieve the operator of liability should the conte	nts of the pit or tank contaminate ground water or	
otherwise endanger public health or the environment. Nor does it relieve the regulations.			
	1 -	<i>N</i>	
Approval: Printed Name/Title CEPUTY COL & GAS INSPECTOR, DIST, 429		DEC 1 4 2005	
Printed Name/Title and Out On the Out of the Color of the	Signature 75 - 1/ 1	// Data: MPA T 2 8000	

3004509867

301081					
BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	LOCATION NO: <u>80858</u> C.O.C. NO: 8693				
FIELD REPORT: CLOSURE VERIFICATION	PAGE No: of				
QUAD/UNIT: K SEC: Z TWP: 30N RNG: 11W PM: NM CNTY: 55 ST: NM	DATE STARTED: 6-5-0/ DATE FINISHED: 6-5-0/				
QTR/FOOTAGE: 18505 (18500 NE SW CONTRACTOR: FLINT	ENVIRONMENTAL JCB				
EXCAVATION APPROX. 9 FT. x 9 FT. x 5 FT. DEEP. CUBIC	YARDAGE: O				
DISPOSAL FACILITY: DN-SITE REMEDIATION METHOD: CLOSE AS IS					
LAND USE: RANGE LEASE: STATE FOR	RMATION: MV				
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 60 FT. N	210W FROM WELLHEAD.				
DEPTH TO GROUNDWATER: <50 NEAREST WATER SOURCE: <7000 NEAREST SURFACE WATER: <6000 CHECK ONE:					
NMOCD RANKING SCORE: 20 NMOCD TPH CLOSURE STD: 100 PPM	PIT ARANDONED				
DESCRIPTION: DESCRIPTION: OVM CALIB. READ. 130.9 ppm TIME: 0900 ambom	STEEL TANK INSTALLED FIBERGLASS TANK INSTALLED				
DEGOTATION					
SQUARE EARTHEN PIT, LIKELY HAD STEEL PIT U	Men or or				
USED BACK HUE TO SAMPLE.					
0'- 8' COALSE GRAINED SAND, KellOW TAN, D	RT.				
(CLOSED)					
FIELD 418.1 CALCULATIONS TIME SAMPLE I.D. LAB NO: WEIGHT (g) mL. FREON DIL	LUTION READING CALC. ppm				
SCALE					
O FT					
PIT PERIMETER PIT	PROFILE				
OVM					
RESULTS SAMPLE FIELD HEADSPACE PID (ppm)					
10 PID (ppm) 1 @ COP 1.5					
3 @	- 0 >				
4 @ 5 @	A				
A = 9 = 9 = 10					
5					
TEST LAB SAMPLES SAMPLE ANALYSIS TIME 3					
FULL COB TPH 0840	SAMAR				
SAMPLE SAMPLE.					
TRAVEL NOTES: CALLOUT: 6-4-01 Non ONSITE: 6-5-01	0745				

revised: 03/12/01

bei1005.skd



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow C @ 8'	Date Reported:	06-07-01
Laboratory Number:	19972	Date Sampled:	06-05-01
Chain of Custody No:	8693	Date Received:	06-05-01
Sample Matrix:	Soil	Date Extracted:	06-06-01
Preservative:	Cool	Date Analyzed:	06-07-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Blanco Com 2 - 1.

Analyst Certification

Christin m Walters Review