District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

	or below-grade tank Closure of a pit or below-gr		
Operator: BP America Production Company Telephon	ne: <u>(505)326-9200</u> e-mail address:		
Address: 200 Energy Ct. Farmington, NM 87401			
Facility or well name: Warren #48 API#:	3004526966 U/L or Qtr/Qtr H	Sec_ <u>13</u> T <u>28N_R_9W</u>	
County: San Juan Latitude	Longitude	NAD: 1927 🗌 1983 🗌	
Surface Owner: Federal State Private Indian			
Pit	Below-grade tank		
Type: Drilling Production Disposal	Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not, explain why not.		
Workover ☐ Emergency ☐			
Lined Unlined			
Liner type: Synthetic Thicknessmil Clay			
Pit Volumebbl			
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)	
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)	
	100 feet or more	(0 points)	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	No	(0 points)	
	Less than 200 feet	(20 points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)	
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excavations.	Yes If yes, show depth below ground surface	description of remedial action taken including	
Additional Comments:			
See Attached Documentation			
,			
	Harrist Harris		
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline			
Date: 11/01/2005	111		
Printed Name/Title Jeffrey C. Blagg, Agent Signat	ture Jeffy C. Oligy	7	
Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.			
Approval: OPPUTY OR & GAS INSPECTOR, OIST. &	Signature Brangh De		

	GG ENGINEERING, 87, BLOOMFIELD, (505) 632-1199	NM 87413	C.O.C. NO: 8000 (
FIELD REPORT: CLC	SURE VERIF	ICATION .	PAGE No: of			
QUAD/UNIT: I SEC: 13 TWP: 28N			DATE STARTED:			
QTR/FOOTAGE:1850'N 1050'E SELNE			ENVIRONMENTAL NU			
EXCAVATION APPROX. NA FT. x NA	FT. x <u>NO</u> FT. 1	DEEP. CUBIC	YARDAGE:			
DISPOSAL FACILITY: ON-SITE						
FIELD NOTES & REMARKS: PIT LO	CATED APPROXIMATELY	84 FT.	574W FROM WELLHEAD			
	ATER SOURCE: >1000		CE WATER: 2/000			
NMOCD RANKING SCORE: NMOCD TPH	CLOSURE STD: <u>5000</u> PPM CALIB. READ. <u>53.7</u> ppm		CHECK ONE			
SOIL AND EXCAVATION DVM	CALIB. GAS = 100 ppm	RF = 0.52	STEEL TANK INSTALLED			
			_ FIBERGLASS TANK INSTALLED			
SOIL TYPE: SAND / SILTY SAND / SILT / SOIL COLOR: OR. YELL ORANGE	TO MOD. YELL - BROWN					
COHESION (ALL OTHERS): NON COHESIVE / CONSISTENCY (NON COHESIVE SOILS): LOOS			A COHEZIAE			
PEASTICITY (CLAYS): NON PLASTIC / SLIGH	TLY PLASTIC / COHESIVE	/ MEDIUM PLAS	TIC / HIGHLY PLASTIC			
DENSITY (COMESIVE CLAYS & SILTS): SOFT MOISTURE: DRY / SLIGHTLY MOIST / MOIST			(CLOSED)			
DISCOLORATION/STAINING OBSERVED: YES	NO EXPLANATION					
HC ODOR DETECTED: YES NO EXPLANATE SAMPLE TYPE: GRAD / COMPOSITE - # OF ADDITIONAL COMMENTS: STEEL TANK REP	PTS					
ADDITIONAL COMMENTS: STEEL TANK REP	houted prior to sa	mpling.				
SCALE SAMP TIME SAMPLE LD	FIELD 418.1 CA		JTION READING CALC. ppm			
SAMIT. TIME SAMITE 1.D.	LAB NO. WEIGHT (g)	THE. TREGIT DIE	STION READING CAEC. DB			
0 FT						
PIT PERIMETER ~/	Own	PIT	PROFILE			
25×25×5	OVM RESULTS					
	SAMPLE FIELD HEADSPACE PID (ppm)	7				
25	1 @ 9' 3.7					
BERM	3 @ 4 @	7				
TEST	5 @	NOT	APPLICABLE			
DI HOLE APPEUX.		_				
3 BELOW		_	•			
TANK 80 TOM						
LAB SAMPLES SAMPLES						
STEEL SEP.	De 9' TPH (8015) 0900	5				
BOTTOM APPROX.	PASSED	_				
5'BELOW GRADE						
TRAVEL NOTES: CALLOUT 7/32/		7/24/21	Λ·			
TRAVEL NOTES: CALLOUT: 7/23/5/-/	ONSHE:	7/24/01 - more				



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

- 11			
Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 9'	Date Reported:	07-25-01
Laboratory Number:	20 44 7	Date Sampled:	07-24-01
Chain of Custody No:	9393	Date Received:	07-24-01
Sample Matrix:	Soil	Date Extracted:	07-25-01
Preservative:	Cool	Date Analyzed:	07-25-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Warren #4E Separator Pit Grab Sample.

Analyst C. Oplesen

Review Review