This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Operator PATINA SAN JUAN, INC.

Lease Name ALAMO 22

Well No. # 08

Location Of Well: Unit Letter H Sec 22 Twp 31N Rge 13W API # 30-045-32690

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	Basin Fruitland Coal	Gas	Artificial Lift	Casing
Lower Completion	Basin Dakota	Gas	Flow	Tubing

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	05/18/06, 11:00 a.m.	5 days	105	Yes
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	05/18/06, 11:00 a.m.	3 days	720	Yes

Flow Test No. 1

			riow re	St 140. 1		
Commenced at (hour, date)*				Zone producing (Upper or Lower):		
Time Lapsed Time		Pressure		Prod. Zone	Remarks	
(Hour, Date)	Since*	Upper Compl.	Lower Comp	l. Temp.		
05/19/06						
11:00 a.m.	24 hrs	20	310	N/A		
05/20/06						
11:00 a.m.	24 hrs	40	675	N/A		
05/21/06					Open DK tbg @ 11:00 a.m. Flow lower	
11:00 a.m.	24 hrs	85	720	N/A	zone.	
05/22/06						
11:00 a.m.	24 hrs	95	290	N/A		
05/23/06						
11:00 a.m.	24 hrs	100	85	N/A	(Crossover). Packer holding.	
05/24/06						
11:00 a.m.	24 hrs	105	40	N/A	Packer holding OK.	

Production rate during test

Oil:	0	BOPD based on	Bbls. In	Hrs.	Grav.	GOR	
		-					

Gas: <u>158</u> MCFPD; Test thru (Orifice or Meter): <u>METER</u>

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)			
Completion				·			
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)			
Completion				and the same of th			

(Continue on reverse side)

Flow Test No. 2

commenced a	nt (hour, date)**		Zor		pper or Lower):	
Time Hour, Date)	Lapsed Time Since**		essure Lower Compl.	Prod. Zone	Remarks	41
						.,
····						
				,		:
7					1	
				,		
oduction rate		d on		Hrs	Grav. GOR	
emarks:	MCFP	D; Test thru (Ori	nce or Meter):			
nereby certify	that the informat	tion herein contai	ned is true and com	plete to the best	of my knowledge.	
	MAY 3 1 2006		20	Operator	PATINA SAN JUAN, INC.	
ew Mexico O	il Conservation I	Division	1	Ву	Langh sattl	
1 /4. V		ra		Title	PRODUCTION FOREMAN	
tle DEPUTY O	& GAS INSPECTO)R, DIS1.	· · · · · · · · · · · · · · · · · · ·	E-mail Addr	ess dwright@nobleenergyinc.com	
				Date	5.30-06.	

Northwest New Mexico Packer Leakage Test Instructions

A packer leakage test shall be commenced on each multiply mpleted well within seven days after actual completion of the well, and nually thereafter as prescribed by the order authorizing the multiple mpletion. Such tests shall also be commenced on all multiple mpletions within seven days following recompletion and/or chemical fracture treatment, and whenever remedial work has been done on a ll during which the packer or the tubing have been disturbed. Tests all also be taken at any time that communication is suspected or when quested by the Division.

At least 72 hours prior to the commencement of any packer leakage st, the operator shall notify the Division in writing of the exact time the st is to be commenced. Offset operators shall also be so notified.

The packer leakage test shall commence when both zones of the dual mpletion are shut-in for pressure stabilization. Both zones shall remain ut-in until the well-head pressure in each has stabilized, provided wever, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be oduced at the normal rate of production while the other zone remains ut-in. Such test shall be continued for seven days in case of a gas well d 24 hours in the case of an oil well. Note: if, on an initial packer akage test, a gas well is being flowed to the atmosphere due to the lack a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be ut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).