

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2006 MAY 30 PM 2 08

1. **Type of Well**
GAS

2. **Name of Operator**
ConocoPhillips

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit P (SESE), 925' FSL & 1054' FEL, Sec. 14, T32N, R8W, NMPM

5. **Lease Number**
NMSF-079380
6. **If Indian, All. or
Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 32-8 Unit
Well Name & Number**

9. **SJ 32-8 Unit #267
API Well No.**

30-045-33075

10. **Field and Pool**

Basin Fruitland Coal

11. **County and State**
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

5/7/06 MIRU Patterson Rid #749. Spud 12-1/4" hole @ 230 am 5/8/06. Drilled to 240'. Circ. hole. RIH w/9-5/8", 32.3#, J-55 Casing and set @ 231'. RU to cement. Pumped preflush of 20 bbls FW & gel. Pumped 150 sx (180 cf-32 bbls) D-907+3% BWOC S-001, .25#/sx D-130. Dropped plug and displaced w/17 bbls FW. Circ. 5 bbls good cement to surface. WOC. NU WH, NU BOJP. 5/9/06 PT casing to 1000#/30 min. Good test.

5/9/06. RIH w/8-3/4" hole & tagged cement @ 191'. D/O cement & then ahead to 3880' (intermediate TD). Circ. hole. RIH w/91 Jts 7", 23#, J-55 casing and set @ 3870'. RU to cement. Pumped 500 sx (1290 cf - 229 bbl) Class G w/3% D-079, .2% D-046, 25#/sx D-29). Tailed w/100 sx (125 cf - 22 bbls) 50/50 G-POZ w/2% D-20, .1\$ D-46, 2% S-001, 5#/sx D-24, 1% D-65. Dropped plug and displaced w/147 bbls FW. Bumped plug to 1600 #. 40 bbls good cement circ. to surface. ND BOP, set slips & cut off casing. RD & released rig @ 1200 hrs 5/13/06. Will show casing PT on the next report. PT will be conducted by the completion rig.

14. I hereby certify that the foregoing is true and correct.

Signed Patsy Clugston Title Sr. Regulatory Specialist Date 5/26/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

Date
JUN 05 2006

FARMINGTON FIELD OFFICE

NMOC