Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-045-33218 5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE
District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
SUNDRY NOT (DO NOT USE THIS FORM FOR PROPO	ICES AND REPORTS ON WELLS OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A ICATION FOR PERMIT" (FORM C-101) FOR SUCH	7. Lease Name or Unit Agreement Name Valentine Gas Com
1. Type of Well: Oil Well	Gas Well Other D	8. Well Number 1 M
2. Name of Operator	63	9. OGRID Number
BP AMERICA PRODUCTION COMPANY		000778
3. Address of Operator P.O. BOX 3092 HOUSTON, TX 77079-2064		10. Pool name or Wildcat
		Basin Dakota & Blanco Mesaverde
4. Well Location		
Unit Letter C: 350 feet from the North line and 2420 feet from the West line		
Section 32 Township 32N Range 10W NMPM SAN JUAN County 11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
5984'		
Pit or Below-grade Tank Application or Closure		
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB		
OTHER: Change to Driling	Plan OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
The original APD was submitted on 7/8/05 and approved 7/12/05. BP requests approval to change the drilling plan		
as per the following:		
Surf. CSG: hole size from 13.5" to 14.5"; Casing Size from 9.625" to 10.750"; Weight from 32 to 40.5; Cement		
from 154sxs to 163sxs.		
Int CSG: hole size from 8.750" to 9.875"; Casing Size from 7" to 7.625"; Weight from 20 to 26.4; Depth from		
3199' to 2420'; Cement from 322 sxs to 349 sxs.		
Production CSG : hole size from 6.25" to 6.750"; Cement from 337 sxs to 512 sxs.		
Please reference e-mail to Charlie Perrin on 6/1/2006. Should you have any questions please call Harald Jordan @326-9202		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan		
SIGNATURE hory TITLE Regulatory Analyst DATE 06/06/2006		
Type or print name Cherry Hlava E-mail address: hlavacl@bp.com Telephone No. 281-366-4081 For State Use Only		
APPROVED BY: H. Villanua TITLE TITLE DATE DATE DATE DATE		

Hlava, Cherry L

From:

Jordan, Harald G

Sent:

Thursday, June 01, 2006 2:37 PM Charlie Perrin (cperrin@state.nm.us)

To: Cc:

Hlava, Cherry L

Subject:

BP Cedar Hill Well Design Changes

Attachments:

Fairway MV DK Design Change.xls

Charlie,

I am sending you for your review more detailed information on our planned well design changes for the MV/DK wells in the Cedar Hill area.

We are proposing these design changes to better manage the lost circulation issues we have experienced while fluid drilling through the Fruitland Coal. Instead of setting the intermediate casing into the Lewis, we are planning to topset the coal with an 'upsized' intermediate string and thus include the possibility of running a contingency drilling liner in case we encounter water influx from the Fruitland Coal or Pictured Cliffs while air drilling to the Dakota. In that case alternative #2 will apply. Should we not encounter any fluid influx the design alternative #1 will apply.

Based on our experience from topsetting 8 MV wells in this area in 1999/2000 I do not expect any fluid influx, however we rather increase our casing size than be forced to fluid drill to the Dakota with both the depleted Fruitland Coal and the MV exposed.

The first tab in the attached spreadsheet contains the wells for which we are requesting the sundries, the second tab details the proposed design changes.

Cherry Hlava will follow up on this e-mail with the official sundry applications. In the event that we will need to move to these wells within the next 2 weeks I will call you to obtain a verbal approval.

The Martinez GC J #1M presents a different problem since we have already preset the 9 5/8" surface pipe. Based on the learnings from drilling the wells in question we will either proceed as originally planned [in case we have not encountered any fluid influx on any of the wells] or propose to abandon the surface hole and redrill the well with bigger surface casing.

I appreciate your consideration.



Fairway MV_DK Design Change.xl...

Harald G. Jordan

Drilling Engineer BP; San Juan Performance Unit

office: (505) 326-9202 cell:(505) 486-5357