District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes No \(\sigma\)

	or below-grade tank \(\begin{array}{ll} \text{Closure of a pit or below-grade} \)			
Operator: Elm Ridge Resources Telephone: (505) 632-347 Address: #20 CR 5060, Bloomfield, New Mexico, 87413 Facility or well name: Candado No. 20A API #: 300397 County: Rio Arriba Latitude 36.510550 I Surface Owner: Federal State Private Indian	21452 U/L or Qtr/Qtr O Sec 3 T_ Longitude107.559083 NAD: 1927 ☑	MAR 2000		
Pit Type: Drilling □ Production ☒ Disposal □ Workover □ Emergency □ Lined □ Unlined ☒ Liner type: Synthetic □ Thicknessmil Clay □ Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not	, explain why not.		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)		
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.) Yes No (20 points) (0 points)				
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points) 10		
Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite ☐ offsite ☒ If offsite, name of facilityEnvirotech, Landfarm #2 (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth below ground surfaceft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.				
Additional Comments:				
Approximately 40 cubic yards of contaminated soil was excavated and train				
Maximum reasonable extent of excavation was reached at bedrock 5' below	w ground surface. BTEX sample taken and analyzed v	ia method 8021B		
Bottom of excavation was sprayed with potassium permanganate solution				
,				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit, or an (attached) alternative OCD-approved plan Date:				
Printed Name/Title Signature Signature Date: MAR 1 6 2006				

		т		
CLIENT: Elm Pidge	ENVI	ROTECH INC.	!	LOCATION NO:
:	5796 FARMING	TAL SCIENTISTS & ENGINEER U.S. HIGHWAY 64-3014 GTON, NEW MEXICO 87401	es .	C.O.C. NO:
	РНО	NE: (505) 632-0615		
FIELD REPORT	Γ: CLOSU	RE VERIF	ICATION	PAGE No: 1 of 1
LOCATION: NAME: CANCADO				DATE STARTED: 1/4/06 DATE FINISHED: 1/13/06
QUAD/UNIT: SW/SE SEC:	-	RACTOR: Franks	*	ENVIRONMENTAL GWC-
EXCAVATION APPROX _23	FT. x 20 F	Г. х <u>5</u> FT.	DEEP. CUBIC	YARDAGE: 40
DISPOSAL FACILITY: Envi	rotech Lanofarm	BZ REMEDIA	TION METHO	D: Land farm
LAND USE:				RMATION:
FIELD NOTES & REMARK	(S: DIT LOCATED	ADDDDVIMATELY	aa:	7.20° COOM VELLEICAD
DEPTH TO GROUNDWATER: >160				
NMOCD RANKING SCORE: 10	_ NMOCD TPH CLOSURE	STD: 1,000 PPN	1	CHECK ONE :
SOIL AND EXCAVATION) DESCRIPTION:			_PIT ABANDONED _STEEL TANK INSTALLED
Approximately 40 gd was exertrated and transported to Envirotech's Landform # 2 for remediation. Maximum reasonable extent of excavation was reached at 5' (bedrock). Pit was sprayed with potassium permangularte BTEX results attached FIELD 418.1 CALCULATIONS TIME SAMPLE I.D. LAB NO: WEIGHT (g) ml. FREON DILUTION READING CALC. ppm				
SCALE	1420 Sidus	50		4 3 12
	1425 bottom 51	5.0	20	40 30 1200
O FT		OVIM		
PIT PERIME	TER	OVM RESULTS	PIT	PROFILE
1	SAMPL ID			
Emph 20 AST O	1 5:d4 2 Bolto 3 4 5		X- bottom SAM * - WAN SAMA	·
TRAVEL NOTES: CALLOUT:		ONSITE:		



Method 418.1 Analysis Log Total Petroleum Hydrocarbons

Date	19/06			Analyst	G. Crabt	re-e	
Location	CANDADO 2	0 A		Instrument	G. Crabto Infraci	41	
Job No.	03056- 040	-013					
Sample No.	Sample Description	Sample Wt. (g)	Volume Freon (mL)	Dilution Factor	Abs. Reading	TPH (mg/kg)	OVM (mg/kg)
1	Pit composition Sample	5.v	20	4	567	2268	176
					:		
			_				
	;						
		Infrared	Spectrophoto	ometer Calibr	ation		
	New Fred	on	-				
Date	Standards Prepare	ed					
Conc	Standard entration (mg/L)	Absorbance	·				
	100		_				
	200	218	_				
	500		-				
	1000		-				
I-CAL RF	•	_			C-CAL RF:		_
RSD:	extance Criteria: L'CAL E	%		%	Difference:	100/	_%



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Elm Ridge Resources

Project #:

03056-040-013

Sample No.:

1

Date Reported:

1/10/2006

Sample ID:

Composite sample of pit area

Date Sampled:

1/9/2006

Sample Matrix:

Soil

Date Analyzed:

1/9/2006

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

2,270.0

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Candado No. 20A

Instrument callibration checked against 200 ppm standard. Zeroed before each sample

Analyst

Review



Method 418.1 Analysis Log Total Petroleum Hydrocarbons

Date	1/13/06			Analyst	G. Crabt	TOL	
Location	CANDADO 20	-A		Instrument	G. Crabt	4	
Job No.	03056-040-0	13					•
Sample No.	Sample Description	Sample Wt. (g)	Volume Freon (mL)	Dilution Factor	Abs. Reading	TPH (mg/kg)	ovn
ì	composite sample of pit walls	5.0	20	4	3	12	1
2	5 point composite of Botton 05' Shale layer	5,0	20	40	4 30	1200	380
		Infrared Sp	ectrophotome	eter Calibratio	n		
	New Freon		-				
Date	Standards Prepared			-			
Cond	Standard centration (mg/L)	Absorbance					
	100		-				
	200	215	_				
	500		-				<u></u>
•	1000		-				_
I-CAL RF		. .		C-CAL RF:		_	
RSD:		_%	%	Difference:		_%	
QA/QC Acc	eptance Criteria: I-CAL RS	SD +/- 20%		C-Cal Difference	e +/- 10%		



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Elm Ridge Resources

Project #:

03056-040-013

Sample No.:

2

Date Reported:

1/16/2006

Sample ID:

Composite sample of pit walls

Date Sampled: 1/13/2006

Date Analyzed: 1/13/2006

Sample Matrix: Preservative:

Soil Cool

Analysis Needed:

1/13/2006 TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

ND

20.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Candado No. 20A

Instrument callibration checked against 200 ppm standard. Zeroed before each sample

Analyst

Review



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Elm Ridge Resources

Project #:

03056-040-013

Sample No.:

3

Date Reported:

1/16/2006

Sample ID:

Composite sample of pit bottom @ 5 Date Sampled: Date Analyzed: 1/13/2006 1/13/2006

Sample Matrix: Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

1,200.0

200.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Candado No. 20A

Instrument callibration checked against 200 ppm standard. Zeroed before each sample



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Elm Ridge Resources	Project #:	03056-040-013
Sample ID:	Candado 20A	Date Reported:	01-16-06
Laboratory Number:	35742	Date Sampled:	01-13-06
Chain of Custody:	15376	Date Received:	01-13-06
Sample Matrix:	Soil	Date Analyzed:	01-16-06
Preservative:	Cool	Date Extracted:	01-16-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	1.8	
Toluene	148	1.7	
Ethylbenzene	1,040	1.5	
p,m-Xylene	882	2.2	
o-Xylene	119	1.0	
Total BTEX	2,190		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Rio Arriba Country Bottom Composite @ 5'.

Analyst C. Ost

Mistine of Wasters Review