<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
1301-W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

office

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure  Is pit or below-grade tank covered by a "general plan"? Yes No   Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank						
Address: 3401 East 30 <sup>th</sup> Street, Farmington, New Mexico, 87402  Facility or well name: Lackey No. 1 API #: 300-	(505) 326-9841 e-mail address: <u>LH</u> 45071070000 U/L or Qtr/Qtr 36.62847 Longitude107.76352	<u>asely@br-inc.com</u> M Sec <u>26 T 28N R 9W</u> NAD: 1927/⊠ 1983.				
Pit  Type: Drilling   Production   Disposal    Workover   Emergency    Lined   Unlined    Liner type: Synthetic   Thicknessmil   Clay    Pit Volumebbl	Below-grade tank  Volume: 40 bbl Type of fluid: Produced Water  Construction material: Fiberglass  Double-walled, with leak detection? Yes If not,  No. Tank in place prior to Rule 50.	explain why not Carles Dr. 5				
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) ( 0 points) 20				
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) 0				
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) ( 0 points)				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite ☐ offsite ☐ If offsite, name of facility _ date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth belo (5) Attach soil sample results and a diagram of sample locations and excavat Additional Comments:	(3) Attach a general description of remedial action w ground surfaceft. and attach sample	n taken including remediation start date and end				
The soils tested clean and no soil remediation was required.						
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guidelines.  Date: 4/2c/cc  Printed Name/Title Mr. Ed Hasely, Environmental Advisor  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.	s [A], a general permit [I], or an (attached) alternation of the contents of t	ive OCD-approved plan				
Approval:  APR 2 7 2006  APR 2 7 2006  Date:						

						<del>~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~</del>	
CLIENT: Budington		ENV	IROTECH	I INC.		LOCATION I	VI:
Misouras			NTAL SCIENTISTS				
		FARMIN	U.S. HIGHWAY NCTON, NEW MEX ONE: (505) 632	CCO 87401		U.L.C.	ND:
FIELD REPOR	T:	CLOSU	RE V	ERIFIC	CATION	PAGE No:	1 of 1
LOCATION: NAME: Lackey WELL #: 1 PIT:  QUAD/UNIT: M SEC: 24 TWP: 28N RNG: 9W PM: NMPM CNTY: SJ ST: NM					DATE STARTED: 331 04		
QTR/FOOTAGE: 990'S 990'W CONTRACTOR: Buildy's Welding					ENVIRONMENTAL SPECIALIST:	ENVIRONMENTAL MPM	
EXCAVATION APPROX.	FT.	x F	T. x	FT. DE	EP. CUBIC	YARDAGE:	-0-
DISPOSAL FACILITY:							
LAND USE:							
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 94' FT. 355° FROM WELLHEAD.  DEPTH TO GROUNDWATER: 20 NEAREST WATER SOURCE: 0 NEAREST SURFACE WATER: 400 10							
NMOCD RANKING SCORE: 30	NMDC	D TPH CLOSUR	RE STD:	OO PPM		CHECK E	INE :
SOIL AND EXCAVATION	N DESC	RIPTION:				_PIT ABANDO	
						STEEL TAN	K INSTALLED
No signs of contemination present. No soil removed from site							
	TIME	SAMPLE I.D.		D 418.1 CAL		ILUTION READIN	0 0 0 0
SCALE	0939	3 below	1		20	1 0.007	
SCALE							70.0
O FT							
PIT PERIME	TER		OVM RESULT	9	PIT	PROFIL	E
		SAMP		EADSPACE (ppm)			· · · · · · · · · · · · · · · · · · ·
N BET	AST.	1 3' bu					
86 TO OT 10 2 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4							
F to 5							
Separati							
7 3 L x							
#		SAMPLE	AB SAMPL ANALYSIS	ES			
	. tal		,	· ·			
x= Sample point							
					x	<b>y</b>	
TRAVEL NOTES: ONSITE:							
CALLOUT:			Or	NOTIC:			****



## EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

**Burlington Resources** 

92115-046-029

Sample No.:

1

Date Reported: 3/3

3/31/2006

Sample ID:

Discrete, 3' Below BG Tank

Date Sampled: 3/3

3/31/2006

Sample Matrix:

Soil

Date Analyzed:

Project #:

3/31/2006

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

48.6

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Lackey No. 1

Analyst

Review



## **EPA METHOD 418.1 TOTAL PETROLEUM HYROCARBONS QUALITY ASSURANCE REPORT**

Client:

**Burlington Resources** 

Project #:

92115-046-029

Sample ID:

**QA/QC** 

Date Reported:

3/31/2006

**Laboratory Number:** 

01-24-TPH.QA/QC

Date Sampled: Date Analyzed: N/A 1/24/2005

Sample Matrix: Preservative:

Freon-113 N/A

Date Extracted:

1/24/2005

Condition:

N/A

Analysis Needed:

TPH

Calibration

I-Cal Date

C-Cal Date

I-Cal RF:

C-Cal RF: % Difference Accept. Range

05-22-04

1/24/2005

1,735

1,695

2.3% +/- 10%

Blank Conc. (mg/Kg)

Concentration

**Detection Limit** 

**TPH** 

ND

5.0

Duplicate Conc. (mg/Kg)

Sample

Duplicate

% Difference Accept. Range

**TPH** 

2,471

2,352

4.8%

+/- 30%

Spike Conc. (mg/Kg)

Sample

Spike Added

Spike Result

% Recovery Accept Range

**TPH** 

2,471

2,000

5,030

112.5% 80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis os Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Lackey No. 1

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865