District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

P	it or Below-Grade Tank Registration or Closure	
Is p	pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌	. 53

Type of action. Registration of a pice	or below-grade tank \(\subseteq\) Closure of a pit or below-grade	auc tair.
Operator: BP America Production Company Telephor	ne: (505)326-9200 e-mail address:	
Address: 200 Energy Ct, Farmington, NM 87401		
Facility or well name: HEATON 5 #3 API#: 3	30-045-10055 U/I or Otr/Otr M	Sec 32 T ZIAL RILLA
County: San Juan Latitude	Longitude	NAD: 1927 🗆 1983 🗀
	Longitude	NAD. 1927 🗆 1989 🗖
Surface Owner: Federal State Private Indian		
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	
Workover	Construction material:	-
Lined Unlined	Double-walled, with leak detection? Yes If no	ot, explain why not.
Liner type: Synthetic Thicknessmil Clay _		
Pit Volumebbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
mgn water elevation of ground water.)	100 feet or more	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)
water source, or less than 1000 feet from all other water sources.)		
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
inigation callats, another, and percentage and opinions are opinions and opinions are opinions and opinions and opinions and opinions are opinions and opinions and opinions and opinions are opinions are opinions and opinions are opinions a	1000 feet or more	(0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit'	s relationship to other equipment and tanks. (2) India	cate disposal location: (check the onsite box if
your are burying in place) onsite offsite If offsite, name of facility_		
remediation start date and end date. (4) Groundwater encountered: No 📑		
(5) Attach soil sample results and a diagram of sample locations and excava		15 15 17 10
Additional Comments:		
		DEO 2000
See Attached Documentation		DEC 2009
		ON PALAMED SA
		The state of the s
		2
		C. MEDENTE
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline		
		
Date:11/01/2005	111 0 10	
Printed Name/Title <u>Jeffrey C. Blagg, Agent</u> Signat	ture Jeffy C. Sligg	
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.	not relieve the operator of liability should the contents the operator of its responsibility for compliance with a	s of the pit or tank contaminate ground water or any other federal, state, or local laws and/or
Approval: DEPUTY CA & GAS INSPECTOR, DIST. & Printed Name/Title	Signature Brandon Tol	DEC 1 6 2005

	DIA	C ENCL	MEEDING	INC			
2.2			NEERING	•	LO	CATION NO	B11/3
CLIENT: BP	P.O. BOX	87, BLO (505) 632		, NM 874	1	OCR NO:	11134
FIELD REPORT	: PIT CL	OSURE	VERIF	CATIO	N PA	GE No:	/_ of/_
LOCATION: NAME: HEAT	500 L5	WELL#:	3 TYPE	5EP.	DAT	E STARTED: _	10/20/03
QUAD/UNIT: M SEC: 3Z				I ST: NM	DAT	TE FINISHED: _	
QTR/FOOTAGE: 9905/9	,				ENV	IRONMENTAL CIALIST:	NV
EXCAVATION APPROX							~ -
	017-2					CLOSEF	,
	Bin				_		MV
FIELD NOTES & REMAR			(IMATELY				
DEPTH TO GROUNDWATER: >15			>1000		JRFACE W	ATER:	000'
NMOCD RANKING SCORE:	NMOCD TPH	CLOSURE STD:	5000 P	PM			
SOU AND EVEAVATIO	N DECCRIPT	TON:		OVM CALIB. F	READ. =	53.7 ppm	
SOIL AND EXCAVATION	DIN DESCRIPT	ION.		OVM CALIB. C			
				TIME: 9:09			
SOIL TYPE SAND SILTY SAI	ND/SILT/SILTY(Yell BROWN		GRAVEL / OTHI				<i>)</i>
COHESION (ALL OTHERS): NON C					UK, GK	* 7	
CONSISTENCY (NON COHESIVE SO							
PLASTICITY (GLAYS): NON PLASTI				HIGHLY PLASTIC	C		
DENSITY (GOHESIVE CLAYS & SILT MOISTURE: DRY / SLIGHTLY MOIS	•						CLOSED
DISCOLORATION/STAINING OBSER				<i>.</i> L. 'Y			
HC ODOR DETECTED: YES NO E	XPLANATION - 4	PISCOWAZD	BEDROCK		SAMPE		
SAMPLE TYPE: (GRAB) COMPOSIT	E - # OF PTS. ~			,			
ADDITIONAL COMMENTS: COLL		FROM BE	DROCK SUR	FACE. BEDI	rock -	HHRD SI	UGHTLY
Borom	18足。			· · · · · · · · · · · · · · · · · · ·			
		FIE	LD 418.1 CALC	ULATIONS			
SCALE SAMP. TI	ME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTIO	NREADING	CALC. (ppm)
0 FT							
PIT PERIMET	ER AN				PIT	PROFIL	.E
			VM				
	wooden's RETAINING		DING				
	RETAIL	SAMPLE ID	FIELD HEADSPACE (ppm)				
&_'	. / (6)	1@ /0	276	_		4	
		2 @ 3 @		-			
T	FORMER	4 @					
8')	TANK OF	5 @		_			
	TANK	<u> </u>			OT E		0.5
10	T.B.N.				, ,	PPLICA	,646
wer /							
١	H :						
~ 5' ~	, 4 '	SAMPLE	AMPLES	_}			
B.6 8.	1.B.		VALYSIS TIME				
			× 80218) "	· .			
		BOTH	PASSED)	-			
P.D. = PIT DEPRESSION; B.G. = BELOV T.H. = TEST HOLE; ~ = APPROX.; T.B. =							
TRAVEL NOTES:	: 10/20/03-	mogs	ONOTE: 1	0/20/03	- 1000	`	
CALLOU!	. 10120102-		_ UNSITE:	0120105	- 1.014	<u> </u>	



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 10'	Date Reported:	10-22-03
Laboratory Number:	26936	Date Sampled:	10-20-03
Chain of Custody No:	11134	Date Received:	10-21-03
Sample Matrix:	Soil	Date Extracted:	10-21-03
Preservative:	Cool	Date Analyzed:	10-22-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.4	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	0.4	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Heaton LS #3 Separator Pit

Grab Sample.

Analyst C. Cerum

A history of Walters
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 10'	Date Reported:	10-22-03
Laboratory Number:	26936	Date Sampled:	10-20-03
Chain of Custody:	11134	Date Received:	10-21-03
Sample Matrix:	Soil	Date Analyzed:	10-22-03
Preservative:	Cool	Date Extracted:	10-21-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	7/0
Benzene	ND.	4.0	
Toluene	ND 13.3	1.8 1.7	
Ethylbenzene	48.9	1.5	
p,m-Xylene	167	2.2	
o-Xylene	235	1.0	
Total BTEX	464		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	94 %
	1,4-difluorobenzene	94 %
	Bromochlorobenzene	94 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Heeaton LS #3 Separator Pit Grab Sample.

Analyst P. Caller

/ Mustine m Walles
Review