## <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Avenue, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410

## State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure
Is nit or below-grade tank covered by a "general plan"? Yes No I

Operator: BP AMERICA PROD. CO. Telephone: (505)-326-9200 e-mail address:  Address: 200 ENERGY COURT. FARMINGTON. NM 87410  Facility or well name: FIELDS #4R								
Address: 200 ENERGY COURT. FARMINGTON. NM 87410  Facility or well name: FIELDS #4R  County: SAN JUAN Latitude 36.95958 Longitude 107.98963 NAD: 1927   1983   Surface Owner Federal   State   Private   Indian    Pit  Type: Drilling   Production   Disposal   DEHY/SEP   Deliver   Deliver   Disposal   DEHY/SEP   Deliver   Deliver   Disposal   DEHY/SEP   Deliver   Deliver								
Facility or well name: FIELDS #4R  API #: 30-045- 24501  U/L or Qtr/Qtr A Sec 28 T 32N R 11W  County: SAN JUAN  Latitude 36.95958  Longitude 107.98963  NAD: 1927								
County: SAN JUAN Latitude 36.95958 Longitude 107.98963 NAD: 1927 🗆 1983 🖂 Surface Owner Federal 🖾 State 🗆 Private 🗀 Indian 🗆  Pit Type: Drilling 🗆 Production 🗀 Disposal 🖾 DEHY/SEP Below-grade tank Volume: bbl—Type-of-fluid:								
Pit     Below-grade tank       Type: Drilling □ Production □ Disposal ☒ DEHY/SEP     Volume:bbl_Type-of-fluid: /								
Type: Drilling Production Disposal M DEHY/SEP Volume: bbl Type of fluid:								
Type: Drilling Production Disposal M DEHY/SEP Volume: bbl Type of fluid:								
Workover								
Lined Unlined STEEL TANK Double-walled, withheak detection? Yes I If the explain why not.								
Liner type: Synthetic Thicknessmil Clay								
Pit Volumebbl								
Depth to ground water (vertical distance from bottom of pit to seasonal  Less than 50 feet (20 points)								
high water elevation of ground water.)  50 feet or more, but less than 100 feet (10 points)								
100 feet or more (0 points)								
Wellhood protection area (Less than 200 fact from a private demostic Yes (20 points)								
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)								
Distance to surface water: (horizontal distance to all wetlands, playas,								
irrigation canals, ditches, and perennial and ephemeral watercourses.)								
Ranking Score (Total Points)								
If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if								
your are burying in place) onsite 🖾 offsite 🗀 If offsite, name of facility (3) Attach a general description of remedial action taken including								
remediation start date and end date. (4) Groundwater encountered: No 🛛 Yes 🗌 If yes, show depth below ground surfaceft. and attach sample results. (5)								
Attach soil sample results and a diagram of sample locations and excavations.								
Additional Comments: PIT LOCATED APPROXIMATELY 75 FT. N88W FROM WELL HEAD.								
PIT EXCAVATION: WIDTH N/Aft., LENGTH N/Aft., DEPTH N/Aft FFB 2008								
PIT REMEDIATION: CLOSE AS IS: ☑, LANDFARM: ☐, COMPOST: ☐, STOCKPILE: ☐, OTHER ☐ (explain)								
Cubic yards: N/A OIL COMS. DIV. S								
BEDROCK BOTTOM, NO TPH ANALYSIS CONDUCTED								
Win. Co.								
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank								
has been/will be constructed or closed according to NMOCD guidelines \( \subseteq \), a general permit \( \subseteq \), or an alternative OCD-approved plan \( \subseteq \).								
Date: 07/06/05								
PrintedName/Title Jeff Blagg - P.E. # 11607 Signature								
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or								
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or								
regulations.								
Approval: TATUTY ON & GAS INSPECTED, GET. (B)								
Approval:  Printed Name/Title  Signature  Signature  Signature  Signature								
Date:								

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199						LOCATION NO: B1566		
	(50	05) 632	-1199		000	SR NO:		
FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: _/_ of _/_								
LOCATION: NAME: FIELD				,			7/6/05	
QUAD/UNIT: A SEC: 28 TWP: 322 RNG: 11W PM: NM CNTY: 5T ST: NM ENVIRONMENTAL								
QTR/FOOTAGE: 1270 E NEINE CONTRACTOR: SIERRA (HAROLO) SPECIALIST:								
EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC YARDAGE: NA								
DISPOSAL FACILITY: ON-SITE REMEDIATION METHOD: CLOSE AS IS								
LAND USE: RANGE-BUM LEASE: NMO10989 FORMATION: MV								
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 75 FT. N88W FROM WELLHEAD.								
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1,000 NEAREST SURFACE WATER: >1,000								
NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5,000 PPM  OVM CALIB. READ. = 59.0 ppm								
						) = <u>59.0</u> ppm = 100 ppm <u>RF = 0.52</u>		
TIME: 9.50						(a)D/pm DATE: 7/5/05		
SOIL TYPE: SAND (SILTY SAND) SILT (SILTY CLAY) CLAY I GRAVEL I OTHER BEDROCK (SHRUE) SOIL COLOR: VERY PAUF ORDINET TO OLIVE GRAY BEDROCK - OLIVE GRAY								
SOIL COLOR: VERY POLE ORDINE TO OLIVE GRAY BEERFOCK - CLIVE GRAY  COHESION (ALL OTHERS): MON COHESIVE SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE								
CONSISTENCY (NON COHESIVE SOILS): LOOSE/FIRM DENSE / VERY DENSE								
PLASTICITY (CLAYS): NON PLASTIC / STIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC  DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRMX STIFP / VERY STIFF / HARD								
MOISTURE ORY SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED								
DISCOLORATION/STAINING OBSERVED: YES (NO EXPLANATION -								
HC ODOR DETECTED: YES (NO EXPLANATION								
ADDITIONAL COMMENTS: COLLECTED SAMPLE FROM SOIL ABOVE BERROCK, BEDROCK_VERY ARRU,								
BEOLOCK SLIGHTLY FRIABLE. NO THY ANKLYSIS WAS CONDUCTED.								
FIELD 418.1 CALCULATIONS								
SCALE SAMP. TIN	ME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)	
0 FT								
PIT PERIMET	ER 40				PITE	ROFIL	F	
		0	VM		1 1 1 1	I(O) IL		
REMAINING REMAINING	ρ.0;	READING						
RETAIL	70	SAMPLE ID	FIELD HEADSPACE (ppm)					
14'		@ 8'	0.0	$\exists$				
	3	@		_				
T	FORMER 4	@		$\exists$ $\sim$	OT A	PHICA	BLE	
	STEEL DC. 5	<u> </u>		$\exists$	,	•		
141	7 · 0 1							
	8.6.							
	LAB SAMPLES							
1.4.	ANALYSIS TIME							
N3.8.	iead =							
P.D. = PIT DEPRESSION; B.G. = BELO	N GRADE B - BELOW							
T.H. = TEST HOLE; ~ = APPROX.; T.B.	= TANK BOTTOM				· · · · · · · · · · · · · · · · · · ·			
TRAVEL NOTES: CALLOUT: ONSITE:								