			/	
Submit 3 Copies To Appropriate District	State of New Me	exico	/	Form C-103
Office <u>District I</u>	Energy, Minerals and Natu	ral Resources		Revised March 25, 1999
625 N. French Dr., Hobbs, NM 88240 District II	OH COMERNIA MICH		WELL API NO.	30-045-31619
301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION		5. Indicate Type	
District III 000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fran		STATE [	FEE X
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87	7303 9315 16 17	6. State Oil & G	as Lease No.
37505		3 1410 011 8		
DO NOT USE THIS FORM FOR PROPOSA DIFFERENT RESERVOIR. USE "APPLICA" PROPOSALS.) 1. Type of Well:	TION FOR PERMIT" (FORM/C3101) FO	ÎĞ BA <b>\C</b> K TO A Ğ	ا ا ا	Unit Agreement Name:
Oil Well Gas Well O  Name of Operator	ther \(\lambda_{\infty}\cdot\)	Con Con Con	8. Well No.	
TEXAKOMA	OIL AND GAS CORPORĂÇÎ@	N OF	o. Won ito.	2
3. Address of Operator	4	C. J. E. De De La	9. Pool name or \	
5400 LBJ FREEWAY, SUI 4. Well Location	TE 500, DALLAS, TEXAS 752	240	BASIN FRUITLA	AND COAL (71629)
4. Well Location				
Unit Letter I :	1964 feet from the SOUT	H line and	838 feet from	the <u>EAST</u> line
Section 21	Township 30N	Range 12W		County SAN JUAN
	10. Elevation (Show whether D. 5664' GR	R, RKB, RT, GR, etc	.)	
11 Check Ar	opropriate Box to Indicate N	lature of Notice.	Report or Other	Data
NOTICE OF INT			SEQUENT RE	
	PLUG AND ABANDON	REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRI	LLING OPNS.	PLUG AND
PULL OR ALTER CASING	MULTIPLE	CASING TEST AN	ND 🗆	ABANDONMENT
	COMPLETION	CEMENT JOB	olete Drilling Operat	tions Log and
OTHER:			and Cement Produ	
<ol><li>Describe proposed or completed starting any proposed work). SEE recompilation.</li></ol>				
THIS WELL DRILLED AHEAD BE THE ON 5-02-03. RAN TRIPLE CO THE CASING TO 1976' KB WITH O THE ON BOTTOM 20 JTS. AMERICAN THE CEMENT W/2% SODIUM METAS THE CEMENT W/2% SODIUM METAS THE COLOR OF THE COLOR THE COLOR OF THE COLOR THE COLOR OF THE COLOR THE COLOR OF THE COLOR THE COLOR OF THE COLOR OF THE COLOR THE COLOR OF THE COLOR OF TH	MBINATION LOG SUITE TO CASING SHOE ON BOTTOM A I ENERGY CEMENTED CASIN SILICATE W/0.25#/SK FLOCES SKS OF CLS B CEMENT W/2% LD, DISPLACED CEMENT WI D FLOAT HELD OK, HAD 6 I I, INSTALLED TUBINGHEAD	LTD 1979' KB. RAND INSERT FLOANG WITH 10 BW PLE W/3#/SK GILSO CACL2 W/0.25#/STH 31 BW AND PEBBL OF GOOD CEAND RELEASED	AN 44 JOINTS OF AT AT 1931' KB V REFLUSH FOLLO ONITE, MIXED A SK FLOCELE W/3 RESSURE TO 600' EMENT CIRCULA RIG 1:00 P.M. 0:	F NEW 4"/2" 10.5 PPF J-5 WITH 10 CENTRALIZER: DWED BY 180 SKS CLS I AT 12.5 PPG, YIELD 2.0 #/SK GILSONITE, MIXEI PSIG, BUMPED PLUG A' TED TO PIT. SET SLIP
hereby certify that the info <del>rmat</del> ion at SIGNATURE	bove is true and complete to the b	pest of my knowledge DRILLING MAY		OATE <u>05-08-2003</u>