UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

	Sundry Notices and Reports on Wells					
	Sundry Notices and Reports on Wens	2006 JUN 22	<u> </u>	2	<u> 26</u>	
		p F C	EIVED	}	5.	Lease Number NMSF-079491
١.	Type of Well GAS	070 FARM			} ∕6.	If Indian, All. or Tribe Name
2.	Name of Operator	A TOWN TO THE REAL PROPERTY OF THE PARTY OF	TO A	<u>,</u>	7.	Unit Agreement Name
	BURLINGTON	JUN 2001	8	Ž.		San Juan 27-5 Unit
	RESOURCES OIL & GAS COMPANY LP	SOR	<u> -</u>	~*\ ~}	8.	Well Name & Number
3.	Address & Phone No. of Operator	CE DIST 8	My c	イリ id		San Juan 27-5 Unit #102P
_	PO Box 4289, Farmington, NM 87499 (505) 326-9700	Shi	697	/ 	9.	API Well No.
4.	Location of Well, Footage, Sec., T, R, M	द्श शामि	مير والم			30-039-29827
4.	Sec., TN, RW, NMPM				10.	Field and Pool
	Unit N (SESW) 1085' FSL & 1800' FWL, Sec. 12, T27N R5W NMPM			Blanco Mesaverde/ Basin Dakota		
	CIME IX ((525 V) 1865 1 52 W 2895 1 1 12, 121				11.	County and State Rio Arriba Co., NM
5/2 523 356	Describe Proposed or Completed Operations 9/06 MIRU Aztec #673. NU BOPE. PT csg to 600psi for 30min 60'. Intermediate TD reached 6/8/06. Circulate hole. 6/12/06 RI 52'. 1 [™] Stage cmt: Preflush w/10bbls gel H 2O, 2bbls FW. Pum 61 to 15 to 16	H w/122jts of 7" 23# ip 19sxs(56cu-10bbls)	J55 ST& prem lite	zC csį e cmt	g & set w/3% (@5226', DV tool @ CaCl2, .25pps Cell-
.4% w/7 sta; tail too 6/1 late 5bl .25 plu PT	lake. 5pps LCM1, .4%FL-52, .4%SMS. Lead in w/169sxs(360c FL52, .4% SMS. Tail w/90sxs (124cu-22bbls)Type 3 cmt w/160bbls FW and 134bbls mud. Bump plug from 720# to 975#. Oges. 2nd Stage Preflush 10bbls FW, 10bbls mud, 10bbls FW. Pu w/500sxs(1065u-190bbls)prem lite same additives as 1sd stage. I from 1013# to 2570#. Plug down @ 0047hrs. Circulated 100b 3/06 RIH 6.250" bit. Tagged DV tool & D/O, unload hole. D/O d hole. RIH w/4 ½" 205jts 11.6# L80 LT&C csg set @8487'. Fols)scavenger Prem lite w/.3% CD32, .25pps Cell-o-flake, 6.25pps Cell-o-Flake, .3%CD32, 6.25pps LCM1, 1%FL52. Drop plg w/1150psi. Plug down @ 1101hrs 6/19/06. WOC ND BOPE. will be conducted by completing rig.	% CaCl2, .25pps Cellipen stage tool. Circula mp 19sxs(56cu-10bbl Drop plug and displabls to reserve pit. ND Float collar drill aheapps LCM1, 1%FL52. Jug and displaced w/12	o-Flake tte 10bbl s)prem liced w/14 BOPE. ad to TD m. wash, Tail w/2: 52bbls F	e, .2% Is to reite sar 40bbls NU se 8499 , 2bbl 34sxs W w/2	FL52. esserve pre addition " s FW. Bection " ction TD res FW. F 463cu- 25# sug	Drop plug and displace bit. Circulate between tive as first stage. Pump sump plug and close DV B". PT csg 1500# 30mins, OK eached 6/17/06. Circu-Pumped cmt w/9sxs(28cu-82bbls)prem lite cmt w/ sar in 1st 10bbls. Bump
14	. I hereby certify that the foregoing is true and correct.					
Sig	ned tymanda Sahah	Amanda Sanche	z_ Title	Regu	latory	Analyst Date <u>6/22/06</u>
						-ACCEPTED FOR PECCOL
AP	ris space for Federal or State Office use) PROVED BYTitle	·				Date JUN 2 6 2006
CC Title the U	NDITION OF APPROVAL, if any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any departness of the states any false. Fictifious or fraudulent statements of teptesentations as to any matter within it	tment or agency of s jurisdiction.				FARMINGTON RELOOFFICE