Description	Submit 3 Copies To Appropriate District	State of New Me	xico	Form C-103
MELL AFI NO.	Office District I	Energy, Minerals and Natu	ral Resources	
1301 W. Chand Ave., Article, NM 87210 1220 South St., Francis Dr. Santa F.p., NM 87305 SubDRY NOTICES AND REPORTS ON WF6.68 Santa F.p., NM 87305 SubDRY NOTICES AND REPORTS ON WF6.68 SubDRY NOTICES AND REPORTS ON	1625 N. French Dr., Hobbs, NM 88240		· ·	
1220 South St. Francis Dr. Santa Fe, NM 87410 Santa Fe, NM 8750.5 Santa Fe, NM 8750.5 Santa Fe, NM 8750.5 Santa Fe, NM 8750.5 SunDR NOTICES AND REPORTS ON WELLS SunDR NOTICES AND REPORTS ON WELLS SunDR NOTICES AND REPORTS ON WELLS SunDR NOTICES AND REPORTS ON WELL OR TO DEPERSOR WELL OF A DEPERSO		OIL CONSERVATION		
1000 Rio Braco Rd., Artic. NM 87410 Santia Fe, NM 87505 G. State Oil & Gas Lease No.				
200 St. Pances Dr. Samte Fe. NM 200 St. Pances Dr. Sundry NOTICES AND REPORTS ON WELLS 200 St. Pances Name of Unit Agreement Name 200 St. Pances Name of Operator 200 St. Pances Name of Unit Agreement Name 200 St. Pances Name of Operator 200 St. Pances Name of Oper	1000 Rio Brazos Rd., Aztec, NM 87410			
SUNDRY NOTICES AND REPORTS ON WEALS CO NOT USE THIS FORM NOR PRODOXALS TO DRILL OR TO DEFENSION THE		Sama re, inivi o	6. S	tate Oil & Gas Lease No.
SUNDRY NOTTICE OF INTENTION TO: PERFORMAND REMOVED AND REPORTS ON WEEKE THE DESCRIPTION OF THE REMOVED AND REPORTS ON THE REMOVED AND REPORTS AS TO REMOVE THE RESERVOR. USE "APPLICATION FOR FERMIT" (FORM 4301) FOND THE REMOVED AND REMOVED AND THE REMOVE		· ·	300000	
1. Type of Well: Oil Well Gas Well Other Company Northern Company	SUNDRY NOTIO (DO NOT USE THIS FORM FOR PROPOS, DIFFERENT RESERVOIR. USE "APPLICA"	CES AND REPORTS ON WELLS ALS TO DRILL OR TO DEEPEN OR PLU ATION FOR PERMIT" (FORM (£101) FO	7. L UG BACK TO A PED OR MUCH 2006	
2. Name of Operator BASIN MINERALS OPERATING CO. 3. Address of Operator c'o Walsh Engineering 7415 East Main Street, Farmington, NM 87402 4. Well Location Unit Letter E. 2425' feet from the NORTH line and 740' feet from the West line Section 27 Township 31M Range 11W NMPM County SAN JUAN 11. Elevation (Show whether DR, RKB, RT, GR, etc.) S764' GR Pit Upe Depth to Groundwater Distance from nearest fresh water well bistance from nearest surface water Pit Liner Talckness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A PULL OR ALTER CASING MULTIPLE COMPL COMPL COMPLETOR COMP			SECTION 8 V	Vell Number 200
3. Address of Operator Co Walsh Engineering T415 East Main Street, Farmington, NM 87402 4. Well Location Unit Letter E 2425' feet from the NORTH line and 740' feet from the West line Section 27 Township 31N Range 11W NMPM County SAN JUAN 11. Elevation (Show whether DR, RKB, RT, GR, etc.)	1. Type of Well: Oil Well []	Jas Well 🔯 Other	The state of the s	
3. Address of Operator Co Walsh Engineering T415 East Main Street, Farmington, NM 87402 4. Well Location Unit Letter E 2425' feet from the NORTH line and 740' feet from the West line Section 27 Township 31N Range 11W NMPM County SAN JUAN 11. Elevation (Show whether DR, RKB, RT, GR, etc.)	2. Name of Operator BASIN MIN	IERALS OPERATING CO.	1 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	
7415 East Main Street, Farmington, NM 87402	3 Address of Operator c/o Walsh	Engineering ((a) (b) 10.	
4. Well Location Unit Letter E 2425' feet from the NORTH line and 740' feet from the West line Section 27 Township 31N Range 11W NMPM County SAN JUAN 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 5764' GR Pit Upe Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil			AZ 5	
Unit Letter E 2425' feet from the NORTH line and 740' feet from the West line Section 27 Township 31N Range 11W NMPM County SAN JUAN 11. Elevation (Show whether DR, RRB, RT, GR, etc.) 5764' GR Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: null Below-Grade Tank Application Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: null Below-Grade Tank: Volume bis: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PULL OR ALTERING CASING CASING/GEMENT JOB CASING/GEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 107/12/06 Spud 8-3/4" surface hole. Drilled to 125'. Ran 3 jts (118.45') of 7", 23#, LS, LT&C new casing and set at 124' KB. Cemented with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and Va#/sk. Celloflake. Returned 5 bbls of cement to the surface. 107/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 107/16/06 TD 6 Va* hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5%/sk gildonite, and Va #/sk celloflake, followed with 200 sx (118 cu. ft) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. 107/16/06 TD 6 Va* hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (418 cu. ft) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate			Carried Car	
Section 27 Township 31N Range 11W NMPM County SAN JUAN		C.C. d. NORTH !	##ADD ## 17 17 17 17 17 17 17 17 17 17 17 17 17	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
S764 GR Pit or Below-grade Tank Application or Choure Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest fresh water well Distance from nearest surface water Distance from nearest fresh water well Distance from nearest surface water Distance from nearest surface water Distance from nearest surface water Distance from nearest surface nearest parts Distance from nearest surface water Distance from nearest surface nearest parts Datte Distance from nearest surface water Distance from nearest surface water Distance from nearest surface water Datte	Section 27 Townsh	<u> </u>	<u> </u>	SAN JUAN
Pit type Depth to Groundwater Distance from nearest fresh water well bbs; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB COMMENCE DRILLING OPNS. PAND A	The second second second second second		, RKB, RT, GR, etc.)	
Distance from nearest surface water	TOTAL TOTAL			
Relow-Grade Tank: Volume bbls: Coastruction Material	Pit or Below-grade Tank Application or			ļ
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB PAND A	Pit typeDepth to Groundwa	terDistance from nearest fresh v	vater well Distance fr	om nearest surface water
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB PAND A	Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Construct	ion Material
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 207/12/06 Spud 8-3/4" surface hole. Drilled to 125'. Ran 3 jts (118.45') of 7", 23#, LS, LT&C new casing and set at 124' KB. Cemented with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and ½#/sk. Celloflake. Returned 5 bbls of cement to the surface. 207/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 207/16/06 TD 6 ½" hole at 2525' KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' CB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. 208	12 Charle A	nnronriate Poy to Indicate N	lature of Notice Desc	ert or Other Data
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUL OR ALTER ASANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: TOTHER:	12. Check A	ppropriate box to mulcate N	ature of Notice, Repo	at of Other Data
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUL OR ALTER ASANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: TOTHER:	NOTICE OF IN	TENTION TO:	SUBSEQ	UENT REPORT OF:
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CA			1	
OTHER: OTHER: OT		- -		
OTHER: OTHER:			ì	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 17/12/06 Spud 8-3/4" surface hole. Drilled to 125'. Ran 3 jts (118.45') of 7", 23#, LS, LT&C new casing and set at 124' KB. Cemented with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl₂ and ¼#/sk. Celloflake. Returned 5 bbls of cement to the surface. 17/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 17/16/06 TD 6 ¼" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' 18. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ¼ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. 19				
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 17/12/06 Spud 8-3/4" surface hole. Drilled to 125'. Ran 3 jts (118.45') of 7", 23#, LS, LT&C new casing and set at 124' KB. Cemented with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl₂ and ¼#/sk. Celloflake. Returned 5 bbls of cement to the surface. 17/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 17/16/06 TD 6 ¼" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gil s onite, and ¼ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs.				
27/12/06 Spud 8-3/4" surface hole. Drilled to 125'. Ran 3 jts (118.45') of 7", 23#, LS, LT&C new casing and set at 124' KB. Cemented with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and ½#/sk. Celloflake. Returned 5 bbls of cement to the surface. 27/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 27/16/06 TD 6 ½" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ½ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. **Report of the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowerade tank has been/will be constructed or closed according to NMOCD guidelines \(\sigma, \text{ ageneral permit} \) or an (attached) alternative OCD-approved plan \(\sigma. \text{ SIGNATURE } \) **TITLE AGENT / ENGINEER DATE 07/18/06 DATE OT/18/06 **TITLE SUPERVISOR DISTRICT # 3 **DATE OT/18/06 DATE	of starting any proposed wor			
with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and 1/4#/sk. Celloflake. Returned 5 bbls of cement to the surface. 27/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 27/16/06 TD 6 1/2" hole at 2525 KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and 1/4 #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Report PT	•			
with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and 1/4#/sk. Celloflake. Returned 5 bbls of cement to the surface. 27/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 27/16/06 TD 6 1/2" hole at 2525 KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and 1/4 #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Report PT x To mest report Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-trade tank has been/will be constructed or closed according to NMOCD guidelines \(\text{\t				
with 80 sx (94 cu.ft.) of Type 5 cement with 3% CaCl ₂ and 1/4#/sk. Celloflake. Returned 5 bbls of cement to the surface. 27/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 27/16/06 TD 6 1/2" hole at 2525 KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and 1/4 #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Report PT x To mest report Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-trade tank has been/will be constructed or closed according to NMOCD guidelines \(\text{\t		·		
27/13/06 Nippled up the BOP. Pressure tested the casing to 1000 psi. 27/16/06 TD 6 1/4" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gil g onite, and 1/4 #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Compart PT x TOC mest report				
D7/16/06 TD 6 ¼" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ¼ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Compared For Y TO Compared For State Use Only Compared For State Use Only	with 80 sx (94 cu.ft.) of Type 5 ceme	nt with 3% $CaCl_2$ and $\frac{1}{4}$ #/sk. Cello	otlake. Returned 5 bbls of	cement to the surface.
D7/16/06 TD 6 ¼" hole at 2525'KB. Ran 60 jts of 4-1/2", 10.5#, J-55, ST&C casing (2502.64') & set @ 2508'. Float collar is at 2486' KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ¼ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Compared For Y TO Compared For State Use Only Compared For State Use Only	07/12/06 Nimalal da BOD B			
APPROVED BY: With 5 (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ½ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Left PT + TOC mest report Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☑, a general permit ☐ or an (attached) alternative OCD-approved plan ☐. SIGNATURE Task C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 For State Use Only APPROVED BY: Mach Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 TITLE SUPERVISOR DISTRICT # 3 DATE DATE	1//13/06 Nippled up the BOP. Pressi	ure tested the casing to 1000 psi.		
KB. Cemented with 200 sx (412 cu. ft.) of Type 5, with 2% sodium metasillicate, 5#/sk gilsonite, and ½ #/sk celloflake, followed with 100 sx (118 cu. ft.) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Compart PT y TOC must report	07/16/06 TD 6 1/2 hala at 25252 PD	Pan 60 its of 4 1/2" 10 5# 1 55	STRC agains (2502 642)	Pr got @ 25092 Elect goller in at 24963
100 sx (118 cu. ft) of Type 5, with 5 #/sk gilsonite and 1/4 #/sk celloflake. Did not circulate cement to surface. Plan to run CBL along with cased hole logs. Compart PT + TOC next report				
APPROVED BY: Appart PT + To C mest report				
Report PT + TC mest report Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below- grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE Past C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: Check No. 505-327-4892 TITLE SUPERVISOR DISTRICT # 3 DATE DATE		misk gusonne and 1/4 #/SK cellotta	ike. Dia noi circulate cem	ent to surface. Plan to run CBL along
hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE SIGNATURE AGENT / ENGINEER DATE 07/18/06 Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: SUPERVISOR DISTRICT # 3 DATE DATE			•	
hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE AGENT / ENGINEER DATE 07/18/06 Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: SUPERVISOR DISTRICT # 3 DATE DATE	1 . 1-	tan met har	ast	
hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE AGENT / ENGINEER DATE 07/18/06 Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: SUPERVISOR DISTRICT # 3 DATE DATE	Kenart Pl	x 100 men rep	ou	
APPROVED BY: Constructed or closed according to NMOCD guidelines Agent permit or an (attached) alternative OCD-approved plan SIGNATURE SIGNATURE AGENT E.	22/1000			
APPROVED BY: Constructed or closed according to NMOCD guidelines A general permit or an (attached) alternative OCD-approved plan SIGNATURE SIGNATURE AGENT / ENGINEER DATE 07/18/06				
TITLE AGENT / ENGINEER DATE 07/18/06 Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: SUPERVISOR DISTRICT # 3 DATE JUL 2 5 2006	I hereby certify that the information a	bove is true and complete to the b	est of my knowledge and	belief. I further certify that any pit or below-
Type or print name Paul C. Thompson, P.E. E-mail address: paul@walsheng.net Telephone No. 505-327-4892 APPROVED BY: SUPERVISOR DISTRICT # 3 DATE DATE	grade tank has been/will be constructed or o	closed according to NMOCD guidelines [凶, a general permit ∐ or an (attached) alternative OCD-approved plan .
APPROVED BY: Chech TITLE SUPERVISOR DISTRICT #3 DATE JUL 25 2006	SIGNATURE Paul C. Tu	TITLE	AGENT / ENGINEER	DATE 07/18/06
APPROVED BY: Much TITLE SUPERVISOR DISTRICT #3 DATE JUL 25 2008 Conditions of Approval (if any):	Type or print name Paul C. Thomps For State Use Only	on, P.E. E-mail address:	paul@walsheng.net	
Conditions of Approval (If any):	APPROVED BY: Junh 7	TITLE S	SUPERVISOR DISTRIC	T#3 DATE JUL 25 2008
	Conditions of Approval (if any):			
			<u>}</u>	