District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

	nk covered by a "general plan"? Yes 🔀 Nor below-grade tank 🗌 Closure of a pit or below-g		
Operator: BP America Production Company Telepho Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: Storey A # 2 API #: 3	30045 <i>36790</i> U/L or Qtr/Qtr_A	- Sec 35 T32N R 11W	
County: San Juan Latitude	Longitude	NAD: 1927	
Surface Owner: Federal State Private Indian		(1 10 10 10 10 10 10 10 10 10 10 10 10 1	
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes	not, explain why not CONS. DIV.	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)	
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite If offsite, name of facility (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No Yes If yes, show depth below ground surface ft. and attach sample results.			
Additional Comments:			
See Attached Documentation			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .			
Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg. Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.			
Approval: EST CL & GAS INSPECTICA, DIST. (M) Printed Name/Title	Signature BM BM	DEC 1 9 2005	

BLAGG ENGINEERING, P.O. BOX 87, BLOOMFIELD, (505) 632-1199				
FIELD REPORT: PIT CLOSURE VERIFIC	CATION PAGE No:/_ of/			
LOCATION: NAME: STOREY A WELL #: 2 TYPE:	BOW DATE STARTED: 8/20/07			
QUAD/UNIT: A SEC: 35 TWP: 32N RNG: 110 PM: NM CNT				
QTR/FOOTAGE: 1040 1/800 E NEW CONTRACTOR: HIGH DESER				
EXCAVATION APPROX. NA FT. x NA FT. x NA FT. D	DEEP. CUBIC YARDAGE: NA			
DISPOSAL FACILITY: ON-SITE REMEDIA				
LAND USE: RANGE - BLM LEASE: NM 0 48	FORMATION: PC			
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY				
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000				
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM	DVM CALIB. READ. 53.5 ppm			
SOIL AND EXCAVATION	OVM CALIB. GAS = /PO ppm RF = 0.52			
DESCRIPTION:	TIME: 8:05 ampm DATE: 8/20/07			
SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRASOIL COLOR: PRIE YELL BROWN TO BLACK (NEAR BEDROOK)	AVEL / OTHER <u>BEDROCK (SADOSTONE)</u> BEDROCK - BLACK			
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COH	HESIVE / HIGHLY COHESIVE			
CONSISTENCY (NON COHESIVE SOILS): COST / CIRD / DENSE / VERY PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE				
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY	STIFF / HARD (CLOSED)			
MOISTURE: DRY / SLIGHTLY MOIST / WET / SATURATED / SI DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION - 5016	UPER SATURATED (0.5 ABOUT BEDROCK) & BEDROCK SURFACE			
HC ODOR DETECTED: YES / NO EXPLANATION - TEST HOVE & OUT				
SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS SOIL ABOUT	E BEDROCIZ,			
BEDROCK BOTTOM				
	FIELD 418.1 CALCULATIONS			
SCALE SAMP. TIME SAMPLE I.D. LAB NO: WEIGHT (g)	ml. FREON DILUTION READING CALC. ppm			
O FT				
PIT PERIMETER 12	PIT PROFILE			
OVM OVM	FII PROFILE			
RESULTS				
SAMPLE FIELD HEADSPACE PID (ppm) 1 @ 5 5 4 4				
5 6				
3 @ 4 @				
5 e	NOT APPLICABLE			
10				
MELL HEAD				
LAB SAMPLES SAMPLE ANALYSIS THE				
7.H. Des TPH (8015B) 1150				
B.6. ~ 1.5 " GTEX(80Z18) "1				
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE				
T.H. = TEST HOLE; ~ = APPROX.; B = BELOW				
I I KAYEL NOIES: I				
TRAVEL NOTES: CALLOUT: 8/20/02 - MORN - ONSITE:	8/20/07 - MORN.			

revised: 02/27/02

bei1005C.skd



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 5'	Date Reported:	08-26-02
Laboratory Number:	23617	Date Sampled:	08-20-02
Chain of Custody No:	10086	Date Received:	08-20-02
Sample Matrix:	Soil	Date Extracted:	08-21-02
Preservative:	Cool	Date Analyzed:	08-25-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	9.6	0.2
Diesel Range (C10 - C28)	226	0.1
Total Petroleum Hydrocarbons	236	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Storey A #2 Blow Pit.

Mister Moeters
Analyst

Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 5'	Date Reported:	08-26-02
Laboratory Number:	23617	Date Sampled:	08-20-02
Chain of Custody:	10086	Date Received:	08-20-02
Sample Matrix:	Soil	Date Analyzed:	08-23-02
Preservative:	Cool	Date Extracted:	08-21-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
	44.0	
Benzene	41.9	1.8
Toluene	133	1.7
Ethylbenzene	1,130	1.5
p,m-Xylene	866	2.2
o-Xylene	1,073	1.0
Total BTEX	3,240	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99 %
	1,4-difluorobenzene	99 %
	Bromochlorobenzene	99 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Storey A #2 Blow Pit.

Mister of Walters

Review